



Compiled by:-

SIGTUNA CONSULTANCY LIMITED

Registered and Licensed EIA/EA Firm of Experts Reg. No.9582 P.O. BOX 569-80100 MOMBASA

E-mail: <u>sigtunaconsultancy@yahoo.com</u>; <u>office@sigtunaconsultancy.org</u>
Tel: 254 0722 493 772



MOMBASA CEMENT LTD

P.O BOX 83594-80100 MOMBASA

Email:csl@nyumba.com

PROPOSED MINING OF LIMESTONE AT ROKA AND MATSANGONI LOCATIONS, KILIFI NORTH SUB-COUNTY, KILIFI COUNTY

Geographical coordinates 3° 26′ 0″ South, 39° 54′ 0″ East

ENVIRONMENTAL IMPACT ASSESSMENT STUDY

Compiled by:SIGTUNA CONSULTANCY LIMITED

Registered and Licensed EIA/EA Firm of Experts Reg. No.9582

Signed by:

Philip Manyi Omenge
EIA/EA Lead Expert Reg. No. 1559
Team Leader
Sigtuna Consultancy Limited EIA/EA Firm of Experts

MOMBASA CEMENT LTD

P.O BOX 83594-80100 MOMBASA

Email:csl@nyumba.com

PROPOSED MINING OF LIMESTONE AT ROKA AND MATSANGONI LOCATIONS, KILIFI NORTH SUB-COUNTY, KILIFI COUNTY Geographical coordinates 3° 26' 0" South, 39° 54' 0" East

ENVIRONMENTAL IMPACT ASSESSMENT STUDY

Submitted by:MOMBASA CEMENT LIMITED
Proponent

MR. HASMUKH PATEL

<u>DIRECTOR</u>

MOMBASA CEMENT LIMITED

EXECUTIVE SUMMARY

This report presents findings of an Environmental Impact Assessment Study for proposed mining of coral limestone to be carried out by Mombasa Cement Limited. The proposed project will be carried out on 116 pieces of land located in Roka and Matsangoni Locations of Kilifi County GPS location 3° 26′ 0″ South, 39° 54′ 0″ East. The Environmental Impact Assessment Study and report was prepared as provided for in Legal Notice No. 31 and 32 of 2019, section 58 (2) of the Environmental Management and Coordination 1999 (Amended) Cap 387 and the Environmental (Impact Assessment and Audit Regulations), 2003.

Objective of proposed project

The objective of the proposed project is to mine coral limestone and transport the mined limestone from the mine to Mombasa Cement Limited Factory at Vipingo.

Scope of the proposed project

The proposed project will cover fencing and securing the proposed project site, construction of quarry camp and associated infrastructure, installation of weighbridge, mobilization of quarry equipment and machinery to site, actual open cast quarrying activities to recover coral limestone, haulage of the recovered coral limestone from site to Vipingo, continuous rehabilitation of disused quarry pits, demobilization of quarrying equipment, decommissioning of all quarry activities and site rehabilitation.

Environmental condition

There is considerable biodiversity within the proposed project site such as trees, shrubs, herbs, grasses and sedge and fauna such as reptiles and amphibians, invertebrate, and avifauna. Within the immediate neighbourhood of the proposed project site there are both on going and abandoned hand-cut and machine cut coral lime quarry pits. Also in some plots of the proposed project site and in the immediate neighborhood there are hand dug wells. Some of the plots of the proposed project site are adjacent to local schools while some access roads to some of the proposed project site plots are pass at the periphery of some of the school compounds.

Potential impacts of the proposed project

A summary of potential positive social impacts likely be realized from the proposed project include:-

- ✓ Employment opportunities
- ✓ Support of existing local businesses
- ✓ Businesses spinoffs
- ✓ Support and development of local institutions
- ✓ Skill enhancement and technological transfer
- ✓ Elaborate corporate social responsibility projects

Proposed enhancement measures of potential positive social impacts

Potential positive social impacts	Proposed enhancement measures
Employment	- Local people from the project area to be given first priority to benefit
opportunities	in direct employment opportunities.
	- There should be no sourcing of unskilled or semi-skilled labour force
	from outside the project area
	- Local youths, both male and female and local women who form the
	bulk of local labour force to be given utmost priority when sourcing
	quarry labour force
	- Both male and female to be considered in allocating employment
	slots for each gender when sourcing labour force.
	- Maintain records of employees with gender and locality of employees
	working at the quarry site to ensure the ratios are maintained.
Support of	- Local business community to position themselves strategically to be
existing local	able to provide required services to the project by making required
businesses	investment prior and during the project period.
Businesses	- Local youths of both gender and women who will benefit from direct
spinoffs	and indirect employment opportunities to invest part of their earnings
	in starting small businesses locally or inject more capital to their
	already existing businesses to scale up them up
Support and	- Local leadership to priorities and communicate to the proponent local
development of	institutions that will require developmental support.
local institutions	- Local primary and secondary schools which can be identified as most

Potential	Proposed enhancement measures
positive social	
impacts	
	disadvantaged in terms of infrastructure development to be among
	those to be prioritized for support and development
Skill	- The proponent to provide opportunities for internship to enhance skill
enhancement and technological	development
transfer	- The proponent to provide for student attachment opportunities from
	learners of local tertiary institutions
Elaborate	- The local community leadership to liaise with the proponent to tap
corporate social	into the proponent's corporate social responsibility programme for
responsibility	the locality for maximum possible benefit.
projects	

Summary of potential negative social impacts from the proposed project may include:-

- ✓ Diminishing/ reduced local ground water resources
- ✓ Labour influx
- ✓ Traffic and Public Safety from trucks along access road
- ✓ Ponding risks resulting spread of malaria from increased breeding of mosquitoes
- ✓ Injuries and accidents
- ✓ HIV and AIDS and other communicable diseases
- ✓ Injuries and accidents
- ✓ Alteration of local aesthetics

Proposed mitigation measures of potential negative socio impacts

Potential negative	Proposed mitigation measures	
impact		
Reduced	- To increase local aquifer recharge maintain pockets of vegetation at	
availability of	the project area and support tree planting activities in public utility	
local ground water	areas outside the project site but within the project catchment	
in the area for	- Depth of limestone mining to be far above the local aquifer and a	
community use	way from any existing hand dug well and or borehole	
	- Existing hand dug well and or boreholes to be maintained and	
	rehabilitated to ensure improved water yield	

Potential negative impact	Proposed mitigation measures
Labour influx	- The proponent to source required labour locally unless expatriates
	who are not available locally
	- The labour to be sourced locally to include women and youth of
	both gender
	- Numbers of women employed in the quarry site to be monitored to
	ensure they remain proportionate to those of their male counterparts.
Traffic and Public	- The proponents to ensure all trucks collecting mined coral limestone
Safety	from the quarry or delivering materials and equipment to the quarry
	are mechanically sound, serviceable and meet all the traffic act requirements.
	- Drivers driving the trucks to observe the highway code, be
	experienced and licensed to drive such trucks
	- Proponent to liaise with the County Government of Kilifi and the
	National Government to request for expansion, upgrading and or
	maintenance of key access roads that will be used to meet required
	needs.
	- Appropriate safety signs including speed pumps to be erected along
	the said access roads.
	- Local community to be sensitised on the increased traffic use of the
	access road and the need for the community to be vigilant and
	exercise of safety precaution when using the said access roads
Ponding risks	- All quarry pits to be adequately drained to ensure no water stagnates
resulting spread of	when it rainsProponent to check all active and disused quarry pits to ensure no
malaria	water stagnates.
	- All disused quarry pits to be backfilled and rehabilitated as soon as recovery of limestone is complete
Injuries and	- The quarry to be safely secured and fenced with a clear entry and
accidents	exit gates that are manned.
	- All active quarry pits to be clearly feasibly marked and manned.
	- There should be no unauthorized access to the quarry pits including
	that of straying livestock from the community or children playing,
	or fetching water.

Potential negative impact	Proposed mitigation measures	
	- Appropriate information notices and warning signs to be displayed at periphery of quarry to inform and educate local community of ongoing quarrying activity and required safety measures to be observed.	
HIV and AIDS	 Sensitization programs on issues HIV/AIDS for the quarry staff and local community to be developed and carried out at the quarry site and local community by peer educators. A condom dispenser always stocked with condoms to be availed at the quarry site Proponent to arrange for convenient and free voluntary and counseling services for quarry workers to be accessed at the quarry site and any community members willing to benefit from the service. 	

Summary of potential negative environmental impacts may include:-

- ✓ Loss of site biodiversity
- ✓ Diminishing of local carbon
- ✓ Fugitive dust
- ✓ Vibration
- ✓ Solid waste generation
- ✓ oil and lubricant spills
- ✓ Soil erosion
- ✓ Change in local geological, hydrological and geotechnical conditions

Proposed mitigation measures of potential negative impacts

Potential negative	Proposed mitigation measures	
impacts		
Loss of flora	- Limit vegetation removal to actual areas within the proposed	
	project site with limestone to be mined only	
	- MCL to support planting of trees in public areas such as schools,	
	Chief camps, local dispensaries within the project catchment to	
	offset overall vegetation loss in the area	

Potential negative	ential negative Proposed mitigation measures	
impacts		
	- Back fill and plant trees in all pits where mining is completed	
Loss and	MCL to maintain pockets of vegetation within the proposed	
displacement of site	project site where there are no limestone to be mined	
fauna	- MCL to maintain pockets of vegetation around the quarry camp	
	that can support local fauna habitat need	
	- MCL to maintain hedge of vegetation along quarry access roads	
	that can support local fauna habitat needs.	
	- MCL to support planting of trees in public areas such as schools,	
	Chief camps, local dispensaries within the project catchment to	
	support local fauna habitat needs	
Loss of local	- Coconut trees growing in parcels of land procured by MCL that	
coconuts trees cover	do not have limestone deposits that can be mined to be preserved	
	- MCL to support local communities to grow coconut trees in their	
	private farms to offset overall reduction of coconut trees in the	
	area.	
Generation of	- Regularly sprinkle water on dusty grounds including quarry	
fugitive dust	access roads and active mining areas	
	- Maintain a vegetation buffer around the schools, local homesteads	
	and other social amenities that border limestone pits.	
	- Maintain a hedge of trees along all quarry access roads to act as	
	wind break, noise attenuator and trap fugitive dust	
Noise disturbance	- Ensure quarry equipment and machinery are well serviced and	
	maintained as per manufacturer's instructions.	
	- Use noise attenuators such as a hedge of vegetation around active	
	quarry pits and along quarry access roads.	
	- Regularly measure and monitor noise levels to ensure they are	
	maintained within the prescribed limits as provided for in the	
	Environmental Management and Coordination (noise and	
	excessive vibration pollution) (Control) Regulations 2009.	
	- MCL to develop and document a comprehensive environmental	
	noise management and conservation programme that will cover	

Potential negative	Proposed mitigation measures	
impacts		
	all quarry activities.	
Soil erosion	- Maintain pockets of vegetation including trees to act as wind	
	breaks in areas where limestone will not be mined.	
	- Maintain a vegetation buffer around the schools, local homesteads	
	and other social amenities that border limestone pits.	
	- Plant trees and other vegetation in open areas to minimise	
	exposure of open ground to agents of erosion.	
	- Maintain a hedge of trees along all quarry access roads to act as	
	wind break	
Spills of oils and	- Provide an equipment service and maintenance garage complete	
lubricants	with a service sump and oil/water separator for servicing quarry	
	equipment.	
	- Provide for oil absorbents to aid in cleaning out any spilled oil	
	and lubricants	
Ponding of water in	Ensure all quarry pits are adequately and effectively drained to	
quarry pits	ensure no collection, stagnation and or ponding of rainwater in	
	the pits when it rains.	
Generation of solid	- Ensure all waste generated is managed and disposed as provided	
waste	for in the Environmental Management and Coordination (Waste	
	Management) Regulations, 2006.	
	- Where possible and applicable practice the four Rs i.e. refuse to	
	generate waste, reduce waste generation, reuse generated waste or	
	recycle generated waste.	
	- Provide for receptacles for dropping and collection of waste	
	- Segregate waste at source appropriately.	
	- Contract the services of a waste collector, ensure the vehicle used	
	to collect waste are licensed by NEMA	
	- Maintain dually filled and completed waste tracking documents	
	for all waste collected and disposed from the quarry	
Injuries and	- Fence off all active quarry pits and disused quarry pits to ensure	
accidents	no unauthorized person or livestock access the quarry pits.	

Potential negative Proposed mitigation measures		
impacts		
	- Promptly backfill all quarry pits where mining of limestone is complete.	
	- Ensure all quarry pits are adequately and effectively drained to	
	ensure no collection, stagnation and or ponding of rainwater in	
	the pits when it rains.	
	- Ensure quarry equipment and machinery are well serviced and	
	maintained as per manufacturer's instructions	
	- Ensure only well trained and experience plant and equipment	
	operators are hired to operate quarry equipment and machinery	
Increase in trucks on	- Use alternative routes/feeder roads to reduce number of trucks on	
local roads	oads one local feeder road.	
	- Monitor number of trucks on local feeder roads from and to	
	quarry	
	- Use fewer trucks of higher carrying capacity as opposed many	
	trucks of lower carrying capacity	
Alteration of local	- Maintain pockets of vegetation within the quarry area to minimize	
hydrological	surface runoff and increase rainwater percolation to improve	
condition	recharge of local aquifer.	
	- Quickly vegetate all areas where mining is completed to reduce	
	soil moisture loss when dry and improve ground water aquifer	
	recharge when it rains.	
	- No mining of limestone close to any existing well or borehole	
Dilapidation of local	- All trucks in and out of the quarry to strictly adhere to required	
roads	axial load limits on all roads used.	
	- Install weighbridge in the quarry to monitor weight of loaded	
	trucks before they leave the quarry.	
	- Upgrade local roads to meet heavy load transportation demand	
	from the quarry	
	- Regularly rehabilitate and maintain all local roads being used	

TABLE OF CONTENTS

1. BACKGROUND	1
1.1 Introduction	1
1.2 Project definition	1
1.3 Project Proponent	1
1.4 Location	1
1.5 Change of user	2
1.6 Project Objective and Scope	4
1.6.1 Proposed project objective	4
1.6.2 Project scope	5
1.7 Terms of Reference	5
1.8 Economic activities in the area	5
1.9 Potentially affected environment	7
2. APPROACH AND METHODOLOGY	9
2.1 Study team	9
2.2 Approach	9
2.3 Methodology	10
2.3.1Scoping	10
2.3.2 Desk review	10
2.3.3 Baseline studies and field assessment	11
2.3.4 Public participation	11
2.3.5 Reporting	11
3. BACKGROUND TO ENVIRONMENTAL IMPACT ASSESSMENT	12
3.1 Definition of Environmental Impact Assessment	12
3.2 The purposes of EIA	12
3.2.1 An aid to decision making	12
3.2.2 An aid to the formulation of development actions	12
3.2.3 A vehicle for stakeholder consultation and participation	13
3.2.4 An instrument for sustainable	13
3.3 Origins and development of EIA	14
3.4 Key elements in the EIA process	14
3.4.1 Screening	14
3.4.2 Scoping	14
3.4.3 Impact analysis	15
3.4.4 Impact Mitigation	15
3.4.5 Reporting	16
3.4.6 Report review	16
3.4.7 Monitoring and auditing	16

4. P	OLICY	AND LEGAL FRAMEWORK	17
4.1	Rele	evant National Policies	17
۷	4.1.1	National Environment Policy, 2013	17
۷	4.1.2	National Climate Change Framework Policy Sessional Paper No. 5 of 2016	17
4.2	Nat	ional legislations	17
۷	4.2.1	The Constitution of Kenya, 2010	17
2	1.2.2	The Environmental Management and Co-ordination Act, 1999 (Amended) 2018	015
2	1.2.3	The Occupational Safety and Health Act, 2007	18
2	1.2.4	The Water Act 2016	19
2	1.2.5	Mining Act 2016	19
2	4.2.6 Th	ne Lands Act 2012	20
۷	4.2.8 W	ork Injuries Benefits Act 2007	21
4.3	Reg	gulatory Framework	21
۷	4.3.1	The Environment (Impact Assessment and Audit) Regulations, 2003	21
4	1.3.2	Building Operations and Works of Engineering Construction Rules, 1984	22
4	1.3.3	Noise and Excessive Vibration (Pollution Control) Regulations, 2009	22
۷	1.2.7	The Public Health Act Cap 242	22
	1.3.4 2006	Environmental Management and Coordination (Water Quality) Regulations, 23	
	4.3.5 Regulat	Environmental Management and Coordination (Waste Management) ions, 2006	23
۷	4.3.6 Er	nvironmental Management and Coordination (Air Quality) Regulations, 2014.	24
5. BA	SELIN	E INFORMATION	25
5.1	Biodiv	ersity	25
4	5.1.1 Fl	ora diversity	25
4	5.1.2 Fa	una diversity	26
5.2	Baselii	ne air quality/particulate matter survey	29
4	5.2.1 Ra	ationale for Monitoring Parameter Selection	29
4	5.2.2 M	onitoring Objectives	30
4	5.2.3 M	ethodology	30
4	5.2.4 M	onitoring Frequency	31
4	5.2.5 M	onitoring Location	31
4	5.2.6 Re	esults of the air quality monitoring	33
5.3		eline Noise Levels	
4	5.3.1 Ba	ackground	35
4	5.3.2 M	onitoring Parameters	36
4	5.3.3 Ot	her Parameters	37

5.3.4 Noise monitoring Objectives	38
5.3.5 Monitoring Methodology	38
5.3.6 Parameters and score criteria	39
5.3.7 Tools and Equipment	40
5.3.8 Monitoring Frequency	40
5.3.9 Monitoring Location	40
5.3.10 Results of the Noise monitoring	42
5.3.11 Discussion of Noise Monitoring Results	49
5.3.12 Conclusions from the Noise monitoring	49
5.3.13 Recommendations	50
5.4 Local ground water resource	50
5.4.1 Groundwater quality	51
5.5 Climate	54
5.5.1 Temperature	54
5.5.2 Sunshine	55
5.5.3 Water Temperature	55
5.5.4 Precipitation	55
5.5.5 Monthly Rainy Days	56
5.5.6 Humidity	56
5.5.7 Wind Speed	57
5.6 Geology	57
5.6.1 Introduction	57
5.6.2 Coral Reef Complex	58
5.6.3 Magarini Formation	59
5.6.4 Quaternary Sands	59
5.7Groundwater	59
6. MINING	60
6.1 Mining Methods	60
6.1.1 Surface Mining	60
6.1.2 Underground Mining	60
6.1.3 In-Situ Leach (ISL) Mining	60
6.1.4 Solution and Placer mining	60
6.2 Mining of Stones/Quarrying	61
6.2.2 Introduction	61
6.2.3 Excavation Methods in Quarrying	61
7. PROJECT DESIGN AND DESCRIPTION	63
7.1 Background to limestone	63

7.2 Proposed project components	63
7.2.1 Quarry access roads	63
7.2.2 Site camp	63
7.2.3 Sanitary facilities	64
7.2.4 Weighbridge	64
7.2.5 Overburden stockpile	64
7.2.6 Holding area of recovered coral limestone	64
7.2.7 Operational quarry pits	64
7.2.8 Disused quarry pits	65
7.3 Mining method	65
7.4 Opening of quarry pits	65
7.5 Extraction of limestone and additives	65
8. ANALYSIS OF PROJECT ALTERNATIVES	66
8.1 The No Project Alternative	66
8.2 The Yes Project Alternative	66
8.3 Alternative use of proposed project site	66
8.4 Alternative project site	68
8.5 Alternative mining methods	68
9. OCCUPATIONAL SAFETY AND HEALTH	69
9.1 Introduction	69
9.2. Occupational Health and Safety Management	
9.3. Employee safety	70
9.4. Safety of neighbours and general public	71
9.5 Machine use and Electrical Safety	71
9.6. Internal Safety	72
9.7. First-Aid	72
9.8. Welfare facilities	72
9.9. Ambient factors in the project site	72
9.9.1 Noise	72
9.9.2 Dust	73
10. STAKEHOLDER CONSULTATION AND PUBLIC PARTICIPATION	74
10.1 Steps taken to consult with stakeholders	74
10.2 Key Informants Interviews	74
10.3 Focused Group Discussions	77
10.3.1 Focused Group Discussions with Learning Institutions	77
10.3.2 Focused Group Discussions with Religious Institutions	82
10.3.3 Focused Group Discussions with Village Elders	83

10.3.4	Focused Group Discussions with Wazee wa Nyumba Kumi	85
10.4	Questionnaire survey	86
10.4.1	Questionnaire Survey Responses from Local Administration	86
10.4.2	Questionnaire survey responses from Political Leaders	87
10.4.3	Questionnaire survey responses from local learning institutions	88
10.4.4	Questionnaire survey responses from Health institutions	90
10.4.5	Questionnaire survey responses from Religious Institutions	90
10.4.6	Questionnaire survey responses from Community Members	91
10.4.7	Consolidated Views, Issues and/or Concerns as captured in the questionnaire 92	ès
10.4.8 enviror	Measures proposed to be put in place to protect and or conserve the ment as captured in the questionnaire	93
10.4.9 questio	The General Concerns, Issues and or observations as captured in the innaires	94
	ONMENTAL AND SOCIAL MANAGEMENT PLAN	
11.1 Man	agement policies	96
11.1.1	Environmental Management Policy	97
11.1.2	Occupational Health and Safety Policy	98
11.1.3	Local Community Policy	98
11.1.4	Employment Policy	99
11.2 Pote	ntial social impacts	99
11.2.1	Potential positive social impacts	99
11.2.2	Potential negative social impacts	101
•	osed enhancement measures of potential positive social impacts	
11.4 Miti	gation measures for potential negative social impacts	104
	ntial negative environmental impacts	
11.5.1	Impact identification and predication	106
	Methodology used to determine environmental and social risks of the impacts	
11.5.3	Identified Potential negative Environmental Impacts	108
11.6 Prop	osed mitigation measures for potential negative environmental impacts	122
117. Envi	ronmental Management action plans	126
	ronmental monitoring	
11.8.1	Noise and excessive vibrations monitoring	138
11.8.2	Air Quality Monitoring	139
	Water quality monitoring	
11.8.4	Solid waste disposal monitoring	140
11.9 Train	ning and capacity building	141
11.10 Ins	titutional arrangements for safeguard implementation and reporting	141

11.10.1Institutional arrangement	141
11.10.2 Reporting obligations	142
11.10.3 Quarry rehabilitation monitoring	142
11.11 Quarry rehabilitation plan	142
11.11.1 Rehabilitation procedure	142
11.11.2 Quarry rehabilitation works	143
11.12 Grievance redress mechanism.	146
11.12.1 Definition and purpose	146
11.12.2 Formation	146
11.12.3 GRM Committee Members	146
11.12.4 Mode of Communication	147
11.12.5 Process	147
11.12.6 Information Awareness	147
11.12.7 Record keeping	148
11.13 Decommissioning plan	148
13. CONCLUSIONS AND RECOMMENDATIONS	
13.1 Conclusions	149
13.2 Recommendations	150
LIST OF REFERENCES	151
FIGURES Figure 1: Man of Vilifi North Sub. County showing Polys and Metagogoni locations	2
Figure 1: Map of Kilifi North Sub- County showing Roka and Matsangoni locations	
Figure 2: Generalized EIA process flowchart. Adapted from UNEP 2002	
Figure 3: The A-Weighted frequency reponse	
Figure 4: The C-Weighted frequency response	36
Figure 5: Average minimum and maximum temperatures of Roka area over the year	55
Figure 6: Monthly total of sunshine hours over the year in Roka area	55
Figure 7: Average mean water temperature in Roka area over the year	55
Figure 8: Average precipitation in Roka area over the Year	56
Figure 9: Average Monthly Rainy Days in Roka area over the year	56
Figure 10: Mean monthly relative humidity over the year in Roka area	56
Figure 11: Mean monthly wind speed over the year in Roka area in meters per second	
Figure 12: Impact significance assessment criteria	107
Figure 13: Risk assessment matrix	
-	

TABLES

Table 1: Species of trees observed	25
Table 2: Species of butterflies observed in and in the neighborhood of the project site	26
Table 3: Species of shrubs	28
Table 4: Species of birds observed in and in the neighborhood of proposed project site	28
Table 5: A table of monitoring locations, parameters tested & GPS coordinates	32
Table 6: Sampling Locations and Measurement Results	33
Table 7: Parameters and score criteria	40
Table 8: A table of monitoring locations, parameters tested & GPS coordinates	41
Table 9: Presentation of findings of noise monitoring including various regulatory limits	
guidelines and site remarks and notes	42
Table 10: Determination of significance of singular diurnal results with reference to EMC	
regulatory limits	45
Table 11: Some of the wells surveyed	50
Table 12: Excavation methods in quarrying	61
Table 13: Tabulation of an of each of the project alternatives to the project costs, schedules	s,
resources, and risks	67
Table 14: Proposed measures to enhance positive impacts	103
Table 15: Proposed mitigation measures for potential negative social impacts	104
Table 16: Assessment of environmental risk resulting from quarry access roads development	ent
	110
Table 17: Assessment of environmental risk of vegetation loss from project site	111
Table 18: Assessment of environmental risk resulting from quarry camp construction	112
Table 19: Assessment of environmental risk resulting from quarry equipment mobilization	1
	113
Table 20: Assessment of environmental risk resulting from excavation and removal of	
overburden	115
Table 21: Assessment of environmental risk resulting from breaking and loosening of the	
massive limestone bedrock	116
Table 22: Assessment of environmental risk resulting from loading into trucks of the mine	ed
limestone	117
Table 23: Assessment of environmental risk resulting from quarry equipment mobilization	ı
	119
Table 24: Assessment of environmental risk resulting from dismantling of quarry camp an	ıd
removal of support infrastructure	120

Table 25: Assessment of environmental risk associated with equipment demobilization	n from
site	121
Table 26 Assessment of environmental risk resulting from backfilling of open quarry	pits.121
Table 27: Proposed mitigation measures for potential negative environmental impacts	122
Table 28: Biodiversity conservation action plan	126
Table 29: Local water resource conservation action plan	127
Table 30: Dust management action plan	129
Table 31: Noise and vibration management action plan	132
Table 32: Traffic management action plan	133
Table 33: Waste management action plan	135
Table 34: Oil spills management action plan	137
Table 35: Maximum permissible noise levels for constructions sites when measurement	nt taken
within the facility	138
Table 36: Maximum Permissible Noise Levels for Mines and Quarries	138
Table 37: Ambient Air Quality Tolerance Limits	139
Table 38: Emission Limits	140
Table 39: Water quality monitoring parameters	140
Table 40: Quarry pit rehabilitation action plan	144
PLATES	
Plate 1: Active machine cut coral limestone quarries adjacent to proposed project site	areas6
Plate 2: Some of the coconut trees within plots of the proposed project site and in the	
neighborhood	7
Plate 3: Livestock grazing in sections of the proposed project site	7
Plate 4: A bush of neem at the proposed project site	25
Plate 5: Ricinus communis growing at the edge of the access road	27
Plate 7: Identification of boreholes	51
Plate 8: The EIA Team meeting the County Commissioner Kilifi County	75
Plate 9: The EIA Team meeting the Deputy County Commissioner Kilifi County	75
Plate 10: The EIA Team meeting the County Director of Environment Kilifi County	76
Plate 11: The EIA Team meeting the Senior Chief Roka Location	76
Plate 12: The EIA Team meeting the Senior Chief Matsangoni Location	77
Plate 13: Focused group discussions with the Chumani Secondary School BOM	78
Plate 14: Focused group discussions with the Roka Secondary School BOM	79

Plate 15: Focused group discussion with the Katana Ngala Secondary School BOM	80
Plate 16: Focused group discussion with Uyombo Girls Secondary School BOM	.81
Plate 17: Focused group discussion with Roka Primary School BOM	.81
Plate 18: Focused group discussion with the Kararacha Primary School BOM	82
Plate 19: Focused group discussion with religious leaders	83
Plate 20: Focused group discussion with the Roka and Matsangoni Sub-Locations Village	
Elders	84
Plate 21: Focused group discussion with the Matsangoni and Uyombo Sub-Locations'	
Village Elders	.84
Plate 22: Focused group discussion with Mkongani Sub-Locationa Village Elders	85
Plate 23: Focused group discussion with Wazee wa Nyumba Kumi	86

1. BACKGROUND

1.1 Introduction

This report is an Environmental Impact Assessment Study for proposed mining of coral limestone to be carried out by Mombasa Cement Limited. The Environmental Impact Assessment Study was carried out and report compiled as provided for in Legal Notice No 31 and 32 of 2019, section 58 (2) of the Environmental Management and Coordination Act, 1999 (Amended) 2015 and Regulation 11 (1) of the Environmental (Impact Assessment and Audit Regulations), 2003.

1.2 Project definition

The proposed project will entail mining of coral limestone at the proposed project site using the open cast mining method. The mined limestone will then be transported out of the mine by a fleet of dump trucks to Mombasa Cement factory located at Vipingo area of Kilifi County for cement production.

1.3 Project Proponent

Mombasa Cement Limited, a private company incorporated with limited liabilities in the Republic of Kenya is the project proponent. The company holds a certificate of incorporation number C. 106734 date eleventh November two thousand and three and personal identification number certificate P051159492Z dated second June 2004. Appendix 1 is copy of the certificate of incorporation and copy of personal identification number certificate.

1.4 Location

The proposed mining of coral limestone is to be done in Kilifi County, Kilifi North Sub-County, Roka location and Matsangoni Location (Geographical location 3° 26' 0" South, 39° 54' 0" East) in 116 plots all owned by Mombasa Cement Limited. Within Roka Location the mining will be done in two sub-locations namely Roka Sub-Location and Chumani Sub-Location. Within Matsangoni Location, limestone mining will be carried out in two sub-locations namely Uyombo Sub-Location, and Matsangoni Sub-location (figure 1). The limestone mining will cover 116 plots this being 28 more plots from what was reported in the terms of reference report. Each plot has an individual title deed which is in the name of the proponent. Appendix 2 is a copy of the 116 title deeds as shown in table 1 and 2...




Figure 1: Map of Kilifi North Sub- County showing Roka and Matsangoni locations

1.5 Change of user

A change of user from agricultural to industrial (stone cutting and mining) has been obtained for the 66 plots (table 10 while 55 of the plots the change of user was yet to be obtained (table

2). The change of user was processed in the names of the previous owners of the plots before being transferred to Mombasa Cement Limited. Appendix 3 is a copy of the change of user

Table 1: Proposed project land parcels with change of user

NO	LAND TITLE DEED	NO	LAND TITLE DEED
1.	Roka/Uyombo/381	34.	Roka/Uyombo/190
2.	Roka/Uyombo/564	35.	Roka/Uyombo/298
3.	Roka/Uyombo/416	36.	Roka/Uyombo/229
4.	Roka/Uyombo/234	37.	Roka/Uyombo/609
5.	Kilifi/Roka/1008	38.	Roka/Uyombo/123
6.	Roka/Uyombo/231	39.	Roka/Uyombo/223
7.	Roka/Uyombo/481	40.	Roka/Uyombo/336
8.	Roka/Uyombo/459	41.	Roka/Uyombo/257
9.	Roka/Uyombo/227	42.	Roka/Uyombo/467
10.	Roka/Uyombo/612	43.	Roka/Uyombo/124
11.	Roka/Uyombo/469	44.	Roka/Uyombo/141
12.	Roka/Uyombo/439	45.	Roka/Uyombo/181
13.	Roka/Uyombo/485	46.	Roka/Uyombo/194
14.	Roka/Uyombo/212	47.	Roka/Uyombo/197
15.	Roka/Uyombo/370	48.	Roka/Uyombo/224
16.	Roka/Uyombo/318	49.	Roka/Uyombo/226
17.	Roka/Uyombo/607	50.	Roka/Uyombo/233
18.	Roka/Uyombo/452	51.	Roka/Uyombo/383
19.	Kilifi/TezoRoka/1009	52.	Roka/Uyombo/388
20.	Roka/Uyombo/588	53.	Roka/Uyombo/410
21.	Roka/Uyombo/583	54.	Roka/Uyombo/460
22.	Roka/Uyombo/397	55.	Roka/Uyombo/479
23.	Roka/Uyombo/601	56.	Roka/Uyombo/488
24.	Roka/Uyombo/77	57.	Roka/Uyombo/175
25.	Roka/Uyombo/176	58.	Roka/Uyombo/444
26.	Roka/Uyombo/154	59.	Roka/Uyombo/230
27.	Roka/Uyombo/96	60.	Roka/Uyombo/242
28.	Roka/Uyombo/246	61.	Roka/Uyombo/475
29.	Roka/Uyombo/445	62.	Roka/Uyombo/64

30.	Roka/Uyombo/249	63.	Roka/Uyombo/308
31.	Roka/Uyombo/147	64.	Roka/Uyombo/441
32.	Roka/Uyombo/413	65.	Roka/Uyombo/220
33.	Roka/Uyombo/400	66.	Roka/Uyombo/252

1.6 Project Objective and Scope

1.6.1 Proposed project objective

The objective of the proposed project is to mine coral limestone and transport the mined limestone from the mine to Mombasa Cement Limited Factory at Vipingo for production of cement.

Table 2: Proposed project land parcels without change of user

NO	LAND TITLE DEED
1.	Kilifi/Roka/Uyombo/399
2.	Kilifi/Roka/Uyombo/461
3.	Kilifi/Roka/Uyombo/131
4.	Kilifi/Roka/Uyombo/65
5.	Kilifi/Roka/Uyombo/331
6.	Kilifi/Roka/Uyombo/384
7.	Kilifi/Roka/Uyombo/463
8.	Kilifi/Roka/Uyombo/395
9.	Kilifi/Roka/Uyombo/157
10.	Kilifi/Roka/Uyombo/105
11.	Kilifi/Roka/Uyombo/315
12.	Kilifi/Roka/Uyombo/239
13.	Kilifi/Roka/Uyombo/570
14.	Kilifi/Roka/Uyombo/453
15.	Kilifi/Roka/Uyombo/255
16.	Kilifi/Roka/Uyombo/411
17.	Kilifi/Roka/Uyombo/391
18.	Kilifi/Roka/Uyombo/196
19.	Kilifi/Roka/Uyombo/482
20.	Kilifi/Roka/Uyombo/454

21.	Kilifi/Roka/Uyombo/372
22.	Kilifi/Roka/Uyombo/323
23.	Kilifi/Roka/Uyombo/376
24.	Kilifi/Roka/Uyombo/75

1.6.2 Project scope

The scope of the proposed project is as follows; fencing and securing the proposed project site, construction of quarry camp and associated infrastructure, installation of weighbridge, mobilization of quarry equipment and machinery to site, actual open cast quarrying activities to recover coral limestone, haulage of the recovered coral limestone from site to Vipingo, continuous rehabilitation of disused quarry pits, demobilization of quarrying equipment, decommissioning of all quarry activities and site rehabilitation.

1.7 Terms of Reference

Terms of reference (ToR) reference number NEMA/TOR/5/2/177 for the EIA study was prepared and submitted to the National Environment Management Authority (NEMA) for approval. The ToR was approved by NEMA on 19th October 2020 paving way to carry out the environmental impact assessment study and compilation of this environmental impact assessment study report. Appendix 4 is copy of the ToR approval letter from NEMA.

1.8 Economic activities in the area

Within the proposed project area, the immediate neighbourhood and the wider project catchment area, there are various economic activities. Notable one include:-

- ✓ Machine cut of coral limestone to recover building blocks. There are a number of quarries in the area which are involved in machine cutting of coral limestone to recover building blocks. Some of these quarries are adjacent to the plots of MCL; others are adjacent to local schools such as that adjacent to Uyombo Girls Secondary School while others are adjacent to homesteads.
- ✓ Cultivation of coconut trees, parts of the land in the neighbourhood including some of the parcels bought by MCL have coconut trees growing. Coconut farming is one of the important economic activities in the area. Other crops grown within the neighbourhood include cassava, watermelon, cowpeas, maize among others
- ✓ Livestock keeping is also carried out within the project catchment area, livestock such as goats and cows have been sported grassing within the project catchment area.



Plate 1: Active machine cut coral limestone quarries adjacent to proposed project site areas



Plate 2: Some of the coconut trees within plots of the proposed project site and in the neighborhood



Plate 3: Livestock grazing in sections of the proposed project site

1.9 Potentially affected environment

The proposed coral limestone mining activities will potentially affect the following environments:-

- ✓ Local homesteads adjacent to the proposed project site are likely to be affected from potential dust and noise from proposed quarrying activities.
- ✓ Local schools adjacent to the proposed project site are likely to be affected by potential noise and dust from proposed quarrying activities. This will potentially affect the learning environment for the learners. Further trucks driving in and out of the proposed project site will not only be a destruction to the learners but also a public safety risk.
- ✓ Local roads likely to be used by trucks to and from the proposed project site will be affected from potential increase in traffic in and out of the proposed project site.

 These roads are likely to be damaged more easily from loaded trucks

- ✓ Local ground water resources within the proposed project site is likely to be affected, the mining will potentially reduce local areas aquifer recharge and hence reduced water yield in the wells besides potential pollution from quarrying activities
- ✓ Local coconut farms within the proposed project site will be negatively affected as coconut trees within parcels of land for the proposed project site will be cut to pave way for proposed mining activities. Also coconut trees on plots adjacent to the proposed project site could potentially be affected by potential dust from the proposed project activities.
- ✓ Machine cut coral limestone building blocks quarries in the area will be affected as they will be competing for local limestone areas with MCL.
- ✓ Local social environment will potentially be affected from proposed project by potential labor influx into the area seeking gainful employment. Further those who will be selling their parcels of land and moving out to settle elsewhere will affect the existing local social fabric. Pressure on local social amenities including health facilities, schools and faith based institutions is likely to be felt from migrants' workers and their followers. This will affect the overall local social environment.

2. APPROACH AND METHODOLOGY

2.1 Study team

The Environmental Impact Assessment Study was carried out by Sigtuna Consultancy Limited firm of experts and Polucon Services Limited an accredited as follows:

- ✓ Philip Manyi Omenge, Team Leader, EIA/EA Lead Expert, Natural Resources Management/Ecology, Rural Development, Conflict Management and Gender Mainstreaming Specialist.
- ✓ James Morumbasi Mong'oni a registered EIA/EA Lead Expert, a Mechanical Engineer, a Safety Practitioner, Safety Trainer, and Inspector of pressure vessels and lifting equipment.
- ✓ Hezekiah Adala, EIA/EA Lead Expert, Mechanical Engineer, Safety Advisor;
- ✓ Jonathana Katana Yeri, EIA/EA Associate Expert, Soil, Water and Environmental Engineer
- ✓ Polucon Services (Kenya Limited)- Accredited laboratory air quality, noise and vibration and water quality.

Registration certificate and practicing license of the firm of experts is attached in appendix 5 while that of the individual experts is in appendix 6.

The study team was aided by the following members from Mombasa Cement Limited and the local community:-

- ✓ Thomas Orina Basweti- MCL Environmental Safety and Health Officer
- ✓ Yonnah Bosire- MCL in- Charge of Proposed project site
- ✓ Joshua Karisa- Surveyor involved in surveying of the proposed project site
- ✓ Dickson Nyamawi Mwaidza-Roka Maweni Village Elder

2.2 Approach

At the beginning of the assignment inception meetings were held between the Proponent and the Consulting Team Leader both in the office and at the proposed project site. The meetings served as formal introduction for clarification of terms of reference for the study team, introduce them to the contact persons and physically show the team the proposed project site. The consulting thereafter embarked on scoping exercise that culminated in the development of terms of reference for the study. Baseline studies and detailed field investigations were later carried out followed by stakeholder consultations. Findings from desk review, baseline

studies and field investigations were compiled into an environmental impact assessment study report.

2.3 Methodology

The following methodology was used in undertaking the Environmental Impact Assessment:

- i) Scoping and development of Terms of Reference
- ii) Desk review of relevant project documents including relevant policy and legislative documents.
- iii) Baseline studies and field visits for detailed documentation of site conditions and actual site assessment.
- iv) Public participation
- v) Reporting.

2.3.1Scoping

Scoping identified the important issues in readiness for preparation of terms of reference; it was a critical, early step in the preparation of an EIA study report. The scoping process identified the issues that are likely to be of most importance during the EIA and eliminated those that were of little concern.

2.3.2 Desk review

Desk top review included review of the following:

- ❖ Policy documents: National Environment Policy, 2013, Kenya National Youth Policy, Kenya Gender Policy, and KNBS Economic Survey Report 2017, National Climate Change Framework Policy Sessional Paper No. 5 of 2016 among others.
- ❖ National legislations: The Constitution of Kenya, 2010; the Mining Act of 2016; The Coordination Environmental Management and Act (EMCA),1999; The Environmental (Impact Assessment and Audit) Regulations, The 2003; Environmental Management and Coordination (Water Quality) Regulations, 2006; The Environmental Management and Coordination (Waste Management) Regulations, 2006; Environmental Management and Coordination (Air Quality) Regulations, 2014; The Public Health Act Cap 242; The Occupational Safety and Health Act 2007; The Physical Planning Act 1996, Cap. 286, The Water Act 2016; Climate Change Act, 2016 among others.
- ❖ **Development Plans:** Kilifi County Integrated Development Plan 2013-2017
- ❖ International agreements, Conventions, and WB Policies:

2.3.3 Baseline studies and field assessment

Baseline studies carried out included local ground water quality analysis, local air quality analysis, noise and vibration levels measurements. Field assessments included local terrestrial flora and fauna survey. The vegetation survey employed the plot-less method to capture plant diversity at the proposed project site. The survey method involved random walks through the proposed project site and recording of the various vegetation species observed. Herpetofauna (reptiles and amphibians) and invertebrates and other terrestrial fauna were observed and recorded. Local account was used to supplement information on existence of species or taxa. Photographic recordings of some of the observed species were done.

2.3.4 Public participation

Due to the challenges brought about COVID-19, stakeholder consultations were innovative. To adhere to the government restrictions on large public gatherings, no public baraza was held, and instead identified key stakeholders were consulted in small groups while observing the Ministry of Health guidelines on social distancing. All stakeholder consultation and participation strictly adhered to the Ministry of Health Public Health guidelines and protocols. The proponent provided face masks, hand sanitizers, water and soap for washing hands and ensure that 1.5 m social distance was observed during the consultation process. Public participation involved office consultations with local leaders, focused group discussions, key informant interviews and questionnaire survey

2.3.5 Reporting

All the information and data collected from scoping exercise, the desk top document review, field assessments and stakeholder consultation and participation was compiled into two reports namely:-

- ✓ Terms of Reference Report; and
- ✓ Environmental Impact assessment (EIA) Study Report.

Terms of Reference Report was submitted to NEMA as specified in Regulation 11 (1) and 11(2) of the Environmental (Impact Assessment and Audit) Regulations, 2003. The Environmental Impact assessment (EIA) Study Report was prepared as specified in Regulation 18 of the Environmental (Impact Assessment and Audit) Regulations, 2003 and submitted to NEMA as specified in Regulation 19 of the Environmental (Impact Assessment and Audit) Regulations, 2003.

3. BACKGROUND TO ENVIRONMENTAL IMPACT ASSESSMENT

3.1 Definition of Environmental Impact Assessment

Broadly environmental impact assessment (EIA) refers to the need 'to identify and predict the impact on the environment and on man's health and wellbeing of legislative proposals, policies, programmes, projects and operational procedures, and to interpret and communicate information about the impacts' (Munn 1979). UNECE (1991) defines EIA as 'an assessment of the impacts of planned activity on the environment', IAIA (2009) on the other hand defines EIA as 'the process of identifying, predicting, evaluating and mitigating the biophysical, social and other relevant effects of proposed development proposals prior to major decision being taken and commitments made'. Glasson *et.al* (2012) defines EIA as 'a systematic process that examines the environmental consequences of development actions in advance'. EIA is thus a vital tool that aid formulation of development actions, decision making, an instrument for sustainable development and vehicle for stakeholder consultation and participation (Glasson *et.al* 2012).

3.2 The purposes of EIA

3.2.1 An aid to decision making

EIA is an aid to decision-making. For the decision maker, for example, a local authority, it provides a systematic examination of the environmental implications of a proposed action, and sometimes alternatives, before a decision is taken. The EIA can be considered by the decision-maker along with other documentation related to the planned activity. EIA is normally wider in scope and less quantitative than other techniques, such as cost-benefit analysis (CBA). It is not a substitute for decision making, but it does help to clarify some of the trade-offs associated with a proposed development action, which should lead to more informed and structured decision-making. The EIA process has a potential, not always taken up, to be a basis for negotiation between the developer, public interest groups and the planning regulator. This can lead to outcome that balances well the interests of the development action and the environment.

3.2.2 An aid to the formulation of development actions

Developers may see the EIA process as another set of hurdles to jump before they can proceed with their various activities; the process can be seen as yet another costly and time-consuming activity in the development consent process. However, EIA can be of great benefit to them, since it can provide a framework for considering location and design issues

and environmental issues in parallel. It can be an aid to the formulation of development actions, indicating areas where a project can be modified to minimize or eliminate all together its adverse impacts on the environment. The consideration of environmental impacts early in the planning life of a development can lead to more environmentally sensitive development; to improved relations between the developer, the planning authority and the local communities; to a smoother development consent process, and sometimes to a worthwhile financial return on the extra expenditure incurred. O'Riordan (1990) links such concepts of negotiation and redesign to the important environmental themes of 'green consumerism' and 'green capitalism'. The growing demand by consumers to goods that do no environmental damage, plus a growing market for clean technologies, is generating a response from developers. EIA can be the signal to the developer of potential conflict; wise developers may use the process to negotiate 'environmental gain' solutions, which may eliminate or offset negative environmental impacts, reduce local opposition and avoid costly public inquiries. This can be seen in the wider and contemporary context of corporate social responsibility (CSR) being increasingly practiced by major businesses (Crane et al.2008)

3.2.3 A vehicle for stakeholder consultation and participation

Development actions may have wide-ranging impacts on the environment, affecting many different groups in society. There is increasing emphasis by government at many levels on the importance of consultation and participation by key stakeholders in the planning and development of projects. EIA can be a very useful vehicle for engaging with communities and stakeholders, helping those potentially affected by a proposed development to be much better informed and to be more fully involved in the planning and development process.

3.2.4 An instrument for sustainable

Existing environmentally harmful developments have to be managed as best as they can. In extreme cases, they may be closed down, but they can still leave residual environmental problems for decades to come. It would be much better to mitigate the harmful effects in advance, at the planning stage, or in some cases avoid the particular development together. This of course leads on to the fundamental role of EIA as an instrument for sustainable development-a role some writers have drawn attention to as one often more hidden than it should be when EIA effectiveness is being assessed (Jay et al.2007).

3.3 Origins and development of EIA

The first EIA legislation was formerly established in the United States of America in 1969 (NEPA 1970), in Europe the 1985 European Community directive on EIA (Directive 85/337) introduced broadly uniform requirements for EIA for all member states (CEC, 1985). In Australia, the Commonwealth EIA system was established in 1974 under the Environmental Protection (Impact of Proposal) Act (Wood 2003, Ellott and Thomas, 2009). The United Kingdom enacted a formal legislation on EIA in 1988 (Glasson *et.al* 2012). China formerly enacted its first EIA legislation in 1979 (Moorman and Ge 2007). In Africa and the Middle East, Israel and Algeria pioneered in enactment and implementation of EIA legislations in 1982, 2003 and 1983, 1990 respectively (Economic Commission for Africa, (2005) Almagi *et.al* (2007). In East Africa Uganda pioneered in enacting EIA legislation in 1998, Kenya EIA legislation was enacted in 2000, and implemented in 2003 (Morara *et.al* 2011).

3.4 Key elements in the EIA process

The environmental impact assessment process comprises of various interactive steps such as screening, scoping, consideration of alternatives, action design, preparation of the EIA report, reviewing or evaluating the report, decision making, and post decision activities such as monitoring and auditing (Glasson *et al.*, 1994; Wood, 1995). According to UNEP (2002) key elements in the EIA process are screening, scoping, impact analysis, mitigation, reporting, review, decision-making, follow up and public involvement. Figure 2 is the schematic presentation of general EIA process adopted from UNEP' environmental impact assessment training manual.

3.4.1 Screening

Screening determines whether or not a proposal requires an EIA and, if so, what level of analysis is necessary. This process brings clarity and certainty to the implementation of EIA, ensuring that it neither entails excessive review nor overlooks proposals that warrant examination.

3.4.2 Scoping

Scoping identifies the important issues in readiness for preparation of terms of reference; it is a critical, early step in the preparation of an EIA (UNEP. 2002). The scoping process identifies the issues that are likely to be of most importance during the EIA and eliminates those that are of little concern. In this way, EIA studies are focused on the significant effects and time and money are not wasted on unnecessary investigations (Glasson *et al.*, 2012).




Figure 2: Generalized EIA process flowchart. Adapted from UNEP 2002

3.4.3 Impact analysis

Impact analysis is carried out in the detailed phase of the EIA; it involves identifying the impacts more specifically, predicting the characteristics of the main impacts and evaluating the significance of the residual impacts (UNEP, 2002).

3.4.4 Impact Mitigation

Mitigation is the stage of the EIA process when measures are identified to avoid, minimize or remedy impacts. These measures are implemented as part of the process of impact management, together with any necessary adjustments to respond to unforeseen impacts. Both elements are integral to ensuring that the EIA process leads to practical action to offset the adverse environmental impacts of proposed developments (UNEP, 2002). Mitigation recommends feasible and cost–effective measures to prevent or reduce significant negative impacts to acceptable levels.

3.4.5 Reporting

Reporting involves compiling all the information obtained into an EIA report which is a keystone document. It assembles the information that assists the proponent in managing the impacts of the proposal, the responsible authority in decision-making and condition setting; and the public in understanding the likely impacts of the proposal (UNEP, 2002).

3.4.6 Report review

The review stage of the EIA report is one of the main 'checks and balances' built into the EIA process to establish the quality of an EIA. It helps to ensure the information submitted is credible and sufficient for decision-making purposes (UNEP, 2002) by verifying the accuracy and comprehensiveness of the report (Glasson *et al.*, 2012). The decision-making element of the EIA process involves approving or rejecting the proposal and setting conditions. Decision making stage provides for incorporation of environmental considerations into proposed development (Glasson *et al.*, 2012). Once the proposed project is approved, implementation and follow up complete the EIA process (UNEP, 2002).

3.4.7 Monitoring and auditing

Monitoring, auditing and other tools are used to 'close the loop' of impact prediction and condition setting (Sadler, 1996). Monitoring and auditing is vital as it is used to identify the impacts that occur; to check that these are within the levels predicted and required by legislation; determine that mitigation measures are properly implemented and work effectively; ensure the environmental benefits expected are being achieved; and provide feedback to improve future applications of the EIA process (Arts, 1998).

4. POLICY AND LEGAL FRAMEWORK

4.1 Relevant National Policies

4.1.1 National Environment Policy, 2013

The National Environment Policy document was prepared with the goal of bettering the quality of life for present and future generations through sustainable management and use of the environment and natural resources. The document underscores the importance and contribution of environment and natural resources to the local and national economy, people's livelihoods and the provision of environmental services such as watershed protection and carbon sequestration. It also reviews the status of environment in Kenya and highlights the key environmental issues and challenges. It identifies Kenya's critical ecosystems and natural resources and proposes measures to enhance conservation and management of ecosystems and sustainable use of natural resources. It addresses a wide range of issues relating to environmental quality and health. The areas covered include air quality, water and sanitation, waste management, radiation, toxic and hazardous substances, noise, HIV and AIDS and environmental diseases. It also outlines strategies and actions that will ensure effective implementation of the Policy and the Environmental Management and Coordination Act.

4.1.2 National Climate Change Framework Policy Sessional Paper No. 5 of 2016

This Policy was developed to facilitate a coordinated, coherent and effective response to the local, national and global challenges and opportunities presented by climate change. The policy adapts an overarching mainstreaming approach to ensure the integration of climate change considerations into development planning, budgeting and implementation in all sectors and at all levels of government. The Policy therefore aims to enhance adaptive capacity and build resilience to climate variability and change, while promoting a low carbon development pathway. The response to climate change in Kenya must adhere to the constitutional governance framework and commitment to sustainable development, while addressing the goal of attaining low carbon climate resilient development. To attain the latter, the policy focuses on appropriate mechanisms to enhance climate resilience and adaptive capacity, and the transition to low carbon growth.

4.2 National legislations

4.2.1 The Constitution of Kenya, 2010

The Constitution of Kenya 2010 is the overarching legal framework for matters on environment. It recognizes the environment as part of the country's heritage, and which must be safeguarded for future generations. It provides for the right to a clean and healthy

environment for every person in Article 42, obligating the state to enact legislation to protect that right as well as to establish systems of environmental impact assessment, environmental audit and monitoring of the environment in Article 69.

Article 69 imposes on the State, other obligations including, to:

- Ensure sustainable exploitation, utilization, management and conservation of the environment and natural resources, and ensure the equitable sharing of the accruing benefits;
- Encourage public participation in the management, protection and conservation of the environment;
- Eliminate processes and activities that are likely to endanger the environment; and
- Utilize the environment and natural resources for the benefit of the people of Kenya.

Article 69 (2) similarly confers a conservation obligation on parties including the proponent of the proposed project. The proponent is thus obligated to cooperate with State organs and other persons to protect and conserve the environment.

4.2.2 The Environmental Management and Co-ordination Act, 1999 (Amended) 2015

EMCA, 1999 (Amended) 2015 provides a legal and institutional framework for the protection and conservation of the environment in line with Article 42 of the Constitution of Kenya, 2010. The ultimate objective is to provide a framework for integrating environmental considerations into the country's overall economic and social development. According to section 58 of the Act projects specified in the second schedule that are likely to have significant impact on the environment have to be subjected to an EIA study. Mining and other related activities are categorized as high risk projects in the second schedule and hence must be subjected to environmental impact assessment study prior to implementation.

4.2.3 The Occupational Safety and Health Act, 2007

This Act came into force in 2007 and replacing The Factories and Other Places of Work Act, Cap 514. It makes provisions for the health, safety and welfare to be observed by employers and persons employed in places of work. Part IV of the act covers health issues such as the state of cleanliness, refuse management, employee space requirement, ventilation and sanitary conveniences. Part V covers fire safety, operation and maintenance of machinery, fencing requirements, storage of dangerous substances, training and supervision of workers. Part VI deals with welfare issues; drinking water supply, washing facilities, sitting areas and first aid provision.

4.2.4 The Water Act 2016

This is an act provides for the regulation, management and development of water resources, water and sewerage services; and for other connected purposes. The Act aligns the water sector with the new Constitution's primary objective of devolution. The Act recognizes that water related functions are a shared responsibility between the national government and the County government. The Act provides that every person has the right to access water resources, whose administration is the function of the national government as stipulated in the Fourth Schedule to the Constitution. Section 63 thereof also provides that every person in Kenya has the right to clean and safe water in adequate quantities and to reasonable standards of sanitation as stipulated in Article 43 of the Constitution. The Water Resource Authority was established under this Act to protect, conserve, control and regulate use of water resources through the establishment of a national water resource strategy. The Water Act provides for the conservation and controlled use of water resources in Kenya. Under the Ministry of Water the Act prohibits pollution of water resources and controls the discharge of industrial and municipal effluents into the ocean and other water bodies.

4.2.5 Mining Act 2016

This is an act of Parliament to give effect to Articles 60, 62 (1)(f), 66 (2), 69 and 71 of the Constitution in so far as they apply to minerals; provide for prospecting, mining, processing, refining, treatment, transport and any dealings in minerals and for related purposes. The Mining Act, 2016 came into force on May, 2016 thereby repealing the previous Mining Act (Cap.306) which was enacted in 1940. Limestone is categorized as a mineral under this Act. In this Act, a holder of a mining license shall:-

- Conduct mining operations in compliance with the approved programme for mining operations;
- Comply with the terms and conditions of the approved environmental impact assessment license, social heritage assessment and environmental management plan relating to the operations to be carried out under the mining license;
- Demarcate and keep demarcated the mining area in the prescribed manner;
- Comply with the conditions of the license, any applicable mineral agreement and any directions issued by the Cabinet Secretary or an authorized officer in accordance with this Act;
- Submit to the Cabinet Secretary up to date quarterly returns of mine development and mineral production;

- Stack or dump any mineral or waste products in the manner provided for in the license or as otherwise prescribed, having regard to good mining industry practice;
- Carry out prospecting and mining activities in accordance with international best practice and the prescribed guidelines; and
- Sign a community development agreement with the community where mining operations are to be carried out in such a manner as shall be prescribed in Regulations.

The holder of a mining license under this Act shall keep at the registered office, a complete and accurate record of the mining operations in the prescribed form. Records shall include:-

- Copies of all maps, geological reports, sample analysis, aerial photographs, cores, logs and tests and other data obtained and compiled by the license holder;
- Financial statements and such other books of account as the Cabinet Secretary may prescribe; and
- Such other reports and information as may be prescribed or otherwise determined by the Cabinet Secretary.

The holder of a mining license under this Act shall give the Cabinet Secretary a notice of any intention to cease or suspend mining operations, or curtail production carried on pursuant to the mining license. The holder shall give notice of at least -

- Six months, for cessation of mining operation;
- Three months, for suspension of mining operation; or
- One month, for curtailment in production.

A notice given under section shall include a statement that sets out the technical and economic basis for the proposed cessation, suspension or curtailment of production. Under the Act, the Cabinet Secretary shall not grant a prospecting license, a retention license or a mining license to an applicant; unless the applicant has submitted a site mitigation and rehabilitation or mine-closure plans for approval. The proposed coral limestone mining project will comply fully with the provisions and requirements of the Mining Act.

4.2.6 The Lands Act 2012

The Land Act 2012 is "an Act of Parliament to give effect to Article 68 of the Constitution, to revise, consolidate and rationalize land laws; to provide for the sustainable administration and management of land and land based resources, and for connected purposes". Part I of the act is preliminary provisions, part II of the act deals with management of public land, part III of the act deals with administration of public land (Leases, Licenses

and Agreements), part IV of the act deals with community land, part V of the act deals with administration and management of private land, part VI of the act deals with general provisions of leases, part VII of the act deals with general provisions of charges, part VIII of the act deals with compulsory acquisition of interests in land, part IX of the act deals with settlement programmes, part X of the act deals with easements and analogous rights, part XI of the act deals with miscellaneous, the schedule lists repealed laws i.e. The Wayleaves Act, Cap. 292 and The Land Acquisition Act, Cap. 295. The proposed mining of coral limestone will comply with the provisions and requirements of the Lands Act 2012.

4.2.8 Work Injuries Benefits Act 2007

Section 7 of the Act stipulates that every employer shall obtain and maintain an insurance policy with an insurance company approved by the Minister in respect of any liability that the employer may incur under this Act to any of his employees. An employee who is involved in an accident resulting in the employees' disability or death is subject to the provisions of this Act, and entitled to benefits provided for under the Act. Section 3 of the Act however states that no employee shall be entitled to compensation if an accident, not resulting to serious disability or death, is caused by the deliberate and willful misconduct of the employee. The proposed project will comply with the provisions and requirements of this Act.

4.3 Regulatory Framework

4.3.1 The Environment (Impact Assessment and Audit) Regulations, 2003

These regulations provide guidelines for conducting an EIA study as well as environmental auditing and monitoring. The Regulations state in Regulation 3 that "the Regulations should apply to all policies, plans, programmes, projects and activities specified in Part III and V of the Regulations" basically lists the guidelines of undertaking, submission and approval of the EIA/SEA Report. The Regulations requires proponents to conduct annual environmental audits to identify the environmental impacts of their undertakings and propose mitigation measures to improve their environmental performance. Section 17 of the same regulation stipulates that during the process of conducting the audit the proponent shall seek the views of persons who may be affected by their operations. This EIA study report is carried out by the project proponent of the proposed project in partial fulfillment to the provisions of this legislation.

4.3.2 Building Operations and Works of Engineering Construction Rules, 1984

The provisions of the Factories Act relevant to building operations and engineering construction works are contained in the Abstract of the Act for Building Operations and Works of Engineering Construction Rules. These rules specify the minimum safety and health measures to be taken during construction works which include that the proponent should:

- Give notice of particular operations or works;
- Such notice should be sent in writing to the Occupational Health and Safety
 Officer, not later than seven days after commencement of construction;
- Post printed copies or prescribed abstracts of the Occupational Safety and Health Act at the site of operations or works (Section 61 of the Act);
- Provide sufficient and suitable sanitary conveniences for persons employed. These must be kept clean and well lit.

The proposed project will adhere to the provisions of this rules..

4.3.3 Noise and Excessive Vibration (Pollution Control) Regulations, 2009

The regulations apply to persons wishing to operate or repair any equipment or machinery, engage in any commercial or industrial activity that is likely to emit noise or excessive vibrations. The regulations specify the limits or levels within which these shall be undertaken. The Regulations also stipulate in the second schedule that construction activities undertaken during the night should not emit excessive noise beyond the permissible levels. Mombasa cement will comply to the provisions of these regulations during implementation of the proposed coral limestone mining project.

4.2.7 The Public Health Act Cap 242

Key relevant provisions of this Act are:

- Section 10, 11, 12, and 13 for regulating the maintenance, repair and inspection of drains, latrines, cesspool or septic tanks
- Section 28, 29, and 30 which give requirements for the construction of drains in connection with buildings and
- Section 115 prohibiting nuisances that may cause injury or health hazards.

The proposed mining project will comply with the provisions of the Public Health Act.

4.3.4 Environmental Management and Coordination (Water Quality) Regulations, 2006

These regulations provide protection to ground water or surface water from pollution by providing the limits and parameters of pollutants in treated wastewater which can be discharged into the environment.

Relevant provisions of this regulation applicable to the proposed project include:-

- Every person shall refrain from any act which will directly or indirectly cause pollution and it shall be immaterial whether or not the water source was polluted before the enactment of these regulations;
- No person shall throw or cause to flow into or near a water source any liquid, solid or gaseous substance or deposit any such substance as to cause pollution;
- Discharge of effluent from sewer must be licensed according to the act;
- Water abstraction must only be done after approval of an Environmental Impact Assessment study.

4.3.5 Environmental Management and Coordination (Waste Management)

Regulations, 2006

Part II of these regulations lists the responsibility of the waste generator and prescribes the proper mechanism of handling all waste through segregation and finally proposes environmental management programme through implementation of cleaner production mechanisms.

Relevant provisions of this regulation include:-

- Prohibition of any waste disposal on a public highway, street, road, recreational area or in any public place except in designated waste receptacle
- All waste generated to be collected, segregated and disposed in a manner provided for under these regulations
- All waste generators to minimize waste generated by adopting cleaner production methods
- All waste transporters to be licensed according to the Act
- Collection and transportation of the waste to be done in such a manner not to cause scattering of the waste
- The vehicle and equipment for waste transportation to be in such a manner not to cause scattering or escape of the waste

The proponent should ensure that the waste is managed in line with the provisions of these regulations.

4.3.6 Environmental Management and Coordination (Air Quality) Regulations, 2014

The objective of these Regulations is to provide for prevention, control and abatement of air pollution to ensure clean and healthy ambient air. The general prohibitions state that no person shall cause the emission of air pollutants listed under First Schedule (priority air pollutants) to exceed the ambient air quality levels as stipulated under the provisions of the Seventh Schedule (Emission limits for controlled and non-controlled facilities) and Second Schedule (Ambient air quality tolerance limits). The proponent will be guided by provisions of this act, during operation phase. Air quality monitoring will be guided by the standards stipulated thereof.

5. BASELINE INFORMATION

5.1 Biodiversity

The proposed project site is rich in biodiversity. Flora at the proposed project site includes trees, shrubs, herbs, grasses and sedge. Fauna at the proposed project site include herpetofauna mainly reptiles and amphibians, invertebrate and avifauna.

5.1.1 Flora diversity

Flora diversity at the proposed project site includes trees, shrubs, herbs, grasses and sedge. Trees at the proposed project site include *Azadirachta indica* (Neem tree), *Adansonia digitata* (Baobab), *Albizia gummifera* (Mchani mbao), *Manilicara sulcata, Tamarindus indica*. Table 3 is a list of flora at the proposed project site.



Plate 4: A bush of neem at the proposed project site

Table 3: Species of trees observed

Genus	Species	
Acacia	nilotica	
Tamarindus	indica	
Commiphora	edulis	

Adansonia	digitata
Manilkara	sansibarensis
Berchemia	discolour
Grewia	bicolour
Flacourtia	indica
Terminalia	brevipes
Ziziphus	mauritiana
Prosopis	juliflora

5.1.2 Fauna diversity

Fauna at the proposed project site include herpetofauna mainly reptiles and amphibians, invertebrate mainly insect pollinators; beetles, ants, and avifauna. Reptiles and amphibians include Black-lined plated lizard (*Gerrhosaurus nigrolineatus*), Puff Adder (*Bitis arietans*), Black mamba (*Latastia longicaudata*), Flap-necked chameleon, python and green mamba. Invertebrates observed at the proposed project site include pollinators of the bee family mainly *Apis melifera*, butterflies mainly *Papilio demodocus*, *Junonia oenone* and *Euphaedra neophron and* grasshopper (*Byblia ilithyia*). Avifauna at the site include Golden Pipit (*Tmetothylacus tenellus*), Malindi Pipit (*Anthus melindae*), Spotted Morning-thrush (*Cichladusa guttata*), Cattle Egret (*Bubulcus ibis*), Namaqua Dove (*Oena capensis*).

Table 4: Species of butterflies observed in and in the neighborhood of the project site

Genus	Species	Genus	Species
Azanus	jesous	Нуроlусаепа	philippus
Tirumala	petiverana	Colotis	danae
Physcaeneura	leda	Colitis	euippe
Belenois	thysa	Junonia	orithya
Belenois	aurota	Junonia	natalica
Phalanta	phalantha	Colitis	daira
Acraea	insignis	Eurema	regularis
Zizula	hylax	Deudorix	antalus
Papilio	demodocu	Byblia	ilithyia
Pardopsis	punctatissima	Catopsilia	florella

Salamis	parhassus	Colitis	vesta
Tuxentius	calice	Colotis	protomedia
Vanessa	cardui	Colotis	vesta
Ypthima	asterope	Cupidopsis	iobates
Zizina	antanossa	Danaus	chrysippus
Acraea	eponina	Eurema	floricola
Amauris	niavius	Eurytela	dryope
Amauris	ochlea	Freyeria	trochylus
Anthene	butleri	Graphium	angolanus
Axiocerses	harpax	Hypolimnas	misippus
Baliochila	hildegarda	Junonia	hierta
Belenois	creona	Junonia	oenone



Plate 5: Ricinus communis growing at the edge of the access road

Table 5: Species of shrubs

Genus	Species	Species		
Cassia	occidentalis			
Aeschynomene	indica			
Sansevieria	suffruticosa			
Tephrosia	villosa			
Calotropis	procera			
Lawsonia	inermis			
Melhania	ovata			
Solanum	incanum			
Thilachium	africanum			
Triumfetta	rhomboidea			
Waltheria	indica			
Strychnos	spinosa			
Grewia	plagiophylla			
Grewia	plagiophylla			
Grewia	forbesii			
Flueggea	virosa			
Agave	sisalana			
Ricinus	communis			
Hibiscus	vitifolius			

Table 6: Species of birds observed in and in the neighborhood of proposed project site

Species	Common Name
Anthus melindae	Malindi Pipit
Ploceus cucullatus	Village Weaver
Anthus cinnamomeus	Grassland Pipit
Platalea alba	African Spoonbill
Glareola pratincola	Collared Pratincole
Turtur chalcospilos	Emerald-spotted Wood-dove
Ardea melanocephala	Black-headed Heron
Bubulcus ibis	Cattle Egret
Anastomus lamelligerus	African Openbill
Halcyon leucocephala	Grey-headed Kingfisher

5.2 Baseline air quality/particulate matter survey

Air quality remains a valued component in this assessment because of its fundamental significance to the well-being of humans, flora and fauna. This air quality baseline report forms part of a comprehensive baseline study of the proposed limestone mining and quarrying activities for the Mombasa Cement Limited. The purpose of this baseline environmental study was to determine conservative background ambient concentrations for contaminants of concern at the three proposed project areas of Roka, Chumani, and Matsangoni. Ambient air quality was done using the Aeroqual portable air quality device. Active method of monitoring was used during exercise. Ambient air quality was done for thirty monitoring locations and the following parameters were monitored:

- Particulate matter (PM₁₀)
- Particulate matter (PM_{2.5})

5.2.1 Rationale for Monitoring Parameter Selection

A quarry is a place where rocks, sand, or minerals are extracted from the surface of the Earth. A quarry is a type of mine called an open pit mine because it is open to the Earth's surface. Another type of mine, a sub-surface mine, consists of underground tunnels or shafts. Quarrying is an activity where stones are dug for the purpose of being used in building, making roads through cutting, digging, or blasting. Quarrying is a huge supporter of local economic development: as the use of extracted material enhances trade, creating jobs for most people who depend on this for their livelihoods aside from other economic activities. Rock quarrying and stone crushing is a global phenomenon and has been the cause of concern everywhere in the world, including the advanced countries. Quarrying activity is a necessity that provides much of the materials used in traditional hard flooring, such as granite, limestone, marble, sandstone, slate and even just clay to make ceramic tiles. However, like many other man-made activities (anthropogenic factors), quarrying activities cause significant impact on the environment (Okafor, 2006). Dust from quarry sites is a major source of air pollution, although the severity will depend on factors like the local microclimate conditions, the concentration of dust particles in the ambient air, the size of the dust particles and their chemistry. Dust is one of the most visible, invasive, and potentially irritating impacts associated with quarrying, and its visibility often raises concerns that are not directly proportional to its impact on human health and the environment (Howard and Cameron, 1998). Dust may occur as fugitive dust from excavation, from haul roads, and from blasting, or can be from point sources, such as open cast mining, crushing, and screening

(Langer, 2001). Site conditions that affect the impact of dust generated during extraction of aggregate and dimension stone include rock properties, moisture, ambient air quality, air currents and prevailing winds, the size of the operation, proximity to population centers, and other nearby sources of dust. Dust concentrations, deposition rates, and potential impacts tend to decrease rapidly away from the source (Howard and Cameron, 1998). The air pollution is not only a nuisance (in terms of deposition on surfaces) and possible effects on health, in particular for those with respiratory problems but dust can also have physical effects on the surrounding plants, such as blocking and damaging their internal structures and abrasion of leaves and cuticles, as well as chemical effects which may affect long-term survival (Guach, 2001). The targeted parameters were monitored using proven sampling and analytical methods.

5.2.2 Monitoring Objectives

To measure the concentrations of fugitive particulates and gaseous parameters at selected locations (thirty) surrounding the project area and results compared to the Environmental Management and Coordination (Air Quality) Regulation 2014 for compliance purpose.

5.2.3 Methodology

It is important to accurately determine a baseline against which predicted effects can be gauged and assessed for any environmental effects' assessment. Detailed baseline data is also particularly desirable for air quality effect assessments involving modeling, as it enables modeled concentrations for the baseline situation to be correlated with monitored concentrations. This process enables greater confidence to be placed in model predictions. Baseline ambient air quality data were obtained from an ambient air quality monitoring program.

The ambient air monitoring stations for this study consist of thirty specific monitoring stations. Information for the Baseline Report is presented based on air monitoring completed for instantaneous weighted averages at each monitoring location.

5.2.3.1 Active monitoring for gaseous and particulate parameters

It is important to accurately determine a baseline against which predicted effects can be gauged and assessed for any environmental effects' assessment. Active monitoring by use of real time equipment (Aeroqual) was deployed. The aeroqual gas meter series, a state-of-theart gas analyser sensor is used for measurements The gas sensitive semiconductor (GSS)

sensor uses proprietary sensing material, built in automatic Correction (ABC) and interference rejection. This combination results in ppb resolution and a highly linear response. The gas sensitive electrochemical (GSE) sensors generate nano-amp currents proportional to the gas concentration. Aeroqual uses low noise electronics to capture these signals resulting in low detection levels. The laser particle counter (LPC) for Particulate Matter (PM) measurements uses optimized signal processing using low noise electronics added algorithms to correct for interferences. The non-dispersive infrared (NDIR) sensor uses infra-red light, a narrow band-pass filter and photodiode to measure the intensity of light at the gas absorption band. The light intensity is proportional to the gas concentration.

5.2.3.2 Instrumentation

- Aeroqual portable air quality monitor
- Geographical positioning system (GPS)
- Digital camera

5.2.4 Monitoring Frequency

Air quality monitoring was conducted on 14th and 15th November 2020 for thirty monitoring locations within Roka, Chumani, and Matsangoni areas.

5.2.5 Monitoring Location

The air quality monitoring was conducted at the three target areas of the proposed project site namely, Roka, Chumani, and Matsangoni all located in Kilifi County. Thirty monitoring stations were selected. Point selection was based on the size of the site, maintaining a 10m minimum radius between each point. Detailed baseline monitoring report is in appendix 7.

Table 7: A table of monitoring locations, parameters tested & GPS coordinates

Area Monitored	Parameters tested	GPS Coordinates	Weather and wind speed and direction
Point 1(Near Uyombo girls' Secondary	PM _{2.5} and PM ₁₀	S 03 25'212"	Weather was sunny. Wind speed was 14km/hr moving from
school and close to an old quarry site)		E 039.57'271"	North east to South
Point 2 (Close to Uyombo primary	$PM_{2.5}$ and PM_{10}	S 03 22'503"	Weather was sunny. Wind speed was 14km/hr moving from
school and surrounded by bushes).		E .039.55'323"	North east to South
Point 3 Control point far from MCL	PM _{2.5} and PM ₁₀	S 03 22'825"	Weather was sunny. Wind speed was 14km/hr moving from
property		E 039.55'581	North east to South
Point 4 Control point Mkongani area	$PM_{2.5}$ and PM_{10}	S 03 28'656"	Weather was sunny. Wind speed was 14km/hr moving from
		E 039.55'890	North east to South
Point 5Near residentials area	PM _{2.5} and PM ₁₀	S 03 28'656"	Weather was sunny. Wind speed was 14km/hr moving from
		E 039.54'976	North east to South
Point 6 Near old blocks making quarry	PM _{2.5} and PM ₁₀	S 03 28'656"	Weather was sunny. Wind speed was 14km/hr moving from
		E 039.54'976	North east to South
Point 7 Near residential area	PM _{2.5} and PM ₁₀	S 03 28'130"	Weather was sunny. Wind speed was 14km/hr moving from
		E 039.55'076	North east to South
Point 8 Boundary wall between MCL	PM _{2.5} and PM ₁₀	S 03 28'191"	Weather was sunny. Wind speed was 14km/hr moving from
land and Government land		E 039.56'976	North east to South
Point 9 Middle of the bush area (Roka)	PM _{2.5} and PM ₁₀	S 03 28'656"	Weather was sunny. Wind speed was 14km/hr moving from
		E 039.54'976	North east to South
Point 10 Middle of the bush area (Roka)	$PM_{2.5}$ and PM_{10}	S 03 27'792"	Weather was sunny. Wind speed was 14km/hr moving from
		E 039.58'471	North east to South
Point 11 (Near residents Chumani)	PM _{2.5} and PM ₁₀	S 03 23'295"	Weather was sunny. Wind speed was 12km/hr moving from
		E 039.55.827"	North east to South
Point 12 (Near residents Chumani)	PM _{2.5} and PM ₁₀	S 03 27'7499"	Weather was sunny. Wind speed was 11km/hr moving from
		E 039.55'825	North east to South
Point 13 (At quarry site) Roka	PM _{2.5} and PM ₁₀	S 03 27'7491"	Weather was sunny. Wind speed was 12km/hr moving from
		E 039.56'085	North east to South
Point 14 (At bushy area near old quarry	PM _{2.5} and PM ₁₀	S 03 277491"	Weather was sunny. Wind speed was 12km/hr moving from
site -Roka)		E 039.56'085	North east to South
Point 15 (Middle of the bushy forest	PM _{2.5} and PM ₁₀	S 03 27'7491"	Weather was sunny. Wind speed was 14km/hr moving from
area).		E 039.56'085	North east to South
Point 16 (At block making quarry) Roka	PM _{2.5} and PM ₁₀	S 03 27'347"	Weather was sunny. Wind speed was 14km/hr moving from
		E 039.56'463	North east to South
Point 17 (Near residential area)	PM _{2.5} and PM ₁₀	S 03 26'653"	Weather was sunny. Wind speed was 13km/hr moving from
		E 039.56'721	North east to South
Point 18 (Near old quarry area)	PM _{2.5} and PM ₁₀	S 03 26'277"	Weather was sunny. Wind speed was 12km/hr moving from
		E 039.56'459	North east to South

Point 19 (Middle of the bushy forest)	PM _{2.5} and PM ₁₀	S 03 25'472"	Weather was sunny. Wind speed was 14km/hr moving from
-		E 039.56'654	North east to South
Point 20 (Middle of the bushy forest).	$PM_{2.5}$ and PM_{10}	S 03 25'247"	Weather was sunny. Wind speed was 14km/hr moving from
		E 039.56'825	North east to South
Point 21(Control point 3) Matsangoni	PM _{2.5} and PM ₁₀	S 03 23'295"	Weather was sunny. Wind speed was 14km/hr moving from
area		E 039.55.827"	North east to South
Point 22 (Near old residential area)	PM _{2.5} and PM ₁₀	S 03 27'7499"	Weather was sunny. Wind speed was 14km/hr moving from
		E 039.55'825	North east to South
Point 23 (Middle of the bushy forest	PM _{2.5} and PM ₁₀	S 03 27'7491"	Weather was sunny. Wind speed was 12km/hr moving from
area-Chumani)		E 039.56'085	North east to South
Point 24 (Middle of the bushy forest-	PM _{2.5} and PM ₁₀	S 03 27'7491"	Weather was sunny. Wind speed was 13km/hr moving from
Roka)		E 039.56'085	North east to South
Point 25 (Middle of the bushy forest	PM _{2.5} and PM ₁₀	S 03 27'7491"	Weather was sunny. Wind speed was 13km/hr moving from
Roka)		E 03936'085	North east to South
Point 26 (Middle of the bushy forest-	$PM_{2.5}$ and PM_{10}	S 03 27'347"	Weather was sunny. Wind speed was 14km/hr moving from
Roka)		E 039.56'463	North east to South
Point 27 (Middle of the bushy forest-	$PM_{2.5}$ and PM_{10}	S 03 26'653"	Weather was sunny. Wind speed was 13km/hr moving from
Roka)		E 039.56'721	North east to South
Point 28 (Middle of the bushy forest-	PM _{2.5} and PM ₁₀	S 03 26'277"	Wind speed was 12km/hr moving from North east to South
Roka)		E 039.56'459	
Point 29 (Middle of the bushy forest-	PM _{2.5} and PM ₁₀	S 03 25'472"	Wind speed was 14km/hr moving from North east to South
Roka)		E 039.56'654	
Point 30 (Middle of the bushy forest-	PM _{2.5} and PM ₁₀	S 03 25'247"	Wind speed was 14km/hr moving from North east to South
Roka)		E 039.56'825	

5.2.6 Results of the air quality monitoring

Table 8: Sampling Locations and Measurement Results

Monitoring Locations	Particulate Matter PM _{2.5} (µg/m ³)	EMC (Air Quality) Regulations 2014	Comments	Particulate Matter PM ₁₀ (µg/m ³)	EMC (Air Quality) Regulations 2014	Comments
Point 1	10	75	Complies	22	150	Complies
Point 2	8	75	Complies	18	150	Complies
Point 3	12	75	Complies	25	150	Complies
Point 4	15	75	Complies	31	150	Complies
Point 5	11	75	Complies	24	150	Complies
Point 6	17	75	Complies	43	150	Complies
Point 7	7	75	Complies	19	150	Complies
Point 8	8	75	Complies	28	150	Complies

Point 9	10	75	Complies	31	150	Complies
Point 10	13	75	Complies	36	150	Complies
Point 11	12	75	Complies	34	150	Complies
Point 12	11	75	Complies	25	150	Complies
Point 13	21	75	Complies	53	150	Complies
Point 14	10	75	Complies	24	150	Complies
Point 15	9	75	Complies	26	150	Complies
Point 16	31	75	Complies	58	150	Complies
Point 17	11	75	Complies	21	150	Complies
Point 18	14	75	Complies	27	150	Complies
Point 19	12	75	Complies	31	150	Complies
Point 20	11	75	Complies	29	150	Complies
Point 21	14	75	Complies	27	150	Complies
Point 22	10	75	Complies	19	150	Complies
Point 23	8	75	Complies	21	150	Complies
Point 24	16	75	Complies	27	150	Complies
Point 25	13	75	Complies	23	150	Complies
Point 26	10	75	Complies	27	150	Complies
Point 27	11	75	Complies	25	150	Complies
Point 28	21	75	Complies	32	150	Complies
Point 29	10	75	Complies	22	150	Complies
Point 30	9	75	Complies	33	150	Complies

5.3 Baseline Noise Levels

5.3.1 Background

Noise, which is often referred to as unwanted sound, is typically characterized by the intensity, frequency, periodicity (continuous or intermittent) and the duration of sound. Sound is the result of pressure changes in the air caused by vibration (Thompson, 1994). Sound is measured as sound level in units of decibels, dB. The human ear responds differently to sounds at different frequencies. This is demonstrated by the fact that we hear higher pitched sounds more easily than lower ones of the same magnitude. To compensate for the different "loudness" as perceived by humans, a standard weighting curve is applied to measured sound levels. The weighting curve represents the frequency response of the human ear and is labeled as dBA ("A" weighted decibels).

A-Weighted Frequency Response




Figure 3: The A-Weighted frequency reponse

The response of the human ear varies with the sound level. At higher levels, 100dB and above, the ear's response is flatter, as shown in the C-Weighted Response to the right.

Although the A-Weighted response is used for most applications, C-Weighting is also available on many sound level meters. C Weighting is usually used for Peak measurements and in some entertainment noise measurement, where the transmission of bass noise can be a problem. C-weighted measurements are expressed as dBC or dB(C).

C-Weighted Frequency Response




Figure 4: The C-Weighted frequency response

Excessive noise pollution, from various industrial/manufacturing activities, can have harmful effects on the humans, plants, animals, and trees constantly exposed to it. Human noise can have ripple effects on long-lived plants and trees that can last for decades even after the sources of noise subside. Many plants and trees rely on birds and other animals to deliver pollen from one flower or tree to the next, or to disperse their seeds, but many animals are adapting to the noise by changing their behavior or moving to quieter locales. Consequently, noise pollution is altering the landscape of plants and trees, which depend on noise-affected animals to pollinate them and spread their seeds. For these reasons environmental monitoring is paramount to objectively assess noise and to quantify and evaluate its potential impact to develop comprehensive conservation and control programs.

5.3.2 Monitoring Parameters

Noise is measured by use of equivalent noise levels.

Leq is the preferred method to describe sound levels that vary over time, resulting in a single decibel value, which takes into account the total sound energy over the period of time of interest. Leq-equivalent continuous noise level: Noise levels often fluctuate over a wide range with time. For example in the middle of the night the level might go down as low as 30 dB (A) with occasional passing vehicles of 70dB (A) or more. Later comes the dawn chorus followed by the general noises of the day before relative peace returns in the late evening. Alternatively, it may be an activity with different noise emissions throughout the day or week, with deliveries, intermittent compressors, and lots of varying noisy processes on top of

the routine production noise levels. This is where the Leq noise or equivalent continuous noise level meter comes in. This meter faithfully follows all the fluctuations, stores them in its memory and at the end of the measurement calculates an 'average energy' or Leq value. When we say average, this is not a simple arithmetic average because we are measuring in decibels which are logarithmic values. So our meter converts the dB values to sound pressure levels, adds them all up then divides by the number of samples and finally converts this equivalent level back to decibels-dBs.

LAeq-It is common practice to measure noise levels using the A-weighting setting built into all sound level meters. In which case the term is properly known as LAeq and the results should say so - for example LAeq = 73 dB or Leq = 73 dBA A good Leq sound level meter samples and 'captures' the noise levels 16 times a second which means over an hour it makes $16 \times 60 \times 60 = 57600$ calculations, not difficult for a modern meter but quite an achievement a few years back.

LCeq-'C' weighting gives much more emphasis to low frequency sounds than the 'A' weighting response and is essentially flat or linear between 31,5Hz and 8kHz, the two-3dB or 'half power' points. In addition, Peak Sound Pressure measurements are made using the 'C' Frequency Weighting. Measurements made with this frequency weighting will be displayed as dB(C) or dBC. For example, as LCeq, LCPeak, LCE etc where the C shows the use of 'C' Weighting.

Leq noise levels are logarithmic (dB) values and cannot be added directly. A doubling of sound level results in a measured increase of 3 dB, four identical sources in a room would increase the noise level by 6 dB and so on. This works both ways, say 10 similar machines in a room produce 100 dBA then removing one machine completely will only reduce the overall noise level to 0.5 dBA, you would need to silence or remove 50% of the machines to achieve a 3 dB reduction. Leq is also used in the assessment of noise dose or sound exposure in the workplace and the 3 dB 'doubling rule' applies to time and/or level.

5.3.3 Other Parameters

- Lmax: Maximum Sound Level: level during a measurement period or a noise event and is not necespeak.
- Lmin: Minimum Sound Level: during a measurement period or a noise event.

- L10 is the level exceeded for 10% of the time. For 10% of the time, the sound or noise has a sound pressure level above L10. For the rest of the time, the sound or noise has a sound pressure level at or below L10. These higher sound pressure levels are probably due to sporadic or intermittent events. L10 is often used when assessing traffic noise and in planning applications: L10 is the level exceeded for 10% of the time and takes account of any annoying peaks in noise.
- L50 is the level exceeded for 50% of the time. It is statistically the mid-point of the noise readings. It represents the median of the fluctuating noise levels.
- L90 is the level exceeded for 90% of the time. For 90% of the time, the noise level is above this level. It is generally considered to be representing the background or ambient level of a noise environment. L90 is often used to quantify the background noise levels in assessments of noise pollution and nuisance noise from industrial sources.

5.3.4 Noise monitoring Objectives

- Baseline monitoring was done to measure and quantify the current ambient noise levels at the selected monitoring locations to represent the ambient noise levels within Roka, Chumani and Matsangoni before the commencement of the limestone mining project.
- To correlate the results of the findings against Environmental Management and Coordination (Noise and Excessive Vibration) Regulation 2009 for compliance purpose.

5.3.5 Monitoring Methodology

Ambient sound levels are the cumulative effects of innumerable sounds generated at various instances both far and near. High measurements may not necessarily mean that noise levels in the area are high. Similarly, a low sound level measurement will not necessarily mean that the area is always quiet, as sound levels will vary over seasons, time of the day, faunal characteristics, vegetation in the area and meteorological conditions (especially wind). This is excluding the potential effect of sounds from anthropogenic origin. It is assumed that the measurement location represents other residential dwellings in the area (similar environment). Some numerous factors that could impact on ambient sound levels at the time of monitoring including; the distance to closest trees, number and type of trees as well as the height of trees; available habitat and food for birds and other animals; distance to residential dwelling, locomotive sources (motorbikes, trucks & personal vehicles) and type of equipment used at the site (grinders) was considered. Determination of existing feeder roads traffic and other noise sources of significance was done, and notes taken. Vehicular noise is one of the

major components and could be a significant source of noise during busy periods. This reconnaissance showed that the vehicular activity at the site was mainly comprised of trucks loading blocks. Noise levels were determined using a Sound analyzer Meter with built-in octave band filters which does real time 1/1 and 1/3 octave analysis. The sound level meter was mounted on at 2.0m above ground level and 3.5m away from any sound reflecting surfaces at a boundary position and measurements are taken at timed intervals over 10 minutes and stored in SLM's memory. The SLM was oriented towards the facility of interest for each measurement taken. TES sound level meter was placed on the microphone to reduce any wind interference during measurements. The sound level meter, which was within its calibration period, was used at the time of monitoring.

In addition, the equivalent noise level (LAeq and LCeq), the maximum sound pressure level (LAFmax, LCFmax) and the minimum sound pressure level (LAFmin, LCFmin) during that measurement period were recorded. Factors to consider such as time, duration and predictability of the noise emission, amplitude and frequency of the noise emission, nature of the source, location of noise sensitive receptors, ambient and background noise level, nature and character of the locality, presence of special acoustic characteristics and the incongruity or familiarity of the noise during Noise Monitoring and site placement were put into consideration.

5.3.6 Parameters and score criteria

After finding various activities, aspects and impacts, identification of the significant aspects was done. It entirely depended on the management of the system or industry to give scaling factor. The table below shows six factors naming as A to F (top row) and column 1 to 6 shows rating scheme with minimum as 1 and maximum marks as 10 depending upon their severity.

5.3.6.1 Procedure of significance evaluation

For evaluation processes, the various activities of the measurement sites are rated based on parameters and score criteria given in the table below and a benchmark of 75 units is taken as a deciding factor. If the total unit of any aspect for an activity comes out to be more than 75, then the aspect can be considered as significant otherwise insignificant.

Table 9: Parameters and score criteria

A-Quantity	B-Occurrence	C-Impact	D-Detection	E-Controls	F-Legislation
1-5	1-6	1-6	1-5	1-5	1 and 10
5-High	6-Continuous	6-Fatal to	5-More than 24	5-Absence or	10-Not meeting
		human life	hours	no effective	legislation/control
				controls	limits
3-Moderate	5-Several times a	5-Health effects	4-Within 24	4-Mechanism	1-In compliance
	day		hours	in place but not	
				reliable	
1-Low	4-Once a day	4-Affects flora	3-Within 8	3-Control need	-
		and fauna	hours	human	
				intervention	
-	3-Once a week	3-Resource	2-Within 1 hour	2-Has inbuilt	-
		consumption		secondary	
		1		control	
-	2-Once a month	2-Discormfort,	1-Immediately	1-Available and	-
	or less frequent	Acid rain,		effective at	
		Nuisance		source	
-	1-Very Rare	1-Negligible	-	-	-
		visual impact			

5.3.7 Tools and Equipment

The following instruments were used during monitoring works:

- SLM TES 1358 C
- Geographic Positioning System (GPS)
- Digital camera

5.3.8 Monitoring Frequency

Baseline ambient levels monitoring was done on 14th and 15th November 2020 for thirty monitoring locations within Roka, Chumani, and Matsangoni areas.

5.3.9 Monitoring Location

The audiometric survey was conducted at the two target areas of the proposed project site namely: Roka and Matsangoni all located in Kilifi County. Thirty monitoring stations were selected. Point selection was based on the size of the site, maintaining a 10m minimum radius between each point. Detailed report of ambient noise monitoring is in appendix 8.

Table 10: A table of monitoring locations, parameters tested & GPS coordinates

Area Monitored	Parameters tested	GPS Coordinates	Weather and wind speed and direction
Point 1(Near Uyombo girls' Secondary	PM _{2.5} and PM ₁₀	S 03 25'212"	Weather was sunny. Wind speed was 14km/hr moving from
school and close to an old quarry site)		E 039.57'271"	North east to South
Point 2 (Close to Uyombo primary	PM _{2.5} and PM ₁₀	S 03 22'503"	Weather was sunny. Wind speed was 14km/hr moving from
school and surrounded by bushes).		E .039.55'323"	North east to South
Point 3 Control point far from MCL	PM _{2.5} and PM ₁₀	S 03 22'825"	Weather was sunny. Wind speed was 14km/hr moving from
property		E 039.55'581	North east to South
Point 4 Control point Mkongani area	PM _{2.5} and PM ₁₀	S 03 28'656"	Weather was sunny. Wind speed was 14km/hr moving from
•		E 039.55'890	North east to South
Point 5Near residential area	PM _{2.5} and PM ₁₀	S 03 28'656"	Weather was sunny. Wind speed was 14km/hr moving from
		E 039.54'976	North east to South
Point 6 Near old blocks making quarry	PM _{2.5} and PM ₁₀	S 03 28'656"	Weather was sunny. Wind speed was 14km/hr moving from
		E 039.54'976	North east to South
Point 7 Near residential area	PM _{2.5} and PM ₁₀	S 03 28'130"	Weather was sunny. Wind speed was 14km/hr moving from
		E 039.55'076	North east to South
Point 8 Boundary wall between MCL	PM _{2.5} and PM ₁₀	S 03 28'191"	Weather was sunny. Wind speed was 14km/hr moving from
land and Government land		E 039.56'976	North east to South
Point 9 Middle of the bush area (Roka)	PM _{2.5} and PM ₁₀	S 03 28'656"	Weather was sunny. Wind speed was 14km/hr moving from
		E 039.54'976	North east to South
Point 10 Middle of the bush area (Roka)	PM _{2.5} and PM ₁₀	S 03 27'792"	Weather was sunny. Wind speed was 14km/hr moving from
		E 039.58'471	North east to South
Point 11 (Near residents Chumani)	PM _{2.5} and PM ₁₀	S 03 23'295"	Weather was sunny. Wind speed was 12km/hr moving from
		E 039.55.827"	North east to South
Point 12 (Near residents Chumani)	PM _{2.5} and PM ₁₀	S 03 27'7499"	Weather was sunny. Wind speed was 11km/hr moving from
		E 039.55'825	North east to South
Point 13 (At quarry site) Roka	PM _{2.5} and PM ₁₀	S 03 27'7491"	Weather was sunny. Wind speed was 12km/hr moving from
		E 039.56'085	North east to South
Point 14 (At bushy area near old quarry	PM _{2.5} and PM ₁₀	S 03 277491"	Weather was sunny. Wind speed was 12km/hr moving from
site -Roka)		E 039.56'085	North east to South
Point 15 (Middle of the bushy forest	PM _{2.5} and PM ₁₀	S 03 27'7491"	Weather was sunny. Wind speed was 14km/hr moving from
area).		E 039.56'085	North east to South
Point 16 (At block making quarry) Roka	PM _{2.5} and PM ₁₀	S 03 27'347"	Weather was sunny. Wind speed was 14km/hr moving from
		E 039.56'463	North east to South
Point 17 (Near residential area)	PM _{2.5} and PM ₁₀	S 03 26'653"	Weather was sunny. Wind speed was 13km/hr moving from
		E 039.56'721	North east to South
Point 18 (Near old quarry area)	PM _{2.5} and PM ₁₀	S 03 26'277"	Weather was sunny. Wind speed was 12km/hr moving from
		E 039.56'459	North east to South

Point 19 (Middle of the bushy forest)	PM _{2.5} and PM ₁₀	S 03 25'472"	Weather was sunny. Wind speed was 14km/hr moving from
-		E 039.56'654	North east to South
Point 20 (Middle of the bushy forest).	$PM_{2.5}$ and PM_{10}	S 03 25'247"	Weather was sunny. Wind speed was 14km/hr moving from
-		E 039.56'825	North east to South
Point 21(Control point 3) Matsangoni	PM _{2.5} and PM ₁₀	S 03 23'295"	Weather was sunny. Wind speed was 14km/hr moving from
area		E 039.55.827"	North east to South
Point 22 (Near old residential area)	PM _{2.5} and PM ₁₀	S 03 27'7499"	Weather was sunny. Wind speed was 14km/hr moving from
		E 039.55'825	North east to South
Point 23 (Middle of the bushy forest	$PM_{2.5}$ and PM_{10}	S 03 27'7491"	Weather was sunny. Wind speed was 12km/hr moving from
area-Chumani)		E 039.56'085	North east to South
Point 24 (Middle of the bushy forest-	PM _{2.5} and PM ₁₀	S 03 27'7491"	Weather was sunny. Wind speed was 13km/hr moving from
Roka)		E 039.56'085	North east to South
Point 25 (Middle of the bushy forest	PM _{2.5} and PM ₁₀	S 03 27'7491"	Weather was sunny. Wind speed was 13km/hr moving from
Roka)		E 03936'085	North east to South
Point 26 (Middle of the bushy forest-	$PM_{2.5}$ and PM_{10}	S 03 27'347"	Weather was sunny. Wind speed was 14km/hr moving from
Roka)		E 039.56'463	North east to South
Point 27 (Middle of the bushy forest-	PM _{2.5} and PM ₁₀	S 03 26'653"	Weather was sunny. Wind speed was 13km/hr moving from
Roka)		E 039.56'721	North east to South
Point 28 (Middle of the bushy forest-	PM _{2.5} and PM ₁₀	S 03 26'277"	Wind speed was 12km/hr moving from North east to South
Roka)		E 039.56'459	
Point 29 (Middle of the bushy forest-	PM _{2.5} and PM ₁₀	S 03 25'472"	Wind speed was 14km/hr moving from North east to South
Roka)		E 039.56'654	
Point 30 (Middle of the bushy forest-	PM _{2.5} and PM ₁₀	S 03 25'247"	Wind speed was 14km/hr moving from North east to South
Roka)		E 039.56'825	

5.3.10 Results of the Noise monitoring

Table 11: Presentation of findings of noise monitoring including various regulatory limits guidelines and site remarks and notes

Measurement site	Measured sound	pressure level (Noise	e dBA)	EMC Limits	World Bank Limits	WHO Limits	OSH Exposure Limits
	LAeq	Lmax	Lmin	LAeq	LAeq	LAeq	LAeq
Point 1(Near Uyombo girls' Secondary school and close to an old quarry site)	48.4	58.8	30.9	55	70	85	90
Point 2 (Close to Uyombo primary	50.6	64.2	32.8	55	70	85	90

	1	1	T		Т	T
48.3	58.6	39.1	55	70	85	90
54.1	58.8	30.9	55	70	85	90
50.2	64.2	32.8	55	70	85	90
50.4	58.6	39.1	55	70	85	90
53.5	65.4	38.6	55	70	85	90
48.7	62.0	32.1	55	70	85	90
47.5	56.0	30.6	55	70	85	90
41.3	52.1	31.6	55	70	85	90
42.6	50.3	32.8	55	70	85	90
50.5	62.6	32.3	55	70	85	90
65.7	77.8	56.8	55	70	85	90
51.2	67.7	38.1	55	70	85	90
49.0	65.7	44.6	55	70	85	90
	50.4 53.5 48.7 47.5 41.3 42.6 50.5 65.7 51.2	54.1 58.8 50.2 64.2 50.4 58.6 53.5 65.4 48.7 62.0 47.5 56.0 41.3 52.1 42.6 50.3 50.5 62.6 65.7 77.8 51.2 67.7	54.1 58.8 30.9 50.2 64.2 32.8 50.4 58.6 39.1 53.5 65.4 38.6 48.7 62.0 32.1 47.5 56.0 30.6 41.3 52.1 31.6 42.6 50.3 32.8 50.5 62.6 32.3 65.7 77.8 56.8 51.2 67.7 38.1	54.1 58.8 30.9 55 50.2 64.2 32.8 55 50.4 58.6 39.1 55 53.5 65.4 38.6 55 48.7 62.0 32.1 55 47.5 56.0 30.6 55 41.3 52.1 31.6 55 42.6 50.3 32.8 55 50.5 62.6 32.3 55 65.7 77.8 56.8 55 51.2 67.7 38.1 55	54.1 58.8 30.9 55 70 50.2 64.2 32.8 55 70 50.4 58.6 39.1 55 70 53.5 65.4 38.6 55 70 48.7 62.0 32.1 55 70 47.5 56.0 30.6 55 70 41.3 52.1 31.6 55 70 42.6 50.3 32.8 55 70 50.5 62.6 32.3 55 70 65.7 77.8 56.8 55 70 51.2 67.7 38.1 55 70	54.1 58.8 30.9 55 70 85 50.2 64.2 32.8 55 70 85 50.4 58.6 39.1 55 70 85 53.5 65.4 38.6 55 70 85 48.7 62.0 32.1 55 70 85 47.5 56.0 30.6 55 70 85 41.3 52.1 31.6 55 70 85 42.6 50.3 32.8 55 70 85 50.5 62.6 32.3 55 70 85 65.7 77.8 56.8 55 70 85 51.2 67.7 38.1 55 70 85

of the bushy forest							
area).							
Point 16 (At block	77.8	98.8	65.4	55	70	85	90
making quarry)	11.8	98.8	03.4	55	/0	05	90
Roka							
Point 17 (Near	52.3	65.8	31.6	55	70	85	90
`	32.3	65.8	31.0	22	/0	85	90
residential area)	1	77.4	22.0		=0	0.	0.0
Point 18 (Near old	45.4	57.6	32.8	55	70	85	90
quarry area)							
Point 19 (Middle	50.2	61.2	32.3	55	70	85	90
of the bushy							
forest)							
Point 20 (Middle	46.5	58.2	38.1	55	70	85	90
of the bushy							
forest).							
Point 21(Control	51.2	74.1	38.1	55	70	85	90
point 3)							
Matsangoni area							
Point 22 (Near old	43.2	54.2	37.4	55	70	85	90
residential area)							
Point 23 (Middle	41.1	56.0	32.2	55	70	85	90
of the bushy forest							
area-Chumani)							
Point 24 (Middle	50.1	65.8	31.6	55	70	85	90
of the bushy							
forest-Roka)							
Point 25 (Middle	45.4	57.6	32.8	55	70	85	90
of the bushy forest							
Roka)							
Point 26 (Middle	50.2	61.2	32.3	55	70	85	90
of the bushy	00.2	01.2	02.0				
forest-Roka)							
Point 27 (Middle	46.5	58.2	38.1	55	70	85	90
of the bushy	. 5.5	30.2	30.1		. "		
forest-Roka)							
Point 28 (Middle	51.2	74.1	38.1	55	70	85	90
of the bushy	31.2	/ 1.1	30.1		, ,		
forest-Roka)							
1010st-KOKa)	1		1	1	1	I .	I .

Table 12: Determination of significance of singular diurnal results with reference to EMC regulatory limits

	Aspect	Condition	Impact	Quantity	Occurrence	Impacts	Detection	Control	Legislation	Total	Remarks (Sig/Insig)
Point 1(Near Uyombo girls' Secondary school and close to an old quarry site)	Noise	N	Hearing Impairment	3	5	1	1	3	1	45	Insignificant
Point 2 (Close to Uyombo primary school and surrounded by bushes).	Noise	N	Hearing Impairment	3	5	1	1	3	1	45	Insignificant
Point 3 Control point far from MCL property	Noise	N	Hearing Impairment	3	5	1	1	3	1	45	Insignificant
Point 4 Control point Mkongani area	Noise	N	Hearing Impairment	3	5	1	1	3	1	45	Insignificant
Point 5Near residentials area	Noise	N	Hearing Impairment	3	5	1	1	3	1	45	Insignificant
Point 6 Near old blocks making quarry	Noise	N	Hearing Impairment	3	5	1	1	3	1	45	Insignificant
Point 7 Near	Noise	N	Hearing	3	5	1	1	3	1	45	Insignificant

residential			Impairment								
area											
Point 8 Boundary wall between MCL land and Government land	Noise	N	Hearing Impairment	3	5	1	1	3	1	45	Insignificant
Point 9 Middle of the bush area (Roka)	Noise	N	Hearing Impairment	3	5	1	1	3	1	45	Insignificant
Point 10 Middle of the bush area (Roka)	Noise	N	Hearing Impairment	3	5	1	1	3	1	45	Insignificant
Point 11 (Near residents Chumani)	Noise	N	Hearing Impairment	3	5	1	1	3	1	45	Insignificant
Point 12 (Near residents Chumani)	Noise	N	Hearing Impairment	3	5	1	1	3	1	45	Insignificant
Point 13 (At quarry site) Roka	Noise	N	Hearing Impairment	3	5	1	1	3	10	450	Significant
Point 14 (At bushy area near old quarry site - Roka)	Noise	N	Hearing Impairment	3	5	1	1	3	1	45	Insignificant
Point 15 (Middle of the bushy forest area).	Noise	N	Hearing Impairment	3	5	1	1	3	1	45	Insignificant
Point 16 (At	Noise	N	Hearing	3	5	1	1	3	10	450	Significant

block making			Impairment								
quarry) Roka					_						
Point 17 (Near residential area)	Noise	N	Hearing Impairment	3	5	1	1	3	1	45	Insignificant
Point 18 (Near old quarry area)	Noise	N	Hearing Impairment	3	5	1	1	3	1	45	Insignificant
Point 19 (Middle of the bushy forest)	Noise	N	Hearing Impairment	3	5	1	1	3	1	45	Insignificant
Point 20 (Middle of the bushy forest).	Noise	N	Hearing Impairment	3	5	1	1	3	1	45	Insignificant
Point 21(Control point 3) Matsangoni area	Noise	N	Hearing Impairment	3	5	1	1	3	1	45	Insignificant
Point 22 (Near old residential area)	Noise	N	Hearing Impairment	3	5	1	1	3	1	45	Insignificant
Point 23 (Middle of the bushy forest area- Chumani)	Noise	N	Hearing Impairment	3	5	1	1	3	1	45	Insignificant
Point 24 (Middle of the bushy forest-Roka)	Noise	N	Hearing Impairment	3	5	1	1	3	1	45	Insignificant
Point 25 (Middle of the bushy	Noise	N	Hearing Impairment	3	5	1	1	3	1	45	Insignificant

forest Roka)											
Point 26	Noise	N	Hearing	3	5	1	1	3	1	45	Insignificant
(Middle of			Impairment								
the bushy											
forest-Roka)											
Point 27	Noise	N	Hearing	3	5	1	1	3	1	45	Insignificant
(Middle of			Impairment								
the bushy											
forest-Roka)											
Point 28	Noise	N	Hearing	3	5	1	1	3	1	45	Insignificant
(Middle of			Impairment								
the bushy											
forest-Roka)											
Point 29	Noise	N	Hearing	3	5	1	1	3	1	45	Insignificant
(Middle of			Impairment								
the bushy											
forest-Roka)											

5.3.11 Discussion of Noise Monitoring Results

- Noise levels measurement was done within the selected monitoring locations within Roka, Chumani, and Matsangoni. From the results, point 16 had the highest noise levels. The noise levels recorded at this point could have been as a result of block cutting operations using the block cutting machine. Vehicular and motorcycle activities were also noted at the time of monitoring.
- Point 13 had the second highest noise levels. These noise levels were attributed by could have been as a result of block making operations using the block cutting machine at the time of monitoring. The lowest noise levels were recorded at point 11, which is located near residential settlements.
- After correlation with the Noise regulatory guidelines, point 13 and 16 had noise levels above the EMC (Noise and Excessive Vibration), Regulations, 2014 tolerance limits. All other locations had noise levels below the regulatory limits.
- Upon determination of significance; Point 13 and 16 were identifies as noise significant area. This is due to the total unit obtained for these two locations is above 75 units which is used as the benchmark.
- Upon comparison with the World Bank noise regulations, all the monitoring location had noise levels within the World Bank noise regulation except for point 16 which had noise levels above 70 decibels.
- All the monitoring stations had noise levels within the World Health Organization and the Occupational Health and Safety noise regulatory guidelines.

5.3.12 Conclusions from the Noise monitoring

- Upon comparisons of results to EMC (Excessive noise and vibration) regulations of 2009, all the monitoring had noise levels within the stipulated limits with the exception of point 13 and 16.
- Upon determination of significance test, all the monitoring locations were identified as
 Noise insignificant area with the exception of point 13 and 16.
- The resultant monitoring and study data will be used as the basis to predict effects from the proposed project.
- The same results documented in this report will be used in the subsequent noise level monitoring technical reports.

5.3.13 Recommendations

Exceedance of any sorts could potentially impact the nearby receptors negatively thus mitigation measures should be put in place and adhered to closely. The proponent is bound to make sure the noise levels are within the stipulated noise regulation limits during the operational life of the proposed project. In case of any exceedance of noise levels, the proponent should adopt noise mitigation measures and regular noise monitoring should be put in place to check the effectives of the noise mitigation measures put in place.

5.4 Local ground water resource

Supplies of ground water in the area are obtained within the unconfined aquifer in the area. Potable water is a scarce resource in the area. Water from the main pipeline by the Malindi Water and Sewerage Company (MAWASCO) are inadequate and are supplemented by groundwater. Despite the fact that groundwater aquifers in this area yield either saline or brackish water, the community relies on the wells to meet their water needs for domestic use. A survey of the area was conducted during this environmental impact assessment study process to document the wells and shallows wells used by the community. The table below gives a list of the wells and shallow wells identified.

Table 13: Some of the wells surveyed

NAME OF WELL	Location (GPS Coordinates)
KIBI 42 Chumani	S03º 28.006' E039° 54.145
Foleni well	S03º 27.662' E039° 55.605
Timboni well	S03º 26.080' E039° 56.601
Kadegeni well	S03° 25.310′ E039° 56.071
Uyombo Girls High School well	S03° 25.240' E039° 57.295
Wireless A well	S03º 26.525' E039° 55.822
Wireless B well	S03º 24.759' E039° 57.594
Matsangoni Police Station borehole	S03º 23.761' E039° 55.591
Gongoni Village Well	S03º 25.862' E039° 55.933
Timboni 2 well	S03º 26.185' E039° 56.588



Plate 6: Identification of boreholes

5.4.1 Groundwater quality

The quality of the wells identified above was benchmarked for purposes of future reference. The bench-marking involved sampling and analyzing the quality of water in the identified wells within the local community. The sampling and analysis was carried out by Polucon Services (Kenya) Limited, an accredited laboratory. Water samples were drawn and analyzed for physical, chemical and microbiological properties. Appendix 9 is the detailed water quality laboratory analysis report for each of the water sample.

5.4.1.1 Water sampling and analysis from KIBI 42 Chumani

Water samples were drawn from the KIBI 42 Chumani well by Polucon Services (Kenya) Limited an accredited laboratory and analyzed. Parameters analysed included pH @ 32.6°C, Conductivity, Total dissolved solids, Chlorides as Cl, Aluminium as Al, Iron as Fe, Sodium as Na, Magnesium as Mg, Calcium as Ca, Phosphates as PO₄³⁻, Sulphates as SO₄, Nitrates as NO³⁻ and Total coliform count. The results of the water sampled collected and analysed from KIBI 42 Chumani show that the water does not conform to the required specifications for natural potable water due to presence of high chlorides and presence of coliforms.

5.4.2.2 Water sampling and analysis for Foleni well

Water samples were drawn from the Foleni well by Polucon Services (Kenya) Limited an accredited laboratory and analyzed. Parameters analysed included pH @ 29.3°C, Conductivity, Total dissolved solids, Chlorides as Cl, Aluminium as Al, Iron as Fe, Sodium as Na, Magnesium as Mg, Calcium as Ca, Phosphates as PO₄³⁻, Sulphates as SO₄, Nitrates as NO³⁻ and Total coliform count. The results of the water sampled collected and analysed from the Foleni show that the water does not conform to the required specifications for natural potable water due to high conductivity, total dissolved solids, chloride ions, sodium ions and presence of coliforms.

5.4.2.3 Water sampling and analysis for Timboni well

Water samples were collected from the Timboni well and analysed. Parameters analysed included pH@28.6°C, Conductivity, Total dissolved solids, Chlorides as Cl, Aluminium as Al, Iron as Fe, Sodium as Na, Magnesium as Mg, Calcium as Ca, Phosphates as PO₄3-, Sulphates as SO₄, Nitrates as NO³⁻ and Total coliform count. The results of the water sampled collected and analysed from the Timboni Well show that the water does not conform to the required specifications for natural potable water due to high conductivity, total dissolved solids, chloride ions, sodium ions and presence of coliforms.

5.4.2.4 Water sampling and analysis for Kadegeni well

Water samples were collected from the Kadegeni Well and analysed. Parameters analysed included pH@30.7°C, Conductivity, Total dissolved solids, Chlorides as Cl, Aluminium as Al, Iron as Fe, Sodium as Na, Magnesium as Mg, Calcium as Ca, Phosphates as PO₄³⁻, Sulphates as SO₄, Nitrates as NO³⁻ and Total coliform count. The results of the water sampled collected and analysed from the Kadegeni Well show that the water does not conform to the required specifications for natural potable water due to high conductivity, total dissolved solids, chloride ions, sodium ions and presence of coliforms.

5.4.2.5 Water sampling and analysis for Uyombo Girls High School well

Water samples were collected from the Uyombo Girls High School well and analysed. Parameters analysed included pH@28.9°C, Conductivity, Total dissolved solids, Chlorides as Cl, Aluminium as Al, Iron as Fe, Sodium as Na, Magnesium as Mg, Calcium as Ca, Phosphates as PO₄³⁻, Sulphates as SO₄, Nitrates as NO³⁻ and Total coliform count. The results of the water sampled collected and analysed from the Uyombo Girls High School well show that the water does not conform to the required specifications for natural potable water due to

high conductivity, total dissolved solids, chloride ions, sodium ions, magnesium ions, calcium ions, sulphate and presence of coliforms.

5.4.2.6 Water sampling and analysis for Wireless A well

Water samples were collected from the Wireless A well and analysed. Parameters analysed included pH@28.6°C, Conductivity, Total dissolved solids, Chlorides as Cl, Aluminium as Al, Iron as Fe, Sodium as Na, Magnesium as Mg, Calcium as Ca, Phosphates as PO₄³⁻, Sulphates as SO₄, Nitrates as NO³⁻ and Total coliform count. The results of the water sampled collected and analysed from the Wireless A well show that the water does not conform to the required specifications for natural potable water due to high conductivity, total dissolved solids, sodium ions, magnesium ions and presence of coliforms.

5.4.2.7 Water sampling and analysis for Wireless B well

Water samples were collected from the Wireless B well and analysed. Parameters analysed included pH@28.8°C, Conductivity, Total dissolved solids, Chlorides as Cl, Aluminium as Al, Iron as Fe, Sodium as Na, Magnesium as Mg, Calcium as Ca, Phosphates as PO₄³⁻, Sulphates as SO₄, Nitrates as NO³⁻ and Total coliform count. The results of the water sampled collected and analysed from the Wireless B well show that the water does not conform to the required specifications for natural potable water due to high conductivity, total dissolved solids, chloride ions, sodium ions, and presence of coliforms.

5.4.2.8 Water sampling and analysis for Matsangoni Police Station borehole

Water samples were collected from the Matsangoni Police Station borehole and analysed. Parameters analysed included pH@28.8°C, Conductivity, Total dissolved solids, Chlorides as Cl, Aluminium as Al, Iron as Fe, Sodium as Na, Magnesium as Mg, Calcium as Ca, Phosphates as PO₄³⁻, Sulphates as SO₄, Nitrates as NO³⁻ and Total coliform count. The results of the water sampled collected and analysed from the Matsangoni Police Station borehole show that the water does not conform to the required specifications for natural potable water due to conductivity, total dissolved solids, chloride ions, sodium ions, magnesium ions, calcium ions and presence of coliforms.

5.4.2.9 Water sampling and analysis for Gongoni Village Well

Water samples were collected from the Gongoni Village Well and analysed. Parameters analysed included pH@29.9°C, Conductivity, Total dissolved solids, Chlorides as Cl, Aluminium as Al, Iron as Fe, Sodium as Na, Magnesium as Mg, Calcium as Ca, Phosphates as PO₄³⁻, Sulphates as SO₄, Nitrates as NO³⁻ and Total coliform count. The results of the water sampled collected and analysed from the Gongoni Village Well show that the water

does not conform to the required specifications for natural potable water due to conductivity, total dissolved ions, chloride ions, sodium ions, magnesium ions and presence of conforms.

5.4.2.10 Water sampling and analysis for Timboni 2 Well

Water samples were collected from the Timboni 2 Well and analysed. Parameters analysed included pH@29.6°C, Conductivity, Total dissolved solids, Chlorides as Cl, Aluminium as Al, Iron as Fe, Sodium as Na, Magnesium as Mg, Calcium as Ca, Phosphates as PO₄³⁻, Sulphates as SO₄, Nitrates as NO³⁻ and Total coliform count. The results of the water sampled collected and analysed from the Timboni 2 Well show that the water does not conform to the required specifications for natural potable water due to conductivity, total dissolved solids, chloride ions, sodium ions, magnesium ions and presence of conforms.

5.5 Climate

Climate is influenced by monsoon winds with the rainfall pattern being characterized into long rains (April-June with an average of 1040mm) and short rains (end of October to December with an average of 240mm). The average annual rainfall for the county is 640mm. The annual mean temperature in the county is 27.9°C with a minimum of 22.7°C and a maximum of 33.1°C. The hottest month is February with a maximum average of 33.1°C while the lowest temperature is in July with a minimum average of 22.7°C. On average, the temperatures are always high in Roka area. Most rainfall (rainy season) is seen in April, May, October and November. On average, the warmest month is March and on average, the coolest month is September. May is the wettest month and February is the driest month.

5.5.1 Temperature

On average, the temperatures in Roka area are always high. The warmest month is March and the coolest month is July. The average annual maximum temperature is: 87.8° Fahrenheit (31.0° Celsius) and the average annual minimum temperature is 69.8° Fahrenheit (21.0° Celsius).




Figure 5: Average minimum and maximum temperatures of Roka area over the year

Source: www.weather-and-climate.com

5.5.2 Sunshine

On average, January, March and October are the sunniest months while May has the lowest amount of sunshine. Figure 2 below is the monthly total of sun hours over the year in Roka area.



Figure 6: Monthly total of sunshine hours over the year in Roka area

Source: www.weather-and-climate.com.

5.5.3 Water Temperature

On average, March has the hottest water temperature while September has the coldest water temperature. Figure 3 below is the mean water temperature in Roka area over the year.




Figure 7: Average mean water temperature in Roka area over the year

Source: www.weather-and-climate.com.

5.5.4 Precipitation

A lot of rain (rainy season) in Roka area, falls in the months of April, May, October and November. On average, May is the wettest month while February is the driest month. The average amount of annual precipitation is: 39.37 in (999.9 mm) as shown in figure 4 below.




Figure 8: Average precipitation in Roka area over the Year

Source: www.weather-and-climate.com.

5.5.5 Monthly Rainy Days

Most rainy days are in the months of April, May, October and November with May having the highest number of rainy days. February has the least number of rainy days. Figure 5 below shows the average monthly rainy days in Roka area over the year.




Figure 9: Average Monthly Rainy Days in Roka area over the year

Source: www.weather-and-climate.com.

5.5.6 Humidity

On average, May is the most humid month in Roka area while February is the least humid. Figure 6 is the mean monthly relative humidity over the year in Roka area.



Figure 10: Mean monthly relative humidity over the year in Roka area

Source: www.weather-and-climate.com.

5.5.7 Wind Speed

On average, the windiest months in Roka area are May and June while the least wind is seen in November. Figure 7 below is the mean monthly wind speed (meters per second).




Figure 11: Mean monthly wind speed over the year in Roka area in meters per second Source: www.weather-and-climate.com.

5.6 Geology

5.6.1 Introduction

The regional geological setting of Kilifi County is dominated by the rifting and break-up of the Palaeozoic Gondwana continent and the development of the Indian Ocean (Embleton and Valencio, 1977). Upper Proterozoic gneisses of the Mozambique belt form the basement of an intra-cratonic basin, filled with continental Permo-Triassic clastics (Pohl and Horkel, 1980). Rifting during the early to middle Jurassic, presumably preceded partly by up-doming along the incipient rift, transformed it into a marine marginal basin at the trailing edge of the African plate (Horkel et.al., 1984). Most of the area is underlain by the continental Permo-Triassic sediments assigned to the Duruma Group (Caswell, 1953), which is generally considered as the Kenyan equivalent of the Karroo system of southern Africa (Horkel et.al., 1984). The Duruma group includes the Taru Formation, Maji ya Chumvi formation, Mariakani Formation and Mazeras Formation (Onyancha and Nyamai, 2014). The Duruma sediments essentially comprise grits, arkosic sandstones, and additives accumulated under lacustrine, sub-aerial conditions (Onyancha and Nyamai, 2014). They also include minor marine ingressions in a broad, roughly NNE-SSW trending intra-cratonic trough, which formed towards the end of the Paleozoic within the Proterozoic gneisses of this part of the Gondwana (Embleton and Valencio, 1977). This fault trend controlled the deposition of all the other formations (Onyancha and Nyamai, 2014) including the Magarini formation and Mtomkuu (Kambe) formation.

After the termination of the Duruma sedimentation, major faulting and rifting led to the breakup of Gondwanaland; it caused a fundamental facies change from a continental cratonic trough to a marginal marine basin with sediments, located at the trailing edge of the continent (Horkel et.al., 1979). This transition is marked by a middle Jurassic marine ingression. The basal sediments of the Mtomkuu (Kambe) formation were deposited under near-shore neritic and estuarine conditions (Onyancha and Nyamai, 2014). Basal transgression conglomerates, largely composed of Duruma detritus, are overlain by impure micritic limestones, occasionally with small bioherms, and near-shore oolithic limestones, which were deposited in a shallow shelf environment with only moderate terrigeneous contamination (Braithwaite, 1984).

Erosion prevailed during the Tertiary until the Upper Pliocene, when tectonic reactivation resulted in increased erosion (Embleton and Valencio, 1977). Fluviatile pebble beds, gravels and sands of the Magarini formation were deposited on down-faulted and eroded Jurassic and Duruma sediments. After a regression during the Late Pleistocene, dunes which form the bulk of the Magarini formation were blown-up. This led to the formation of Pleistocene sands. At the same time, corals accumulated to form the Reef Complex along the Coast. The oldest rocks are the Gneisses of Neo Proterozoic Era while the youngest is the Reef Complex of Recent Age. The location of MCL Vipingo, Roka and Matsangoni sites consists of three geological units namely the Coral Reef Complex, Magarini Formation and Quaternary Sands. The units are readily identifiable and their field relationships clearly indicate the depositional history of the area.

5.6.2 Coral Reef Complex

Most of the MCL Vipingo, Roka and Matasangoni sites is founded on the Coral Reef Complex. In the wider context, the unit covers a long stretch of the Kenyan Coast from Vanga in the south to Lamu in the north. The Coral Reef Complex is considered to be Pleistocene age. Coral limestone, which is dead remains of sea corals, is the main rock type of the reef complex. However, depending on the conditions that prevailed at the time of deposition, within a locality, other sedimentary rocks may be found alongside the limestone. Often such rocks would include shale and marl. Over most of the unit, a thin layer of either wash down sand or brown soil covers the coral limestone. The brown soil (terra rosa), formed from weathering of part of the limestone, supports pockets of vegetation.

5.6.3 Magarini Formation

Part of the MCL Vipingo, Roka and Matsangoni sites especially the south-western and north-western sectors, consists of sandy reddish brown soils. The soils are part of the Magarini Formation that is Pliocene age. Magarini sands comprise of fluviatile pebble beds of gravels and sands deposited in fresh water environment. In the regional context, the Magarini Formation, known to consist of yellowish to brownish sandy soils with layers of clays, occupies a considerable part of the Coastal Belt inland of the Coral Reef Complex. The Magarini Formation resulted from back reef depositional environment.

5.6.4 Quaternary Sands

Thick alluvial sand deposits considered as Quaternary in age cover some parts of MCL Vipingo, Roka and Matsangoni sites. The sands are regarded to be derivatives of the Magarini Formation. Vegetative cover on the alluvial sands is mainly grass, indicating relatively low amount of soil and recent age of the unit. The alluvial sands are very difficult to drive through.

5.7Groundwater

The proposed project site of Roka and Matsangoni has groundwater resources; groundwater in the area occurs in confined and unconfined aquifers in sedimentary formations of fluvial and lacustrine origin. Groundwater flow direction is generally eastward with recharge rate decreasing westward. The geology of the area plays an important role in determining occurrence of the groundwater. Whereas coral limestone is permeable, the Magarini Formation and Quaternary alluvial sands have layers of clay that help trap water. Therefore over the entire Coastal Belt, occurrence of groundwater is characteristic of the dune sands lying behind the coral limestone. Given that Roka and Matsangoni sites are within the Reef Complex which was formed from accumulation of corals along the coast, limestone cavens allow sea-water intrusion inland where there are no faults causing little drawdown in boreholes even with continuous large-scale abstraction.

6. MINING

Mining is the extraction of economically valuable minerals or other geological materials from the earth surface.

6.1 Mining Methods

6.1.1 Surface Mining

Surface Mining is one of the oldest methods of mining. Surface mining is the predominant exploitation procedure worldwide. Most of these are mined by open pit or open cast methods. Ores closer to the surface are accessed by creating an open pit and then excavating the ore below for further processing. In most cases, a significant amount of overburden, which is a layer of rock or soil that covers the deposit, must be removed.

The open pit mining is a mechanical extraction method. Open pit is also called as open cast mining. It is usually employed to exploit a near-surface deposit or ore that has a low stripping ratio. This method often requires a large capital investment but generally results in high productivity, low operating cost and good safety conditions.

6.1.2 Underground Mining

Ores in buried bedrock deposits are usually accessed through the construction of access shafts and tunnels.

This method provides for less waste rock removal and offers less environmental impact than open-pit mining.

6.1.3 In-Situ Leach (ISL) Mining

Some ore bodies, due to ore concentration or the surrounding material, can only be accessed by dissolving the ore body using water soluble acids or alkalis and then pumping out the solution. The ore body is then recovered as a precipitate. This method is common when extracting minerals near aquifers. It is also used if ores are not locally concentrated but spread over a wide area.

6.1.4 Solution and Placer mining

Solution mining includes both borehole mining, such as the methods used to extract sodium chloride or sulphur, and leaching, either through drill holes or in dumps or heaps on the surface.

Placer mining is used to exploit loosely consolidated deposits like common sand and gravel or gravels containing gold, tin, diamonds, platinum, titanium, or coal.

Placer and solution mining are among the most economical of all mining methods but can only be applied to limited categories of mineral deposits.

The aqueous extraction methods depend on water or another liquid (e.g., dilute sulphuric acid, weak cyanide solution, or ammonium carbonate) to extract the mineral.

6.2 Mining of Stones/Quarrying

6.2.2 Introduction

Stones occur in the form of natural rock masses or layers on the surface. The process of mining/extraction of suitable stones from their natural rock beds or layers is commonly called Quarrying of Stones.

It differs from the mining of ores of metals in that whereas quarrying is an operation carried out entirely on the surface, mining involves digging below the ground, sometimes at considerable depth.

Mining of stone is basically by surface mining method.

6.2.3 Excavation Methods in Quarrying

Excavations can be made with any means. Economics and time determine what method is most viable.

Excavation can be either:-

- Without blasting, or
- By blasting

The table below summarizes the excavation methods

Table 14: Excavation methods in quarrying

E	xcavation Method	Technology/Tools Required		
Excavation	Small-scale hand excavation		 Hammer and chisel 	
without blasting			Fire setting	
	Mechanical	Digging and	Man-made shovel/excavator	
		ripping	Ripper	
		Cutting and	Road Header	
		grinding	Trench Cutter	
		Hammering	Jack Hammer	
			Hydraulic/Pneumatic Hammer	
Excavation by Blasting			Drill and Blast	

6.2.3.1 Quarrying of Stones without Blasting

In these methods, blocks of rocks are broken loose from their natural outcrops by men using hand tools or special purpose mechanical machines.

No explosive material is used at any stage in this method of quarrying of stones. Soft rocks and also those rocks which have layered structure are easily quarried by these methods.

6.2.3.2 Quarrying of Stones by Blasting

This method consists of using explosives for breaking stones from very hard rocks. The basic principle of this method is to explode a small quantity of an explosive material at a calculated depth within the rocks. The force generated due to this explosion is sufficient only to create cracks and loosen blocks of good size Quarrying by blasting, therefore, requires very experienced persons thoroughly acquainted with blasting explosives on the one hand and strength qualities of rocks on the other hand. Quarrying by blasting involves a series of systematic operations such as drilling of blast-holes, charging of blast-holes and firing the shots.

6.2.3.3 Quarrying without blasting verses quarrying by blasting

The main environmental impacts associated with quarrying are dust, noise and vibrations. These impacts are usually aggravated with blasting. Blasting operations cause several adverse environmental effects, including ground vibrations, air-blast, fly-rock and generation of dust to a much higher extent. Stone quarries are long-term projects with a life of their own in which deposits are usually mined over several decades. These quarries are part of the landscape, and during operations residential developments often expand up to the edges of the quarry site. The use of explosives to mine the rock then becomes a source of annoyance to residents, and a safety issue. Overtime, changes in the law, environmental requirements and/or safety considerations have made the use of explosives difficult. Quarry owners should always review the breaking method when they want to avoid possible operation restrictions, simplify the renewal of mining permits, maintain profitability or increase the demand on product quality.

7. PROJECT DESIGN AND DESCRIPTION

7.1 Background to limestone

Limestone is composed essentially of calcium carbonate, varying percentages of magnesium carbonate and mechanically admixed impurities of sand and clay. Depending on the type and source of limestone, a range of accessory minerals may be present, including iron and magnesium oxides, sulfides of common metals, authigenic feldspars, gypsum, quartz, clay minerals, mica and bituminous matter. However, quality of the limestone can be ascertained from its chemical composition, which is commonly analysed as percentages of calcium oxide (CaO), magnesium oxide (MgO), iron oxide (Fe₂O₃), Alumina (Al₂O₃), silica (SiO₂) and LOI (Loss on Ignition). Some chemical analyses include percentage of potash (P₂O₅), TC (Total Carbonate) and magnesium carbonate (MgCO₃). Limestone at the proposed project site is to mined and later transported out of the site to Vipingo cement factory.

7.2 Proposed project components

The components of the proposed quarry will include:

- ✓ Quarry access roads
- ✓ Site camp
- ✓ Sanitary facilities
- ✓ Weighbridge
- ✓ Overburden stockpile
- ✓ Holding area of recovered coral limestone
- ✓ Operational quarry pits
- ✓ Disused quarry pits

7.2.1 Quarry access roads

All quarry access roads will be graded and graveled from time to time to ensure they are able to sustain heavy weights of loaded trucks evacuating mined coral limestone from the quarry. The quarry access roads will connect from the nearest existing graveled road to where the quarry pits will be opened up.

7.2.2 Site camp

The site camp will consist of essential facilities necessary for day-to-day smooth operation of the quarry. These will include a site office, temporary garage for minor repairs of quarry equipment, oil/water separator, site workshop, water tanks for sanitation and dust suppression, waste handling facilities and security guard station.

7.2.3 Sanitary facilities

Sanitary facilities will be those that will be used at the quarry pit areas where actual limestone mining is being done and those within in the quarry camp. Sanitary facilities will include toilets, urinals, showers and hand washing stations. The sanitary facilities will have reliable and adequate water connection to ensure requires hygiene standards are achieved and maintained.

7.2.4 Weighbridge

A weighbridge will be appropriately sighted close to the quarry camp along the access road within a parcel of land owned by the proponent. The weighbridge will be used to monitor the quantity of mined limestone ferried out of the quarry.

7.2.5 Overburden stockpile

An area will be set aside where all the stripped overburden material will be stockpiled and held through the mining period. It will be important to stockpile all the overburden material recovered because it contains important plant and animal genetic material that will be necessary for successful site rehabilitation. The stored overburden will therefore be used later during site rehabilitations.

7.2.6 Holding area of recovered coral limestone

Recovered limestone will be held temporary at a designated holding area before haulage out of the quarry. The holding will enable quarry, recovery of limestone and stockpiling to be a head of the pace of haulage of the quarried limestone out of the quarry. This will reduce and or eliminate dump truck idling time waiting material to be recovered for transportation.

7.2.7 Operational quarry pits

Quarry pits will be open systematically to match the rate of recovered limestone haulage from the quarry pit to either the holding area or direct to Vipingo. Continuous excavation of the limestone will overtime create a quarry pit. The changing boundary of the quarry pits will be clearly marked with red flags to warn all persons of existing of the quarry pit in the area ns to keep off. Further as mining progresses measures will be put in place to avoid ponding/pooling of water in the pit when it rains. This will include drain out any water collected in the quarry pit. All active quarry pits will in addition be physically manned to ensure no unauthorized access to the site by local community members including livestock. This will be critical to ensure no accidents occur.

7.2.8 Disused quarry pits

Quarry pits where mining and recovery of limestone is complete will be adequately secured and manned to ensure no persons or livestock access them. This is vital to ensure to cases of incidences of dropping in the quarry or accidents occur as such open pits are a safety hazard. Rehabilitation of all disused quarry pits will begin once it has been ascertained that no further limestone recovery will be done from such pits in the future. The rehabilitation will be done in such a way that the resulting rehabilitated land will be economically usable.

7.3 Mining method

Winning of the limestone will be by quarrying also referred to as open cast mining. No explosives will be used at any time. Any identified hard bedrock; a dozer will first be used to break the bed rock.

7.4 Opening of quarry pits

Opening of a quarry pit will entail identification of the most suitable site for setting up of new quarry pit within the MCL limestone deposits; clearing, cleaning and stripping of overburden on the identified site to adequately expose coral limestone in readiness for mining. Overburden material will be scrapped and moved to other locations using a bulldozer, and sometimes using a shovel and/or dump truck if necessary.

7.5 Extraction of limestone and additives

The operations at the quarry pits will include stripping of the overburden to expose the required limestone to be mined. The mining of the limestone will involve stripping of the limestone using a bucket excavator. Where the limestone bedrock is hard that it cannot be mined using the bucket excavator, then a dozer will be used to break the hard limestone first before employing the bucket excavator. The entire mining will require committing adequate mining equipment including excavators, dozers, wheel loaders and shovel. Once the limestone has been mined, the materials are transported out of the quarry to MCL cement plant at Vipingo using a fleet of dump trucks.

8. ANALYSIS OF PROJECT ALTERNATIVES

A Project Alternative (project option) is another combination of the project's costs, schedules, resources, and risks that allow achieving the same results as compared to the project base-line. It is one or more ways to produce the project and address its need while using the same resource base yet operating in a new way and facing new working conditions. Project alternative considered for the proposed coral limestone mining project include the yes project alternative, the no project alternative, alternative use of proposed project site, alternative project site and alternative mining methods. An analysis of each of the project alternatives to the project costs, schedules, resources, and risks is tabulate in table 13. Evaluation of each of the project options is as follows.

8.1 The No Project Alternative

The no project alternative means that the project as currently proposed i.e. mining of coral limestone using the open cast mining method at the proposed project site to be totally rejected. This means that the proposed project site to remain as currently is. The no project alternative implies that the developer MCL having procured the proposed project site transferred the title to company name and processed change of user to new user to allow for the proposed project will not be able to achieve the proposed plans to develop the company land and recover limestone from the proposed project site.

8.2 The Yes Project Alternative

The yes project alternative means that, the proposed project of mining coral limestone from the proposed project site to be implemented as currently proposed. The yes project alternative will enable the project proponent achieve the proposal of mining and recovering limestone from the proposed project site.

8.3 Alternative use of proposed project site

The proposed project site consists of a number of plots that were procured from local people. The previous owners of these plots used the plots in extraction of coral limestone building blocks, grazing of livestock and in arable crop farming including coconut farming among other crops such as cassava. Alternative use of the proposed project site could be farming, machine cutting of building blocks, livestock grazing among others.

Table 15: Tabulation of an of each of the project alternatives to the project costs, schedules, resources, and risks

Project alternative	Yes project	No project alternative	Alternative project site	Alternative design/ mining
	alternative			method
Project aspect				
Cost	No change on	Loss of the project as it will	Will change the project cost as	Redesigning the project and
	current projected	not be implemented	an alternative site has to be	or changing the mining
	project cost		procured	method will be an added cost
Schedules	No change on	Proposed project schedule	Will change the schedule to take	New schedules will have to be
	current project	will not be used as the	care of time lost in obtaining	developed to take care of the
	schedule	project will not be	alternative site	requirements of the new
		implemented		design and mining method
Resources	No change on	Available project resources	More resources	Resources needed will change
	current planned	will not be used as the	(time, expertise, finances) will	depending on the new design
	project resources	project will not be	be required	and or mining method
		implemented		
Risks	Risk of not	All risks associated with	Risk of not implementing the	Risk of not getting a design
	implementing the	implementation of the	project on schedule or failing to	that can be implemented
	project is minimal	project will not be realized	implement it all together is	within the project budget and
		as the project will not be	feasible	location
		implemented		

8.4 Alternative project site

The proposed project aims to mine and recover limestone from the proposed project site. An alternative project site should have adequate coral limestone deposits of required quality. Within the South Coast there are other places with parcels of land which limestone that can be mined. Likewise in the South Coast area of Likoni area stretching all the way to Lunga Lunga there are limestone deposits that can be mined. So both at the South and North Coast there areas that can be alternative project sites for mining of coral limestone.

8.5 Alternative mining methods

The proposed project will by surface mining which employs the open cast mining method without blasting to recover coral limestone from the site. The open cast mining method is used to exploit a near-surface deposit that has a low stripping ratio. Limestone in the area being on the surface, open cast mining method will be the best mining methods that can be used for the proposed project site. Other available mining methods such as underground mining, in-situ leach mining and solution mining are not relevant to exploitation of minerals occurring at the surface or near-surface. Therefore there is no alternative mining method to the proposed one.

9. OCCUPATIONAL SAFETY AND HEALTH

9.1 Introduction

Occupational Health and Safety (OHS) is of importance at project sites. It is important for mechanisms to be put in place to predict potential risks, incidents and hazards in the said working environment. This is because the occupational environment directly affects employees involved in a project, the neighborhood, visitors, contractors, sub-contractors and the general public. Therefore before commissioning of the project, a number of safety measures have to be in place to ensure the safety of employees, neighbors and the general public. Employees and visitors to the project site may be exposed to a variety of personal health and safety risks. The type and level of exposure is generally related to factors controlled by the employer/ developer. Such factors include design, equipment, tools, work procedures, project, and employee training. Occupational health and safety risks that should be considered by the employer arise from normal functions and operations and during unusual circumstances such as accidents and incidents. The project proponent is responsible for:

- Implementation of appropriate national and internal recognised OHS standards, practices and guidelines.
- Inclusion of meaningful participation of employees in implementation and maintenance of procedures and processes.
- Implementation of a programme to change employee culture and altitudes regarding health and safety.
- Planning, implementing and monitoring programs and s required to ensure OHS at the workplace.
- Provide and maintain workplaces, equipment, tools and machinery and organise work so as to eliminate or control hazardous ambient work factors.
- Provide appropriate occupational health and safety training for all employees.
- Provide adequate personal protective equipment to all employees at no cost to employees.
- Record and report occupational injuries and illness.
- Ensure contract specifications include demands for service providers, contractors, and sub-contractors to have or establish enabling them to meet the OHS requirements of the employer.

9.2. Occupational Health and Safety Management

An Occupational Health and Safety Management system (OHSMS) will be established, managed and operated for the proposed project. The system will contain the following features:

- 1. Occupational Health and Safety Policy for the company
- 2. Organizational framework of the OHSMS
 - ✓ Staffing of OHSMS
 - ✓ Competence requirements
 - ✓ Operating procedures
 - ✓ Training programs
 - ✓ Documentation
 - ✓ Communication
- 3. OHSMS objective (documentation)
- 4. Hazard prevention
 - ✓ Risk assessment
 - ✓ Prevention and control measures
 - ✓ Management of changes
 - ✓ Emergency preparedness and response
 - ✓ Procurement (tools, equipment, services, contractors)
- 5. Performance monitoring and measurements
 - ✓ Hazard prevention measures
 - ✓ Ambient working environment
 - ✓ Work related injuries, ill health, disease and injuries
- 6. Evaluation
 - ✓ Feedback
 - ✓ Corrective measures
 - ✓ Action plan

9.3. Employee safety

In addressing requirements and needs to ensure employee safety, the following will be in place: -

- Pre- employment medical examination
- ➤ Annual medical examination against baseline pre-employment medical examination records

- > Provision of adequate personal protective equipment.
- > Enforcement and proper use of personal protective equipment by all employees.
- Provision of first aid and emergency services on site.
- ➤ In case of injury of employee during work; management must have a clear policy on treatment of the injured employee.
- ➤ In case of permanent disability arising from injury at work place, adequate compensation should be available within the law.
- Appropriate tools and equipment in sound working condition must be provided to employees to enable them work safely.
- ➤ All practical measures must be in place to ensure that the work place is free of dust and excessive noise.

9.4. Safety of neighbours and general public

Project sites are associated with incidents and accidents that endanger workers, neighbors and general public. The proponent must ensure the safety of all neighbours and the general public is taken care of by putting the following measures in place: -

- ✓ All neighbours to be informed of the date of commencement of project.
- ✓ Heavy vehicles and trucks that will be ferrying in project equipment to the project site
 to observe required minimum speed limit when approaching the site to avoid
 accidents.
- ✓ There should be notices and warning prominently displayed at entry of project site and strategically around the project boundaries informing general public of on-going activity and safety requirements.

9.5 Machine use and Electrical Safety

During the implementation of the proposed project, it is expected that different machines, tools and equipment will be used. Most of this machine will be powered internally by use of diesel. In regard to electrical safety, the following will have to be undertaken: -

- Installation and fitting of proper electrical appliances to enable supply of electrical energy to utility point.
- All electrical installations and fittings are done according to electrical safety rules.
- All electrical wires must be safely insulated.
- Sockets and other electrical outlets must be securely fitted.
- When not in use all machines should be shut down.

- Qualified and well-experienced electrician should be hired to carry out all electrical work.
- Safety slogans should be strategically posted as a reminder to employees.
- Operating manuals of equipment should be available for use whenever needed.

9.6. Internal Safety

During the entire project implementation and operation cycle, safety of the employees on the site should be taken care of. Some of the things that need to be in place include:-

- ✓ Emergency preparedness
- ✓ First aid
- ✓ Welfare facilities
- ✓ Personal protective equipment

9.7. First-Aid

- i. Proponent to ensure qualified First Aiders are available to administer first aid to affected employees at all times.
- ii. An appropriately equipped First-Aid station to be easily accessible at the project site.
- iii. The First Aid station to be adequately equipped to meet first aid needs at the project site.
- iv. A written Emergency Procedure to be in place.

9.8. Welfare facilities

- i. Changing rooms for workers to be provided.
- ii. Shower rooms and washing facilities to be provided.
- iii. Proponent to avail potable drinking water to all employees at site.
- iv. Appropriate and adequate Personal Protective Equipment to be provided
- v. The enforcement on the consistence of the correct use of PPE provided
- vi. The PPE provided are to maintain clean and replaced when damaged or worn out.

9.9. Ambient factors in the project site

9.9.1 Noise

Management will put in place a comprehensive noise conservation programme which will include the following:-

- i) Training of workers in noise prevention, control and management.
- ii) Provision of appropriate noise protective devices to workers.

- iii) Training of the workers on the importance of making appropriate use of the protective devices provided.
- iv) Monitoring of noise levels through periodic noise survey.
- v) Use of appropriate noise attenuators.
- vi) Audiometric test of workers

9.9.2 Dust

- ✓ Exposure to dust to be controlled by ensuring dust accumulation at project site is mitigated.
- ✓ Equipment to be selected, especially that with in-built dust extraction.
- ✓ Employee exposed to dust to be provide with disposable dust masks.
- ✓ Regular sprinkling of water on dusty roads and other dusty working areas.

10. STAKEHOLDER CONSULTATION AND PUBLIC PARTICIPATION

Consultation with stakeholders that are likely to be affected and those that are likely to have an interest in the proposed limestone quarry project was conducted as provided for in Regulation 17 of the Environmental (Impact Assessment and Audit) Regulations, 2003. The consultation was vital and served to:-

- Inform local community especially those drawn from the proposed project site of the proposed development within their locality.
- Explain to the local community the nature of the proposed project, its objectives and scope.
- Give local community especially those drawn from the proposed project site an opportunity to present their views, concerns and issues regarding the proposed.
- Obtain feedback and suggestions from the local community and other stakeholders on the proposed limestone quarry project on possible ways potential negative impacts can be effectively mitigated and how the stakeholders can be involved in the project cycle to ensure their interests are addressed.

10.1Steps taken to consult with stakeholders

Due to the prevailing Covid-19 challenges and restrictions on gatherings, stakeholder consultation and public participation activities involved the following;

- Key Informants Interviews
- Focused Group Discussions
- Questionnaire survey

10.2 Key Informants Interviews

Key informants interviews were undertaken with various Government Officers and representatives of government institutions and/or Lead Agencies.

County Commissioner Kilifi County:- On the 8th October 2020, the Environmental Impact Assessment Study team held a meeting with the County Commissioner Kilifi County and briefed the County Commissioner on the proposed project and the requirement for stakeholder consultation and participation. On his part, the County Commissioner Mr. Kutswa Olaka urged the experts involved in the Environmental Impact Assessment Study to ensure that they undertake an assessment that is above board. He reiterated that any consultation with members of the public should be in strict conformity with the Ministry of Health guidelines on Covid-19 regarding restrictions in gatherings.





Plate 7: The EIA Team meeting the County Commissioner Kilifi County

Deputy County Commissioner Kilifi County:- On the 8th October 2020, the Environmental Impact Assessment Study team held a meeting with the Deputy County Commissioner Kilifi County and briefed the Deputy County Commissioner on the proposed project and the requirement for stakeholder consultation and participation. On his part, the Deputy County Commissioner Mr. Josphat S. Mutisya urged the experts involved in the Environmental Impact Assessment Study to ensure they do good work. He said that findings of the assessment should be made available to all stakeholders including his office.





Plate 8: The EIA Team meeting the Deputy County Commissioner Kilifi County

Member of County Assembly-Matsangoni Ward and Chairperson Water, Environment and Natural Resources Committee:- On the 8th October 2020, the Environmental Impact Assessment Study team held a meeting with the Member of County Assembly-Matsangoni Ward and Chairperson Water, Environment and Natural Resources Committee and briefed him on the proposed project and the requirement for stakeholder consultation and participation. On his part, the MCA Matsangoni Ward Hon. Hassan Mohamed urged the

experts involved in the Environmental Impact Assessment Study to ensure that all stakeholders are involved in the environmental impact assessment process.

County Director of Environment -Kilifi County:- On the 8th October 2020, the Environmental Impact Assessment Study team held a meeting with the County Director of Environment Kilifi County and briefed him on the proposed project. On his part, the County Director Mr. George Oyoo urged the experts involved in the Environmental Impact Assessment Study to ensure they do good work as per the EMCA 1999 (Amended) 2015.





Plate 9: The EIA Team meeting the County Director of Environment Kilifi County

Senior Chief-Roka Location:- On the 6th October 2020, the Environmental Impact Assessment Study team held a meeting with the Senior Chief Roka Location and briefed him on the proposed project and the requirement for stakeholder consultation and participation. On his part, the Senor Chief Mr. Julius Pole Ziro urged the experts involved in the Environmental Impact Assessment Study to ensure all stakeholders are consulted and their views taken on board. He said his office was ready and willing to help in organizing stakeholder consultations through the offices of the two Assistant Chiefs within the Location and through the Village Elders and *Wazee wa Nyumba Kumi*.





Plate 10: The EIA Team meeting the Senior Chief Roka Location

Senior Chief-Matsangoni Location:- On the 7th October 2020, the Environmental Impact Assessment Study team held a meeting with the Senior Chief Matsangoni Location and briefed him on the proposed project and the requirement for stakeholder consultation and participation. On his part, the Senor Chief Mr. Festus Yaa urged the experts involved in the Environmental Impact Assessment Study to ensure all stakeholders are consulted and their views taken on board. He said his office was ready and willing to help in organizing stakeholder consultations through the offices of the three Assistant Chiefs within the Location and through the Village Elders and *Wazee wa Nyumba Kumi*.





Plate 11: The EIA Team meeting the Senior Chief Matsangoni Location

10.3 Focused Group Discussions

Focused group discussions were held with various organized groups within the proposed project catchment area. Focused group discussions were organized as follows:-

- Focused Group Discussions with Learning Institutions' Boards of Management
- Focused Group Discussions with Religious Leaders
- Focused Group Discussions with Village Elders
- Focused Group Discussions with Wazee wa Nyumba Kumi

10.3.1 Focused Group Discussions with Learning Institutions

Focused group discussions were held with the following learning instructions' Boards of Management within Roka and Matsangoni Locations:-

- Chumani Secondary School Board of Management
- Roka Secondary School Board of Management
- Katana Ngala Secondary School Board of Management
- Uyombo Girls Secondary School Board of Management

- Roka Primary School Board of Mnagement
- Kararacha Primary School Board of Management

10.3.1.1 Focused Group Discussion with Chumani Secondary School Board of Management

Chumani Secondary School Board of Management raised the following issues and/or suggestions.

- The need to have haulage roads to be used by the heavy trucks ferrying the quarried limestone maintained
- The need to have excavated land rehabilitated after mining
- That the local community members should be given first priority on any employment opportunities that may arise as a result of the proposed project.
- That the proponent should have proper checks and balances to ensure that no minors and/or school going children are employed at the proposed project.
- That to handle the social impacts of the project such as STIs, the proponent should help equip the local dispensaries.
- Impacts on dust and noise to be adequately handled.





Plate 12: Focused group discussions with the Chumani Secondary School BOM

Appendix 10 is Minutes of the Focused Group Discussion with the Chumani Secondary School Board of Management.

10.3.1.2 Focused Group Discussion with Roka Secondary School Board of Management

Roka Secondary School Board of Management raised the following issues and/or suggestions.

Dust impacts be adequately mitigated

- That noise from the project activities may affect the tranquility of the neighbourhood including the learning environment for students.
- That quarry pits should be rehabilitated after excavation.
- Heavy trucks that would be ferrying the limestone would lead to road deterioration.
- What are the checks and balances to ensure that the proponent would adhere to the Environmental and Social Management Plan?
- That the proposed project could potentially impact on the marine environment especially if it involves blasting.
- The proponent to escalate their CSR activities within the area.
- The proposed project could potentially impact on the acquifer especially knowing that most of the people in the area depend on ground water.
- That the occupational health and safety of employees should be a top priority.





Plate 13: Focused group discussions with the Roka Secondary School BOM

Appendix 11 is Minutes of the Focused Group Discussion with the Roka Secondary School Board of Management.

10.3.1.3 Focused Group Discussion with Katana Ngala Secondary School Board of Management

Katana Ngala Secondary School Board of Management raised the following issues and/or suggestions.

- Dust impacts should be adequately mitigated
- Noise impacts should be adequately mitigated
- Very deep excavations should be avoided
- Quarry pits to be rehabilitated after excavation
- That the occupational health and safety of employees should be a top priority

- That haulage roads should be adequately maintained
- Cleared vegetation should be compensated for
- The proponent to escalate their CSR activities within the area.





Plate 14: Focused group discussion with the Katana Ngala Secondary School BOM

Appendix 12 is Minutes of the Focused Group Discussion with the Katana Ngala Secondary School Board of Management.

10.3.1.4 Focused Group Discussion with Uyombo Girls Secondary School Board of Management

Uyombo Girls Secondary School Board of Management raised the following issues and/or suggestions.

- How will dust impacts be handled? The BOM emphasized that dust impacts be mitigated properly so that any health complications especially to the students are avoided.
- Quarry pits should be rehabilitated after excavation
- Loss of vegetation should be mitigated
- That impacts on dust, noise and vibrations should be mitigated well.
- That the proponent should put in measures to protect the school from the glare and general disturbance of the activities that would be going on at the quarries.
- That a wide-enough buffer zone of trees should be established between the school and the quarry area.



Plate 15: Focused group discussion with Uyombo Girls Secondary School BOM

Appendix 13 is Minutes of the Focused Group Discussion with the Uyombo Girls Secondary School Board of Management.

10.3.1.5 Focused Group Discussion with Roka Primary School Board of Management

Roka Primary School Board of Management raised the following issues and/or suggestions.

- The proposed project is welcome to the area, only that appropriate mitigation measures put in place.
- Priority should be given to the local community in terms of employment
- Dust impacts to the neighbourhood to be adequately handled.
- Quarry pits should be rehabilitated.
- Health and safety of workers be taken care of.





Plate 16: Focused group discussion with Roka Primary School BOM

Appendix 14 is Minutes of the Focused Group Discussion with the Roka Primary School Board of Management

10.3.1.6 Focused Group Discussion with Kararacha Primary School Board of Management

Kararacha Primary School Board of Management raised the following issues and/or suggestions.

- The project should go on with appropriate mitigation measures put in place
- Heavy trucks that would be ferrying the limestone may lead to road deterioration.
- Members of the community should be given priority for employment opportunities.
- What are the checks and balances to ensure that the proponent would adhere to the Environmental and Social Management Plan?
- The proponent to escalate their CSR activities within the area.





Plate 17: Focused group discussion with the Kararacha Primary School BOM

Appendix 15 is Minutes of the Focused Group Discussion with the Kararacha Primary School Board of Management

10.3.2 Focused Group Discussions with Religious Institutions

On the 9th October 2020, the Environmental Impact Assessment Study team held a discussion with a group of religious leaders drawn from the Roka and Matsangoni Locations and briefed them on the proposed project and the requirement for stakeholder consultation and participation. On their part, the religious leaders raised the following issues.

- The need to have excavated land rehabilitated after mining
- That the local community members should be given first priority on any employment opportunities that may arise as a result of the proposed project.
- Impacts on dust and noise to be adequately handled.
- Dust impacts be adequately mitigated

- The proponent to escalate their CSR activities within the area.
- Cleared vegetation should be compensated for
- Health and safety of workers and the general public should be taken care of.





Plate 18: Focused group discussion with religious leaders

Appendix 16 is Attendance List of the Focused Group Discussion with the Religious Leaders

10.3.3 Focused Group Discussions with Village Elders

Focused group discussions were held with a section of village elders drawn from Roka and Matsangoni Locations.

10.3.3.1 Focused Group Discussion with Roka and Chumani Sub-Locations' Village Elders

The Village Elders drawn from the Roka and Chumani Sub-Locations raised the following issues and/or suggestions.

- The village elders said potential impacts on fugitive dust should be handled well so as not to adversely affect people living in the area.
- The said that the local community should be given first priority when it comes to job opportunities at the proposed project
- The village elders expressed concern that the haulage of limestone by heavy trucks would render the local roads unusable.
- They said that the there is no doubt that the proposed project will be beneficial to the local community, however they said that, dust impacts should be handled prudently.
- They said that vegetation cleared should be compensated for.





Plate 19: Focused group discussion with the Roka and Matsangoni Sub-Locations Village Elders

Appendix 17 is Minutes of the Focused Group Discussion with the Roka and Chumani Sub-Locations Village Elders

10.3.3.2 Focused Group Discussion with Matsangoni and Uyombo Sub-Locations' Village Elders

The Village Elders drawn from the Matsangoni and Uyomboi Sub-Locations raised the following issues and/or suggestions.

- The village elders expressed concern that the haulage of limestone by heavy trucks would render the local roads unusable.
- They said quarry pits should be rehabilitated after excavation.
- They wanted to know the expertise required for the work at the proposed project so the local community can prepare adequately.
- They expressed concern that crop farms bordering the quarries would be rendered less productive.
- They also said that the locals should be given priority for employment opportunities.





Plate 20: Focused group discussion with the Matsangoni and Uyombo Sub-Locations' Village Elders

Appendix 18 is Minutes of the Focused Group Discussion with the Matsangoni and Uyombo Sub-Locations Village Elders

10.3.3.3 Focused Group Discussion with Mkongani Sub-Locations Village Elders

The Village Elders drawn from Mkongani Sub-Location raised the following issues and/or suggestions.

- The village elders wanted to know how dust impacts will be handled.
- They said that the locals should be given priority for employment opportunities.
- They said quarry pits should be rehabilitated after excavation.





Plate 21: Focused group discussion with Mkongani Sub-Locationa Village Elders

Appendix 19 is Minutes of the Focused Group Discussion with the Mkongani Sub-Location Village Elders

10.3.4 Focused Group Discussions with Wazee wa Nyumba Kumi

Focused group discussions were held with a section of the *Wazee wa Nyumba Kumi* and they raised the following issues and/or suggestions.

- That dust impacts should be adequately mitigated
- That quarry pits should be rehabilitated after excavation
- They expressed concern that heavy truck to be involved in the proposed project would damage local roads.





Plate 22: Focused group discussion with Wazee wa Nyumba Kumi

Appendix 20 is Minutes of the Focused Group Discussion with a section of the *Wazee wa Nyumba Kumi*.

10.4Questionnaire survey

A questionnaire survey was carried out targeting as many stakeholders of the proposed project as possible. These included the local administrative leaders, the political leaders, learning institutions in the area, religious leaders in the area, business community and the community members. The following are the respondents to the questionnaire and the key issues/concerns raised.

10.4.1 Questionnaire Survey Responses from Local Administration

The following leaders in the Local administration responded to the questionnaire.

- Julius Pole Ziro-Snr Chief Roka Location
- John Amuma Munga-Snr. Asst. Chief Matsangoni Sub. Location
- William Karabu Kombe-Asst. Chief Uyombo Sub. Location
- Albert Kazungu Menza-Asst. Chief Mkongani Sub. Location
- Kombe Vincent J. Katana-Mtsangoni Town Village Elder
- Lawrence Garama Mwamure-Uyombo Centre (B) Village Elder
- James Charo Konde-Kadaina Island Village Elder

The following is a summary of the responses by the local administration leaders:-

- The proposed project will create job opportunities for the residents that will thus enhance their socio-economic lives and the general development of the area.
- The company being an investor will help in driving the development agenda of the area.
- The proposed project will lead to increased population in the hood and thus enhancement of business activities in the area.

- Mass production of dust and smoke from machines are likely to pollute the environment which may cause health complications among residents and low plant production.
- The mining processes may have adverse impacts on the road network of the area.
- Dust mitigation mechanisms should be inculcated in the project.
- Construction, repair and or maintenance of the roads in the area and if possible tarmac the access road to the limestone mining sites.
- Abandoned quarries should be turned into fish ponds.
- Rehabilitate (abandoned) quarries once the mining processes are completed to restore/improve the aesthetic value of the area.
- Develop tree planting and or soil reclamation programs that will also incorporate the organized community groups.
- Undertake Corporate-social-responsibility like the construction of health facilities around the project sites and support of existing institutions as a way of ploughing back to the host community.
- The purchasing power of the residents shall be improved due to the economic empowerment of the community.
- Residents of the area should be given priority in terms of employment and any other arising opportunities from the company.
- Residents to be accorded assistance in terms of education, health and incase of calamities.
- Institutions within the area should be included in the company's welfare fund.

Detailed responses from each of the respondents in this category are in appendix 21.

10.4.2 Questionnaire survey responses from Political Leaders

The following political leaders responded to the questionnaire.

 Mr. Hassan Mohamed; Member of County Assembly-Matsangoni Ward and Chairperson Water, Environment and Natural Resources Committee.

The following is a summary of the responses:-

- The proposed project will create job opportunities for the residents that will thus enhance their socio-economic lives and the general development of the area.
- Infrastructural development as a result of the project will lead to the growth of the area.
- The proposed project will lead to increased population in the hood and thus enhancement of business activities in the area.
- Increased debris and wastes in the hood.
- Water, noise and air pollution due to the mining processes will affect the locals and the living organisms.

- Proper waste management at the site to avoid any form of pollution in our environment.
- Minimize on the usage of heavy machinery at the site to reduce on the impact of earth tremours.
- The proposed mining project will open up the area in terms of development and for many youths who could not manage to complete school may get a form of employment to earn income and improve their living standards unlike the current devastating state.

Detailed responses from each of the MCA are in appendix 22.

10.4.3 Questionnaire survey responses from local learning institutions

The following learning institutions responded to the questionnaire

- Roka Secondary School
- Chumani Secondary School
- Katana Ngala Secondary School
- Uyombo Girls Secondary School
- Roka Primary School
- Uyombo Maweni Primary School
- Roka Maweni Primary School
- Chumani Primary School
- Ufuoni Primary School
- Kararacha Primary School

The following is a summary of the responses from the local learning institutions:-

- The proposed project will create job opportunities for the residents that will thus enhance their socio-economic lives and the general development of the area.
- The community will be able to source building materials locally from the mines.
- Land value is likely to rise in the area due to demand and thus better income for the land sellers though it may also increase landlessness due to thirst for ease money.
- Noise from machinery and dust will have a damaging impact on the learners of the area.
- Limestone mining will lead to depletion of top soils causing land degradation as well as creation of open pits that may be breeding grounds of vectors like mosquitoes.
- Exposure of the land due to the mining processes will actuate soil erosion in the area.
- Clearance of vegetation to pave way for the proposed project will affect the quality of air and the hydrological cycle that may trigger climate change.
- The mining processes will have adverse impacts on the road network of the area.
- The project will destroy the bio-diversity of the area.

- Increased school dropout which may emanate from early pregnancies, created employment opportunities, early marriages and land displacement/migration of families may be witnessed.
- The mining processes will lead to destruction of water catchment areas that are a heritage to the community besides diminishing the water quantity and quality of the area.
- Loss of communal grazing lands will lead to low animal production.
- The current serene and tranquil state shall cease once mining processes begin due to noise pollution.
- Quarrying activities should not be undertaken near schools and other institutions where the company has acquired land.
- Buffer the community/institutions from the company's activities likely to cause negative impacts in the area.
- Construction, repair and or maintenance of the roads in the area and if possible tarmac the access road to the limestone mining sites.
- Rehabilitate (abandoned) quarries once the mining processes is completed to restore/improve the aesthetic value of the area.
- Develop tree planting and or soil reclamation programs that will also incorporate the organized community groups.
- Create awareness/train staff and the community at large on the need to protect and or conserve the environment.
- Conduct open clinics to address/create awareness and or to treat ailments emanating from the project's activities.
- Provide alternative water sources to the community/institutions to be affected by mining activities.
- Develop employment guidelines at the company in respect to the labour laws.
- Undertake Corporate-social-responsibility like the construction of health facilities around the project sites and support of existing institutions as a way of ploughing back to the host community.
- Quarrying processes pose risks to learners especially young girls who elope with employees while students drop early out of school to seek employment at the mines.
- The purchasing power of the residents shall be improved due to the economic empowerment of the community.
- Residents to be accorded assistance in terms of education, health and incase of calamities.
- Disintegration of families due economic empowerment esp. the women.

 Guiding and counseling programs to be developed to aid students who may intent to drop out of school to join the mines to complete school first being doing so.

Detailed responses from each of the respondents in this category are in appendix 23.

10.4.4 Questionnaire survey responses from Health institutions

The following health institutions responded to the questionnaire

Roka Maweni Dispensary

The following is a summary of the responses from the health institutions:-

- Effect to ground water considering that the people in the area rely on well water
- Air pollution as a result of mining activities may lead to respiratory problems.
- Provide an alternative to the well water for the community
- Ensure proper management of waste
- Boost the health facilities in the areas with medicine and equipment so that they are able to effectively deal with any conditions that may arise.
- The company should give first priority to employ people from the locality before employing people from other places.

Detailed responses from each of the health institutions are in appendix 24.

10.4.5 Questionnaire survey responses from Religious Institutions

The following religious institutions responded to the questionnaire

- Roka Maweni Agape Church-Pst. Dickson Nyamawi Mwaidza
- The Sanctuary of Praise Ministry-Paul C. Mbaru
- Upendo Gospel Planter Ministries Church-Deacon Harrison Ngao Vaya
- Baptist Church-Mishi Stori Chege
- Kajiweni Gospel Planters Church-Bishop. Ambrose Senje Mwayaona

The following is a summary of the responses from the religious institutions:-

- The proposed project will create job opportunities for the residents that will thus enhance their socio-economic lives and the general development of the area.
- Noise from machinery and dust will have a damaging impact on the learners of the area.
- Loss of communal grazing lands will lead to low animal production.
- Dust mitigation mechanisms should be inculcated in the project.
- Construction, repair and or maintenance of the roads in the area and if possible tarmac the access road to the limestone mining sites.
- Develop tree planting and or soil reclamation programs that will also incorporate the organized community groups.

- Provide alternative water sources to the community/institutions to be affected by mining activities.
- Undertake Corporate-social-responsibility like the construction of health facilities around the project sites and support of existing institutions as a way of ploughing back to the host community.
- Residents to be accorded assistance in terms of education, health and incase of calamities.

Detailed responses from each of the religious institutions are in appendix 25.

10.4.6 Questionnaire survey responses from Community Members

The following community members responded to the questionnaire

- Henry Said Wanje
- Gilbert Baya Kadzamba
- Kenga Gona Charo
- Rose Mbala Kitengele
- David Baraka Masha
- Kombe Yeri Cleophas
- Stanley Kitsao Lewa
- Samuel Gunga Ndurya

The following is a summary of the responses from the community members:-

- The proposed project will lead to increased population in the hood and thus enhancement of business activities in the area.
- Water, noise and air pollution due to the mining processes will affect the locals and the living organisms.
- Noise from machinery and dust will have a damaging impact on the learners of the area.
- Limestone mining will lead to depletion of top soils causing land degradation as well as creation of open pits that may be breeding grounds of vectors like mosquitoes.
- Clearance of vegetation to pave way for the proposed project will affect the quality of air and the hydrological cycle that may trigger climate change.
- The mining processes will have adverse impacts on the road network of the area.
- Loss of communal grazing lands will lead to low animal production.
- The mining project may lead to cracking and falling of structures e.g. buildings.
- Insecurity problems may emanate if the company doesn't put proper measures to man or clear bushes in the large tracks of land that they have acquired as thugs may use it as a hiding den.

The proposed project will affect the economy of the local stone cutters and their consumers at the area who depend on the sites acquired by the company.

Detailed responses from each of the community members who responded to the questionnaire are in appendix 26.

10.4.7 Consolidated Views, Issues and/or Concerns as captured in the questionnaires

- The proposed project will create job opportunities for the residents that will thus enhance their socio-economic lives and the general development of the area.
- Infrastructural development as a result of the project will lead to the growth of the area.
- The company being an investor will help in driving the development agenda of the area.
- The community will be able to source building materials locally from the mines.
- The proposed project will lead to increased population in the hood and thus enhancement of business activities in the area.
- Land value is likely to rise in the area due to demand and thus better income for the land sellers though it may also increase landlessness due to thirst for ease money.
- Increased debris and wastes in the hood.
- Water, noise and air pollution due to the mining processes will affect the locals and the living organisms.
- Noise from machinery and dust will have a damaging impact on the learners of the area.
- Mass production of dust and smoke from machines are likely to pollute the environment which may cause health complications among residents and low plant production.
- Limestone mining will lead to depletion of top soils causing land degradation as well as creation of open pits that may be breeding grounds of vectors like mosquitoes.
- Exposure of the land due to the mining processes will actuate soil erosion in the area.
- Clearance of vegetation to pave way for the proposed project will affect the quality of air and the hydrological cycle that may trigger climate change.
- The mining processes will have adverse impacts on the road network of the area.
- The project will destroy the bio-diversity of the area.
- Increased school dropout which may emanate from early pregnancies, created employment opportunities, early marriages and land displacement/migration of families may be witnessed.
- The mining processes will lead to destruction of water catchment areas that are a heritage to the community besides diminishing the water quantity and quality of the area.
- Loss of communal grazing lands will lead to low animal production.

- Displacement of persons to pave way for the proposed mining project will lead to disintegration of families.
- The mining project will lead to cracking and falling of structures e.g. buildings.
- The current serene and tranquil state shall cease once mining processes begin due to noise pollution.
- Insecurity problems may emanate if the company doesn't put proper measures to man or clear bushes in the large tracks of land that they have acquired as thugs may use it as a hiding den.
- The proposed project will affect the economy of the local stone cutters and their consumers at the area who depend on the sites acquired by the company.
- The proposed project will affect us if the company doesn't observe the NEMA guidelines and regulations on the environment.

10.4.8 Measures proposed to be put in place to protect and or conserve the environment as captured in the questionnaire

- Proper waste management at the site to avoid any form of pollution in our environment.
- Minimize on the usage of heavy machinery at the site to reduce on the impact of earth tremors.
- Quarrying activities should not be undertaken near schools and other institutions where the company has acquired land.
- Dust mitigation mechanisms should be inculcated in the project.
- Buffer the community/institutions from the company's activities likely to cause negative impacts in the area.
- Construction, repair and or maintenance of the roads in the area and if possible tarmac the access road to the limestone mining sites.
- Construction of a perimeter wall around the proposed quarry sites.
- Abandoned quarries should be turned into fish ponds.
- Rehabilitate (abandoned) quarries once the mining processes is completed to restore/improve the aesthetic value of the area.
- Develop tree planting and or soil reclamation programs that will also incorporate the organized community groups.
- Create awareness/train staff and the community at large on the need to protect and or conserve the environment.
- Conduct open clinics to address/create awareness and or to treat ailments emanating from the project's activities.

- Provide alternative water sources to the community/institutions to be affected by mining activities.
- Develop employment guidelines at the company in respect to the labour laws.
- Undertake Corporate-social-responsibility like the construction of health facilities around the project sites and support of existing institutions as a way of ploughing back to the host community.
- Respect the rights and demands of the host community.
- NEMA and the Ministry of Health to ensure that the Mombasa Cement Company is doing their work in the area positively in the interest of residents.

10.4.9 The General Concerns, Issues and or observations as captured in the questionnaires

- The proposed project is a great idea likely to benefit the community once the negative impacts are mitigated.
- The proposed mining project will open up the area in terms of development and for many youths who could not manage to complete school may get a form of employment to earn income and improve their living standards unlike the current devastating state.
- Pollution is the greatest concern from the mining processes.
- Quarrying processes pose risks to learners especially young girls who elope with employees while students drop early out of school to seek employment at the mines.
- Roads should be enhanced to ease transportation and minimize road accidents.
- Purchase of land at fair price and returning of land to original owners after rehabilitation.
- The proposed project should create job opportunities for the community especially the youths.
- Security in the area will be enhanced especially when the idle people involved in thug life shall have an alternative source of income.
- The proposed project being a business of the company should also benefit the community.
- The purchasing power of the residents shall be improved due to the economic empowerment of the community.
- Residents of the area should be given priority in terms of employment and any other arising opportunities from the company.
- Residents to be accorded assistance in terms of education, health and incase of calamities.
- Institutions within the area be included in the company's welfare fund.
- Harmonious working relationship between the company and the residents will lead to reaping of dividends to both parties.

- Disintegration of families due economic empowerment esp. the women.
- Guiding and counseling programs to be developed to aid students who may intent to drop out of school to join the mines to complete school first being doing so.
- Transparent agreement between the company and the community on issues/projects towards corporate responsibility to avoid hyped up expectations.
- The Mombasa Cement company has undertaken projects in the area that have already benefited the community which we appreciate and we look towards a positive engagement in all our future dealings.
- It is our hope and desire that MCL will regard our opinions as well as abiding by the NEMA & Ministry of Health's instructions when implementing the proposed project.

11. ENVIRONMENTAL AND SOCIAL MANAGEMENT PLAN

The Environmental (Impact Assessment and Audit) Regulations, 2003 define environmental management plan to mean "all details of project activities, impacts, mitigation measures, time schedule, costs, responsibilities and commitments proposed to minimise environmental impacts of activities, including monitoring and environmental audits during implementation and decommissioning phases of a project". This environmental and social management plan (ESMP) identifies potential impacts from implementation of the proposed coral limestone mining process, outlines measures to be put in place during the implementation, operation and decommissioning phases of the coral limestone mining project to enhance positive impacts and mitigate negative impacts, identifies compliance requirements, training and capability building needs, safeguards implementation, grievance redress mechanism, quarry rehabilitation and decommissioning. More specifically, the ESMP address the following;

- ✓ Company management policies
- ✓ Potential positive social impacts
- ✓ Potential negative social impacts
- ✓ Potential negative environmental impacts
- ✓ Maximization of identified potential positive impacts.
- ✓ Mitigation of identified potential negative environmental and social impacts
- ✓ Environmental management action plans
- ✓ Monitoring for compliance with the provisions of relevant national legislations.
- ✓ Training, capacity development, implementation schedule and related costs.
- ✓ Institutional arrangements for safeguard implementation and reporting.
- ✓ Grievances redress mechanism.
- ✓ Quarry pits rehabilitation and decommission plan

11.1 Management policies

MCL will need to update and document policies to reflect unique requirements of the proposed project that will guide implementation of the proposed coral limestone mining project at Roka and Matsangoni Locations. The policies once updated will be vital in the following ways among others:

The policies once updated will be vital in the following ways among others:

✓ The policies will identify the unique stakeholder mix within the project catchment hence enable management to develop and maintain sound relations with all stakeholders.

- ✓ The policies will enable management identify and fact in unique and project specific measures and structures that will care for the safety, health and welfare of all workers and the neighbouring community to the project site.
- ✓ The policies will provide a broad framework for management to plan for, and put in place, monitoring programmes that will ensure conservation and protection of the environment.
- ✓ The policies will provide an enhanced framework for management to expand its corporate responsibility to the proposed project area and wider project catchment to foster environmental conservation, sustainable utilization of natural and the well-being of the local community.

MCL being an on-going concern already has developed and documented most if not all of these policies. We therefore propose that MCL to update the existing policies by incorporating requirements and needs of the proposed project. The updated policies should therefore capture unique requirements of the proposed project site and its diverse stakeholder mix. The following policies should be updated:-

- a) Environmental Management Policy
- b) Occupational Health and Safety Policy
- c) Local Community Policy
- d) Employment Policy

11.1.1 Environmental Management Policy

The environmental policy to be updated should be one that enables MCL to carry out company activities with the highest regard to the natural environment and sustainable utilisation of environmental resources therein. The policy update should therefore cover the following, among other issues:-

- ✓ All legal requirements that will need to be complied during implementation of the coral limestone mining project.
- ✓ Measures to be put in place to ensure continuous environmental improvement and performance through monitoring of limestone mining activities.
- ✓ Ways to ensure that utilisation of natural resources is optimal with measures in place to ensure resource availability for future generation.

- ✓ Awareness creation to the surrounding community regarding sustainable utilisation of natural resources, protection of sensitive ecosystems and bio-diversity maintenance for communal livelihood.
- ✓ Balancing between natural resource use, environmental conservation and economic development.

11.1.2 Occupational Health and Safety Policy

The Occupational Health and Safety Policy to be updated should enable MCL put in place appropriate measures that will ensure that the health, safety and welfare of all employees of the mining project is cared for; together with the health requirements of the local community The policy should highlight the following, among others:-

- ✓ Handling of heavy mining equipment
- ✓ Quarry mine safety
- ✓ Safety measures required for evacuation of recovered coral limestone.
- ✓ Appropriate safety and rescue equipment to be availed at the mine
- ✓ Emergency procedures and actions at the mine
- ✓ Risk minimization of accidental damage to employees, community and environment
- ✓ Mining equipment maintenance and machine operator proficiency
- ✓ Training in mining safety.

11.1.3 Local Community Policy

The proponent will update local community policy to bring on-board Matsangoni and Roka communities. The updated policy will serve to ensure that the company develops and maintains sound relations with quarry employees and the local community on mutual respect and active partnership. The policy should highlight on ways the proponent should:-

- ✓ Work with the local community to achieve sustainable community development.
- ✓ Promote public awareness in regard to monitoring of developments site; potential environmental consequences to the area and the role of the local community.
- ✓ Propose ways of enhancing information flow from management to the community and employees, and vice visa.
- ✓ Community capacity building.
- ✓ Active engagement of the local community in the project.

11.1.4 Employment Policy

The Employment Policy to be updated by MCL should take into consideration the varying employment needs of the community in the new proposed project site. The policy update should endeavour to protect the local community from unfair competition when it comes to recruitment of workers to work in the mine. The policy update should cover the following, among other issues:-

- ✓ Local community considerations in employment.
- ✓ Training needs for employees.
- ✓ Employment of people with specialized skills.
- ✓ Casual Workers.
- ✓ Compensation, allowances and benefits.
- ✓ Terms of payment and scales.

11.2 Potential social impacts

Implementation of the proposed coral limestone mining activities will potentially result in impacts that will affect the social environment. Social environment refers to the aggregate of social and cultural institutions, forms, patterns, and processes that influence the life of an individual or community. It includes the immediate physical and social setting in which people live or in which something happens or develops. Social environment also includes the culture that the individual lives in, and the people and institutions with whom they interact. The interaction may be in person or through communication media.

11.2.1 Potential positive social impacts

Implementation of the proposed coral limestone mining activity will potentially result in the following positive social impacts:-

- ✓ Employment opportunities
- ✓ Support of existing local businesses
- ✓ Businesses spinoffs
- ✓ Support and development of local institutions
- ✓ Skill enhancement and technological transfer
- ✓ Elaborate corporate social responsibility projects

11.2.1.1 Employment opportunities

Implementation of the proposed coral limestone mining activity has the potential to provide both direct and indirect employment opportunities. Likely direct employment will include security personnel, machine and plant operators, truck drivers, quarry camp staff, site mechanics, bush clearing and ground maintenance personnel among others. To ensure maximum employment returns to the local community, MCL will ensure that sourcing of required personnel is first from the local community. The project also will provide indirect employment opportunities; this will include food outlets who will benefit from clientele drawn from workers at the quarry site, hotels and lodges offering catering and accommodation services, other service providers such as local garages, financial institutions, shop outlets, entertainment joints such as bars and clubs that will draw clients from quarry workers.

11.2.1.2 Support of existing local businesses

Local businesses are likely to benefit from improved purchasing power of people in the area as a result of their remuneration. There is likelihood that there will be more money in the pockets of people who are directly or indirectly employed in the quarry and that part of the money will be spent in the local economy hence benefits local businesses.

11.2.1.2 Businesses spinoffs

The multiplier effect of implementation of the proposed coral limestone mining project is likely to star business spinoffs in the area. Small business such as outside catering, track transport businesses, accommodation businesses and entertainment business are some of the likely incidental businesses to be realized.

11.2.1.3 Support and development of local institutions

Implementation of the proposed project will further open up the area and hence increase the need of supporting and developing local institutions to meet growing demand of services. Increased activities in the area will require that institutions such as local administration, local health institution, and local basic and tertiary learning institutions be further developed and expanded to meet growing demand for services.

11.2.1.4 Skill enhancement and technological transfer

Implementation of the proposed coral limestone mining project will involve the use of heavy mining equipment. The operation, use, servicing and maintenance of the equipment will be by well trained and experienced personnel. The availability of the equipment in the locality will expose local people to their use, servicing and maintenance, through this new skills and knowledge will be imparted. Further skill enhance and knowledge transfer will be realised through attachment and internship program where students and interns can be attached to an

experienced equipment operator for a given period of time to learn how the equipment is operated, serviced and maintained.

11.2.1.5 Elaborate corporate social responsibility projects

Whereas MCL has not started implementing the proposed project on site, the company has started extending its corporate social responsibility (CSR) programme to the area. A number of local primary schools are already benefiting from the project, the company is carrying out extensive rehabilitation of school building and structures and in some cases constructing new buildings and structures to improve infrastructure of local schools. Equally local administration offices have started to receive major facelift. MCL intends to roll out an elaborate CSR programme in the local community that will significantly transform social institutions within the catchment of the proposed project once the proposed project commences.

11.2.2 Potential negative social impacts

Potential negative social impacts likely from implementation of the proposed coral limestone mining activities may include the following:-

- ✓ Diminishing/ reduced local ground water resources
- ✓ Labour influx
- ✓ Traffic and Public Safety from trucks along access road
- ✓ Ponding risks resulting spread of malaria from increased breeding of mosquitoes
- ✓ Injuries and accidents
- ✓ HIV and AIDS and other communicable diseases

11.2.2.1 Diminishing/ reduced local ground water resources

Most local households depend on local hand dug wells for their water supply needs. Whereas the water in most of the wells is saline, it is relied on for domestic uses. Implementation of the proposed project may affect recharge of local aquifer due to reduced vegetation in that area that will reduce rainwater percolation and hence aquifer recharge. Reduced aquifer recharge will gradually reduce the yield of water in the local hand dug wells and hence available water in the well.

11.2.2.2 Labour influx

Implementation of the proposed coral limestone mining project will require both skilled and unskilled labour force. In the event that the required skilled workforce cannot be obtained locally either because of lack of technical skills or capacity, in such a scenario, the required labour force may be sourced outside the project area. In such a scenario, there is a potential

for potential workers together with other people who will be supplying goods and services to the proposed project in the short term to migrate from outside and settle at the project area resulting in a labour influx into the project area. Social risks associated with such labour influx will include the following:-

- ✓ Increased pressure on local accommodation facilities and rent hiking: Sourcing of quarry labour outside the project area will necessitate that they seek for convenient accommodation close to the project site. This will increase pressure on available accommodation facilities. Further due to increased demand for accommodation there may be increase of accommodation prices and crowding out of local residents.
- ✓ Local inflation of commodity prices: Labour influx may result in a significant increase in demand of goods and services at proposed project site and its environs; this may result in local price hikes and/or crowding out of community consumers.
- ✓ Gender-based violence: Mine workers in most mining sites are younger males although more recently young females are now joining the workforce. Based on this it is likely that quarry staff to the proposed project site may be male dominated. Young males who are away from home on the quarrying job will be separated from their family and act outside their normal sphere of social control. This can lead to inappropriate behavior, such as sexual harassment of women and girls, exploitative sexual relations, and illicit sexual relations with minors from the host community.
- ✓ Incidence of child labour and school dropout: The proposed project will potentially increase opportunities for the host community to sell goods and services to the incoming workers. Depending on the nature of the social fabric and individual local family dynamics, such an opportunity can be a temptation to parents who can allow their children to produce and deliver these goods and services at the expense of attending school. This will lead to enhanced school dropout.

11.2.2.3 Traffic and Public Safety from trucks along access road

The public safety of users of the access roads that are off the Kilifi-Malindi Highway to the project site may be affected by the potential increase of traffic to and from the project site during the coral limestone mining period. Considering that the said access roads are all earth roads narrow and with pot holes and that it were meant for light traffic, it is likely that trucks ferrying limestone out of the mining sites will potentially affect public safety of the users of the access roads.

11.2.2.4. Ponding risks resulting spread of malaria from increased breeding of mosquitoes

Poorly drained quarry pits will potentially collect rainwater which becomes potential mosquito breeding grounds. This may result in contributing to breeding of mosquitos that can in turn potentially contribute to the spread of malaria in the area.

11.2.2.5 Injuries and accidents

Open quarry pits pose a risk for injuries and accidents to local community, local livestock and workers. People and livestock can easily fall in unmarked and unsecured quarry pits and injury themselves. The injuries and accidents can be more severe if the open quarry pits are deep and contain stagnant water. In such a scenario, people and livestock that accidently fall in can draw.

11.2.2.6 HIV and AIDS and other communicable diseases

Considering the possibility that quarry workers in most quarry sites are young males who sometimes are sourced outside the project area, sexual interactions between local workforce and services providers with those from outside the project area may contribute to spread of communicable diseases in the project area and or among quarry workers, including sexually transmitted diseases such as HIV and AIDS.

11.3 Proposed enhancement measures of potential positive social impacts Table 16: Proposed measures to enhance positive impacts

Potential positive social	Proposed enhancement measures
impacts	
Employment	- Local people from the project area to be given first priority to benefit
opportunities	in direct employment opportunities.
	- There should be no sourcing of unskilled or semi-skilled labour force
	from outside the project area
	- Local youths, both male and female and local women who form the
	bulk of local labour force to be given utmost priority when sourcing
	quarry labour force
	- Both male and female to be considered in allocating employment
	slots for each gender when sourcing labour force.
	- Maintain records of employees with gender and locality of employees
	working at the quarry site to ensure the ratios are maintained.
Support of	- Local business community to position themselves strategically to be

Potential	Proposed enhancement measures
positive social impacts	
existing local	able to provide required services to the project by making required
businesses	investment prior and during the project period.
Businesses	- Local youths of both gender and women who will benefit from direct
spinoffs	and indirect employment opportunities to invest part of their earnings
	in starting small businesses locally or inject more capital to their
	already existing businesses to scale up them up
Support and	- Local leadership to priorities and communicate to the proponent local
development of	institutions that will require developmental support.
local institutions	- Local primary and secondary schools which can be identified as most
	disadvantaged in terms of infrastructure development to be among
	those to be prioritized for support and development
Skill	- The proponent to provide opportunities for internship to enhance skill
enhancement and technological	development
transfer	- The proponent to provide for student attachment opportunities from
	learners of local tertiary institutions
Elaborate	- The local community leadership to liaise with the proponent to tap
corporate social	into the proponent's corporate social responsibility programme for
responsibility	the locality for maximum possible benefit.
projects	

11.4 Mitigation measures for potential negative social impacts

Table 17: Proposed mitigation measures for potential negative social impacts

Potential negative	Proposed mitigation measures
impact	
Reduced	- To increase local aquifer recharge maintain pockets of vegetation at
availability of	the project area and support tree planting activities in public utility
local ground water	areas outside the project site but within the project catchment
in the area for	- Depth of limestone mining to be far above the local aquifer and a
community use	way from any existing hand dug well and or borehole
	- Existing hand dug well and or boreholes to be maintained and
	rehabilitated to ensure improved water yield
Labour influx	- The proponent to source required labour locally unless expatriates

Potential negative impact	Proposed mitigation measures
P	who are not available locally
	- The labour to be sourced locally to include women and youth of
	both gender
	- Numbers of women employed in the quarry site to be monitored to
	ensure they remain proportionate to those of their male counterparts.
Traffic and Public	- The proponents to ensure all trucks collecting mined coral limestone
Safety	from the quarry or delivering materials and equipment to the quarry
	are mechanically sound, serviceable and meet all the traffic act
	requirements.
	- Drivers driving the trucks to observe the highway code, be
	experienced and licensed to drive such trucks
	- Proponent to liaise with the County Government of Kilifi and the
	National Government to request for expansion, upgrading and or
	maintenance of key access roads that will be used to meet required
	needs.
	- Appropriate safety signs including speed pumps to be erected along
	the said access roads.
	- Local community to be sensitized on the increased traffic use of the
	access road and the need for the community to be vigilant and
	exercise of safety precaution when using the said access roads
Ponding risks	- All quarry pits to be adequately drained to ensure no water stagnates
resulting spread of	when it rainsProponent to check all active and disused quarry pits to ensure no
malaria	water stagnates.All disused quarry pits to be backfilled and rehabilitated as soon as
	recovery of limestone is complete
Injuries and	- The quarry to be safely secured and fenced with a clear entry and
accidents	exit gates that are manned.
	- All active quarry pits to be clearly feasibly marked and manned.
	- There should be no unauthorized access to the quarry pits including
	that of straying livestock from the community or children playing,
	or fetching water.
	- Appropriate information notices and warning signs to be displayed

Potential negative	Proposed mitigation measures
impact	at periphery of quarry to inform and educate local community of on-
	going quarrying activity and required safety measures to be observed.
HIV and AIDS	- Sensitization programs on issues HIV/AIDS for the quarry staff and
	local community to be developed and carried out at the quarry site
	and local community by peer educators.
	- A condom dispenser always stocked with condoms to be availed at
	the quarry site
	- Proponent to arrange for convenient and free voluntary and
	counseling services for quarry workers to be accessed at the quarry
	site and any community members willing to benefit from the
	service.

11.5 Potential negative environmental impacts

11.5.1 Impact identification and predication

The type, scale and location of the proposed project guided the scope of the impact identification. The direct and indirect project-related impacts on the environment and local community and residual impacts were considered during the assessment of impacts. The extent of impact covers the project site, specific project activity at particular period and potentially affected areas beyond the project site. Duration in which the impact takes place is also considered in the evaluation of the impact. The period can be specific to the period of certain activities or could be related to the occupancy period of the project development. Thus, in terms of duration an impact can be viewed as a short, medium, long term impact or permanent. Impact can affect biodiversity partially or completely. For instance only small part of habitat, ecological processes or small population of species can be destroyed by the impact. Thus, magnitude of an impact was evaluated as proportion of the environmental entity affected. The probability of the impact to happen was derived from the frequency of the activity and frequency of impacts. The four characteristics described above were used to synthesise significance of the impact as shown in impact significance assessment criteria (figure 12) that is used to generate the risk assessment matrix (figure 13).

EXTENT

Localized (At localized scale	1		
and a few hectares in extent)			
Study area (The proposed site	2		
and its immediate environs)			
Regional (County and Regional	3		
level)			
National (Country)			
International (Beyond Kenya)	5		
1			

MAGNITUDE

Small and will have no effect on the	0			
environment				
Minor and will not result in an	2			
impact on the processes				
Low and will cause a slight impact	4			
on the processes				
Moderate and will result in process	6			
continuing but in a modified way				
High (processes are altered to the				
extent that they temporarily cease)				
Very high and results in complete	10			
destruction of patterns and				
permanent cessation of the				
processes				

DURATION

Very short (0 – 1 Years)	1
Short (1 – 5 Years)	2
Medium term (5 – 15 years)	3
Long term (>15 years)	4
Permanent	5

PROBABILITY

Highly improbable (<20% chance of	1
occurring)	
Improbable (20 – 40% chance of	2
occurring)	
Probable (40% - 70% chance of	3
occurring)	
Highly probable (>70% - 90%	4
chance of occurring)	
Definite (>90% chance of	5
occurring)	

Figure 12: Impact significance assessment criteria

11.5.2 Methodology used to determine environmental and social risks of the impacts

Determination of environmental and social risks of the impacts involved the identification of potential negative impacts, analysis and evaluation of the negative impacts associated with the proposed project. Potential negative impacts were identified using checklists and matrices as defined by Petra (2009). An impact assessment was carried out to identify where the interactions were likely to occur between the proposed project activity and the receiving environment. Checklists of project activities were used and impact scores were assigned

through consultative approaches, brainstorming sessions, scenario analyses, interviews and prior experience. Expert judgement was used to elicit, distributions, preferences, rankings, comparisons, qualitative information, point values and probabilities as explained by O'Hagan et. al.(2006). Leopold Matrix developed by Leopold et. al (1971) was used to estimate the magnitudes and importance of the potential impacts. The Leopold, Lohani and Thanh methods (Petra, 2009) were used to identify major activities and define areas were attention was mostly required. The resulting information together with available information from baseline data, professional judgement of the assessment team constituted the basis for the environmental and social risks of the identified potential negative impacts.

11.5.2.1 Determination the environmental and social risk of the impacts

The environmental and social risk of each of the identified impact was calculated by multiplying impact consequence by impact probability. Impact consequence is the summation of the extent of the impact, its duration and magnitude as shown in the risk assessment matrix below.

		CONSEQUENCE (Extent+Duration+Magnitude)																			
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
≥	1	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
BILI	2	2	4	6	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40
BAE	3	3	6	9	12	15	18	21	24	27	30	33	36	39	42	45	48	51	54	57	60
RO	4	4	8	12	16	20	24	28	32	36	40	44	48	52	56	60	64	68	72	76	80
□	5	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100

Figure 13: Risk assessment matrix

NOTE 1: Risk = Consequence x Probability

NOTE 2: Consequence = Extent + Duration + Magnitude

NOTE 3: Confidence assessment (low, medium and high) based on combination of available information and expert judgment

Low impact (<30) this impact would not have a direct influence on the decision to implement the proposed project

Medium impact (30-60) the impact could influence the decision to implement the proposed project unless the impact is effectively mitigated

High impact (>60) the impact will have a direct influence on the decision to implement the proposed project

11.5.3 Identified Potential negative Environmental Impacts

Mining is widely regarded as having adverse effects on environment of both magnitude and diversity. Some of these effects include erosion, formation of sinkhole, biodiversity loss and contamination of groundwater by chemical from the mining process in general and open-pit

mining in particular (Monjezi, et.al. .2009). Open-cast mining changes geological, hydrological and geotechnical conditions; it influences the existing ecological system and landscape (Drebenstedt, et.al. 2015). The actual environmental impact of mining will depend of the type of mineral, the mining process utilized, the vulnerability of the area affected and the timescale over which impacts occur (Parliamentary Commissioner for the Environment (2010). The implementation of the proposed limestone mining project will potentially result in environmental impacts that will affect the biophysical environment. The **biophysical environment** includes living things (bio), such as plants and animals, and non-living things (physical), such as rocks, soils and water. The biophysical environment is made up of four parts: the atmosphere, hydrosphere, lithosphere and biosphere. Interactions occur between the four spheres. The **atmosphere** refers to the whole mass of air surrounding the earth. At a local level it refers to the air of a locality. The **hydrosphere** is the portion of the earth that is composed of water in all forms i.e. running water, ice and water vapor. The lithosphere refers to the rocks and soils on the crust of the earth. The **biosphere** is the zone of the earth and adjoining parts of the atmosphere in which plants and animals exist.

11.5.3.1 Potential negative environmental impacts during quarry preparation phase of the proposed limestone mining project

Site preparation activities for proposed limestone mining will include the following:

- ✓ Development of access roads to the areas to be mined
- ✓ Clearing of vegetation on site
- ✓ Construction of quarry camp and other support facilities
- ✓ Assembly of heavy mining equipment

11.5.3.1.1. Development of quarry access roads to the areas to be mined

Accesses roads will be required to access various plots were proposed limestone mining is to be done. This may necessitate connecting the proposed mining site to the nearest access road. Also improvement of some of the existing access roads may be necessary to be able to accommodate increase of vehicular traffic on the roads. Development and improvement of the access roads will require vegetation removal, excavation, removal of overburden, placement of gravel, leveling and compaction. These activities will potential result in negative impacts. Potential negative impacts likely from the development of access roads to the areas to be mined could include:

✓ Loss of site vegetation where the access roads will be developed. Loss of vegetation will translate to reduced local greenery, overall reduction in local carbon sink.

- ✓ Generation of fugitive dust from soil excavation activities, removal of overburden and leveling activities. Generated fugitive dust will potentially negatively affect people using the access road as it could contribute to reduction of local feasibility, vegetation along the access road and adjacent areas as when the dust settles on surfaces of the vegetation it result in smothering of vegetation foliage.
- ✓ Generation of noise and vibration from equipment activity, exaction and compaction works on site. This will potentially contribute to interferences conversation and communication, course annoyance, interfere with local recreation, and negate work performance, thought and concentration.

An assessment of the environmental risk associated with development of access roads at the proposed project site to make developed quarries accessible to move out quarried limestone was informed by the identified potential negative impacts associated with access roads development. The assessment was done using the risk assessment matrix. The confidence of assessment of impacts resulting from quarry access roads development when unmitigated and the resulting environmental risk based on the risk assessment matrix is as tabulated table 18 below.

Table 18: Assessment of environmental risk resulting from quarry access roads development

Extent of impact	1
Magnitude of impact	2
Duration of impact	1
Probability of impact	4
Risk = (Extent + Magnitude + Duration) x Probability	16
Environmental risk of site vegetation clearing	Low impact

The outcome of the assessment of the environmental risk associated with development of quarry access roads at the proposed project site is low. This implies that impacts associated with development of quarry access roads at the proposed project site should not have a direct influence on the decision to implement or not implement the proposed project.

11.5.3.1.2 Clearing of vegetation on site

Clearing of site vegetation will be a pre-requisite to pave way for opening the ground for limestone mining. Vegetation at the proposed project site includes trees, shrubs, herbs, climbers, grasses and sedge. Some of the plots vegetation include food trees such as coconuts. Clearing of the vegetation at the proposed project site will result in loss of environmental and ecological services derived from the vegetation. Also cutting down of

food trees such as coconuts will result in loss of the various economic and social benefits delivered from coconut crop trees. The environmental services that will be lost include reduction in local carbon sink, loss of local shade and loss of local wind break. Ecological services likely to be lost include loss of soil conservation as tree roots bind soil aggregates thus minimizing soil erosion, nitrogen fixing, and windbreak. Potential negative environmental impacts likely to result from vegetation clearing from the proposed project site will include:-

- ✓ Direct loss of local vegetation abundance and biodiversity due to the clearing of vegetation within the proposed project area
- ✓ Direct and indirect loss of fauna abundance and biodiversity through habitat loss resulting from vegetation clearance.
- ✓ Diminishing of local carbon sink resulting in reduced area capacity of carbon sequestration.
- ✓ Overall reduction of flora in the area and overall loss and/or reduction of ecological and economic services derived from the lost floral species.
- ✓ Loss and or reduced foliage for local fauna species that will negatively impact on the growth, reproduction and development of the affected faunal species.
- ✓ Loss of various economic services derived from coconut tree such as source of food (coconut), source of palm wine (mnazi) source of madavu, source of building and thatching materials among many others.

An assessment of the environmental risk associated with vegetation loss from the project site as a result of implementation of the proposed project was informed by the identified potential negative impacts. The assessment was done using the risk assessment matrix. The confidence of assessment of negative impacts to vegetation when unmitigated and the resulting environmental risk based on the risk assessment matrix is as tabulated in table 19 below.

Table 19: Assessment of environmental risk of vegetation loss from project site

Extent of impact	2
Magnitude of impact	8
Duration of impact	4
Probability of impact	5
Risk = (Extent + Magnitude + Duration) x Probability	70
Environmental risk of site vegetation clearing	High impact

The outcome of the assessment of the environmental risk associated with site vegetation clearing and resulting potential negative impacts of vegetation loss from the proposed project site is high. This implies impacts associated with vegetation clearing from the proposed project site could have a direct influence on the decision to implement/ not implement the proposed project.

11.5.3.1.3 Construction of quarry camp and other support facilities

A quarry camp will be constructed as part of the pre-requisite infrastructure before
commencement of mining of the limestone. It is anticipated that the quarry camp will be
secured by perimeter fencing and that it will include among others office spaces, sanitary
facilities, truck parking area, temporally area for minor repairs of trucks, staff canteen, water
storage facilities among others. Potential negative impacts likely to result from the
construction of the quarry camp could include:

- ✓ Loss of vegetation that will be cleared to crate room to construct the camp
- ✓ Generation of fugitive dust from opening up the ground where the camp will be constructed
- ✓ Noise and vibration during the actual construction of the various camp structures and infrastructure. The noise and vibration could be from use of equipment and the actual construction activities.
- ✓ Generation of solid waste from construction activities. Waste likely to be generated includes excavated earth material offcuts of timber, steel and plastic among others.
- ✓ Injuries and accidents from construction activities and use of tools and equipment.

 Injuries and accidents could include falling from height, fractures, cuts, bruises among others.

An assessment of the environmental risk associated with quarry camp construction at the proposed project site was informed by the identified potential negative impacts associated with construction of the quarry camp. The assessment was done using the risk assessment matrix. The confidence of assessment of impacts resulting from construction of the quarry camp when unmitigated and the resulting environmental risk based on the risk assessment matrix is as tabulated table 20 below.

Table 20: Assessment of environmental risk resulting from quarry camp construction

	8 1 j r
Extent of impact	1
Magnitude of impact	2
Duration of impact	1

Probability of impact	3
Risk = (Extent + Magnitude + Duration) x Probability	12
Environmental risk of site vegetation clearing	Low impact

The outcome of the assessment of the environmental risk associated with quarry camp construction at the proposed project site is low. This implies that impacts associated with quarry camp construction at the proposed project site should not have a direct influence on the decision to implement or not implement the proposed project.

11.5.3.1.4 Mobilization of heavy mining equipment at the mining site Mining of limestone at the proposed project site will require use of heavy mining equipment. Such equipment will include bucket excavators, backhoes, bulldozers, often referred to as "dozers," front-end loaders, or simply "loaders," stationary and portable electrical generators, haul trucks, or "haulers," among others. As part of preparation for mining these equipment will be assembled on site. Potential negative impacts of site assembly of the equipment include:

- ✓ Noise disturbance to local neighborhood when the equipment are being mobilized to site.
- ✓ Inconvenience to local access road users due to presence of heavy quarry equipment on local access road during equipment mobilization.
- ✓ Leakage of oil and lubricant from equipment will potentially contaminate local information.

An assessment of the environmental risk associated with quarry equipment mobilization to proposed project site was informed by the identified potential negative impacts associated with their mobilization. The assessment was done using the risk assessment matrix. The confidence of assessment of impacts resulting from equipment mobilization when unmitigated and the resulting environmental risk based on the risk assessment matrix is as tabulated table 21 below.

Table 21: Assessment of environmental risk resulting from quarry equipment mobilization

Extent of impact	1
Magnitude of impact	2
Duration of impact	1
Probability of impact	2
Risk = (Extent + Magnitude + Duration) x Probability	8
Environmental risk of site vegetation clearing Low impact	

The outcome of the assessment of the environmental risk associated with quarry equipment mobilization to the proposed project site is low. This implies that impacts associated with quarry equipment mobilization to the proposed project site should not have a direct influence on the decision to implement or not implement the proposed project.

11.5.3.2 Potential negative environmental impacts during quarry implementation phase of the proposed limestone mining project

Activities that are likely during mining phase of the limestone will include the following:

- ✓ Site excavation and removal of overburden
- ✓ Breaking and loosening of limestone bedrock
- ✓ Loading of mined limestone into trucks
- ✓ Haulage of mined limestone out of the Quarry
- ✓ Impacts from repair and maintenance of quarry equipment

11.5.3.2.1 Site excavation and removal of overburden

Limestone recovery from the site will be by the open cast method; this will involve first site excavation and removal of overburden. Potential negative impacts likely to result will include:-

- ✓ Loss of biodiversity: Excavation and removal of overburden will contribute to loss of site biodiversity. All flora on site will be cleared and removed, also site fauna that depend on site flora for feeding, roosting, and as a habitat and those in affected local soil and limestone rocks will be lost. Potential loss of site biodiversity will disrupt local food chains and food webs.
- ✓ Generation of fugitive dust: Excavation and removal of overburden will potentially result in fugitive dust generation. Such fugitive dust will potentially negatively affect potential receptors such as site mine workers, adjacent homesteads and other neighboring facilities. The fugitive dust can potentially result in throat irritation for site workers and occupants of adjacent homestead, reduce local feasibility, skin irritation, coughing and sneezing.
- ✓ Noise and vibration: Heavy mining equipment which will be used in excavation and stripping the overburden will potentially cause noise and vibration. Also actual equipment activity on site will potentially result in noise and vibration. Mine workers and adjacent neighbors are potential receptors of the noise and vibration. Potential negative effects of the noise and vibration will include loss of comfort and repose

- ✓ *Alteration of local aesthetics*: Excavation and removal of overburden will potentially alter local aesthetics the area will be glaringly open, local beauty will be lost.
- ✓ *Opening ground to erosion agents*: Vegetal removal and stripping of overburden will open the ground to wind and water erosion. The open ground will be susceptible to wind erosion when windy and water erosion during rainy session. Adjacent homesteads and likely to be affected from suspended soil particles as a result of wind erosion.

An assessment of the environmental risk associated with excavation and removal of overburden at the proposed project site was informed by the identified potential negative impacts associated with the activity. The assessment was done using the risk assessment matrix. The confidence of assessment of impacts resulting from excavation and removal of overburden when unmitigated and the resulting environmental risk based on the risk assessment matrix is as tabulated table 22 below.

Table 22: Assessment of environmental risk resulting from excavation and removal of overburden

Extent of impact	2	
Magnitude of impact	6	
Duration of impact 4		
Probability of impact	3	
Risk = (Extent + Magnitude + Duration) x Probability	36	
Environmental risk of site vegetation clearing	Low impact	

The outcome of the assessment of the environmental risk associated with excavation and removal of overburden is medium. This implies that the impact could influence the decision to implement the proposed project unless the impact is effectively mitigated.

11.5.3.2.2 Breaking and loosening of limestone bedrock

Actual quarrying will involve breaking and loosening of the massive limestone bedrock to recover limestone aggregates. The breaking and loosening of the limestone bedrock will be by use of equipment. Potential negative impacts likely to result will include:-

- ✓ Noise and vibration: Breaking and loosening of limestone bedrock will by means of heavy mining equipment. Noise and vibration will be generated from equipment use and the exercise of breaking of the limestone.
- ✓ *Generation of fugitive dust*: Mining activity, coupled with equipment activity on site will be a source of fugitive dust. Wind action on mined loosened limestone material

in an open area devoid of any vegetation to act as wind break is more likely to be blown and hence more fugitive dust in the area.

- Change in local geological, hydrological and geotechnical conditions. Likely environmental geological problem from the open pit mining will be stability of the resulting open pit slopes. Open cast mining result in artificially shaped slope which keep expanding with the increase of mining deep, with a potential to damage the natural balance to the stress and lead to artificial slope deformation, damage and slippage. Also the open cast mining has the potential to alter local hydrological conditions as a result of clearance of site vegetation and removal of overburden this lead to water retention capacity decreased in the area.
- ✓ *Change in local landscape*: The surface mining method that will be used will be the open-cast mining method. This method results in change of local landscapes as borrow pits are generated once the limestone is extracted. The removal of vegetation and excavation of overburden alter the local natural landscape of the affected area.

An assessment of the environmental risk associated with breaking and loosening of the massive limestone bedrock was informed by the identified potential negative impacts associated. The assessment was done using the risk assessment matrix. The confidence of assessment of impacts resulting from breaking and loosening of the massive limestone bedrock when unmitigated and the resulting environmental risk based on the risk assessment matrix is as tabulated table 23 below.

Table 23: Assessment of environmental risk resulting from breaking and loosening of the massive limestone bedrock

Extent of impact	2
Magnitude of impact	4
Duration of impact	5
Probability of impact	3
Risk = (Extent + Magnitude + Duration) x Probability	33
Environmental risk of site vegetation clearing Low impact	

The outcome of the assessment of the environmental risk associated with breaking and loosening of the massive limestone bedrock is medium. This implies that the impact could influence the decision to implement the proposed project unless the impact is effectively mitigated.

11.5.3.2.3 Loading of mined limestone into trucks

The mined limestone will be loaded into trucks by means of front wheel loaders. During loading it is likely that the exercise may result in negative impacts. Some of the potential negative impacts could include:-

- ✓ *Generation of fugitive dust*::Fine particles scoped with the limestone pebbles are likely to be airborne when the pebbles are being emptied from the front wheel loaders into the trucks hence generating fugitive dust. Potential receptors of this fugitive dust will be workers within the quarry and adjacent neighbors to the quarry.
- ✓ Noise disturbance: Equipment activity on site necessary for loading work will potentially result in noise disturbance. Potential receptors of the likely noise to be emitted will include workers in the quarry site and adjacent neighbors.
- ✓ Occupational injuries: Occupational injuries such as slip and falls, skidding, sliding, cuts could potentially occur due to equipment activity on site coupled with the actual quarrying activities.

An assessment of the environmental risk associated with loading of the mined limestone into trucks was informed by the identified potential negative impacts associated with limestone loading activity. The assessment was done using the risk assessment matrix. The confidence of assessment of impacts resulting from limestone loading activity when unmitigated and the resulting environmental risk based on the risk assessment matrix is as tabulated table 24 below.

Table 24: Assessment of environmental risk resulting from loading into trucks of the mined limestone

Extent of impact	1
Magnitude of impact	2
Duration of impact	1
Probability of impact	2
Risk = (Extent + Magnitude + Duration) x Probability	8
Environmental risk of site vegetation clearing	Low impact

The outcome of the assessment of the environmental risk associated with loading of mined limestone into trucks is low. This implies that impacts associated with loading of mined limestone into trucks should not have a direct influence on the decision to implement or not implement the proposed project.

11.5.3.2.4 Haulage of mined limestone out of the Quarry

The mined limestone once loaded into tracks will be hauled from the quarry site via quarry access roads into local feeder loads to the Malindi highway then to Mombasa Cement factory at Vipingo. Limestone haulage will be done by a fleet of dump trucks driving in and out of the limestone quarry pits. The haulage activity is likely to result in negative impacts to the environment. Some of the potential negative impacts will include:

- ✓ Fugitive dust along the quarry access roads, and local feeder roads being used.

 Increased heavy commercial trucks on local roads will potentially result in generation of fugitive dust along the said roads. Potential receptors of this fugitive dust will include other users of the same roads, occupants of homesteads along the said roads, learners and teachers of schools along the said roads, shops and other social facilities located along the said roads.
- ✓ *Noise disturbance* from trucks playing along the said roads is likely to increase with an increase in vehicular activity on the said roads. The noise is likely to be a nuisance to leaners and teachers of schools along the said roads, medical facilities, churches and other places of worship, homesteads and other amenities along the said roads.
- ✓ Accidents and incidents on the said roads due to increased vehicular activity on the roads may be witnessed. Increased road use by heavy commercial vehicles playing in and out of the quarry pits will potential contribute to incidents of local accidents on the said roads.
- ✓ Increase in wear, tear and dilapidation of local road infrastructure due to increased use of the roads by loaded heavy commercial trucks. This will translate to increased costs of maintenance of affected roads. In absence of timely maintenance of affected roads, then motorists using affected roads will have to spend more time on the said roads besides spending more on maintaining their vehicles.

An assessment of the environmental risk associated with haulage of mined limestone out of the quarry was informed by the identified potential negative impacts associated with the activity. The assessment was done using the risk assessment matrix. The confidence of assessment of impacts resulting from haulage of mined limestone out of the quarry when unmitigated and the resulting environmental risk based on the risk assessment matrix is as tabulated table 25 below.

Table 25: Assessment of environmental risk resulting from quarry equipment mobilization

Extent of impact 2	
Magnitude of impact	4
Duration of impact 4	
Probability of impact	3
Risk = (Extent + Magnitude + Duration) x Probability	30
Environmental risk of site vegetation clearing Medium impact	

The outcome of the assessment of the environmental risk associated with haulage of mined limestone out of the quarry is medium. This implies that impacts associated with associated haulage of mined limestone out of the quarry could influence the decision to implement the proposed project unless the impact is effectively mitigated

11.5.3.3 Potential negative environmental impacts during decommissioning phase of the limestone mining project

Activities that are likely during decommissioning phase of the Quarry include the following:

- ✓ Dismantling of quarry camp and removal of support infrastructure
- ✓ Demobilization of all quarrying equipment and machinery
- ✓ Backfilling of open quarry pits
- ✓ Rehabilitation of the quarries

11.5.3.3.1 Dismantling of quarry camp and removal of support infrastructure

Dismantling of quarry camp and all support infrastructures will be carried out at the end of the useful life of the limestone mining activities at the proposed project site. Structures housing site office, sanitary facilities and other structural developments on site will be dismantled and cleared from site. It is likely that the dismantling and removal of these structures will potentially result in negative impacts to the environment. Some of the potential negative impacts will include:-

- ✓ *Generation of noise* which will be a nuisance to neighbors, passersby and workers involved in the decommissioning exercise. Noise will likely be generated from actual demolitions activities and from use of equipment on site during demolition.
- ✓ *Fugitive dust* generation which will be a nuisance to neighbors, passersby and workers involved in the decommissioning exercise. Potential fugitive dust on site will be from demolition activities.

✓ *Generation of waste* including scrap metal, wooden waste, wastepaper, concrete rubbles. If the waste is not appropriately handled, managed and disposed, it can be scattered all over the place thus polluting the local environment.

An assessment of the environmental risk associated with dismantling of the quarry camp and removal of support infrastructure was informed by the identified potential negative impacts associated with the activity. The assessment was done using the risk assessment matrix. The confidence of assessment of impacts resulting from the activity when unmitigated and the resulting environmental risk based on the risk assessment matrix is as tabulated table 26 below.

Table 26: Assessment of environmental risk resulting from dismantling of quarry camp and removal of support infrastructure

Extent of impact	1	
Magnitude of impact	2	
Duration of impact	1	
Probability of impact	3	
Risk = (Extent + Magnitude + Duration) x Probability	12	
Environmental risk of site vegetation clearing	Low impact	

The outcome of the assessment of the environmental risk associated with dismantling of quarry camp and removal of support infrastructure is low. This implies that impacts associated with the activity should not have a direct influence on the decision to implement or not implement the proposed project.

11.5.3.3.2 Demobilization of all quarrying equipment and machinery

At the end of quarrying activities at the proposed project site, all quarry equipment that had been mobilized to the proposed project site will be demobilized out of the site. It is anticipated that equipment demobilization may result in negative impacts to the environment. Some of the potential negative impacts may include:-

- ✓ *Spill of oil and lubricants*, most of the equipment will likely be old, not maintained to date, with defects and leakages here and there which could contribute to leakage of oils and lubricants in the equipment.
- ✓ *Noise disturbance*. Equipment demobilization may also result to noise disturbance to neighbors especially if the equipment will be old and poorly maintained.

An assessment of the environmental risk associated with equipment demobilization out of the proposed project site was informed by the identified potential negative impacts associated with the activity. The assessment was done using the risk assessment matrix. The confidence

of assessment of impacts resulting from the activity when unmitigated and the resulting environmental risk based on the risk assessment matrix is as tabulated table 27 below.

Table 27: Assessment of environmental risk associated with equipment demobilization from site

Extent of impact	1
Magnitude of impact	2
Duration of impact 1	
Probability of impact	2
Risk = (Extent + Magnitude + Duration) x Probability	8
Environmental risk of site vegetation clearing	Low impact

The outcome of the assessment of the environmental risk associated with the activity is low. This implies that impacts associated with equipment demobilization out of the proposed project site should not have a direct influence on the decision to implement or not implement the proposed project.

11.5.3.3.3 Rehabilitation of the quarries

All open quarry pits will be backfilled with remnants of the quarried material first then at the top by the overburden that was kept aside. Backfilling will thus involve use of quarry equipment among other techniques. Thereafter appropriate species of tree seedlings will be planted among other vegetation. The use of equipment in backfilling open pits will potentially result in negative impacts such as noise disturbance and generation of fugitive dust. Potential receptors of noise and fugitive dust will be equipment operators and adjacent neighbors. An assessment of the environmental risk associated with backfilling of quarry pits was informed by the identified potential negative impacts associated with the activity. The assessment was done using the risk assessment matrix. The confidence of assessment of impacts resulting from the activity when unmitigated and the resulting environmental risk based on the risk assessment matrix is as tabulated table 28 below.

Table 28 Assessment of environmental risk resulting from backfilling of open quarry pits

Extent of impact	1	
Magnitude of impact	2	
Duration of impact	1	
Probability of impact	2	
Risk = (Extent + Magnitude + Duration) x Probability	8	
Environmental risk of site vegetation clearing	Low impact	

The outcome of the assessment of the environmental risk associated backfilling of open quarry pits is low. This implies that impacts associated with the activity should not have a direct influence on the decision to implement or not implement the proposed project.

11.6 Proposed mitigation measures for potential negative environmental impacts

Table 29: Proposed mitigation measures for potential negative environmental impacts

Potential negative	nitigation measures for potential negative environmental impacts Proposed mitigation measures
impacts	
Loss of flora	- Limit vegetation removal to actual areas within the proposed
	project site with limestone to be mined only
	- MCL to support planting of trees in public areas such as schools,
	Chief camps, local dispensaries within the project catchment to
	offset overall vegetation loss in the area
	- Back fill and plant trees in all pits where mining is completed
Loss and	- MCL to maintain pockets of vegetation within the proposed
displacement of site	project site where there are no limestone to be mined
fauna	- MCL to maintain pockets of vegetation around the quarry camp
	that can support local fauna habitat need
	- MCL to maintain hedge of vegetation along quarry access roads
	that can support local fauna habitat needs.
	- MCL to support planting of trees in public areas such as schools,
	Chief camps, local dispensaries within the project catchment to
	support local fauna habitat needs
Loss of local	- Coconut trees growing in parcels of land procured by MCL that
coconuts trees cover	do not have limestone deposits that can be mined to be preserved
	- MCL to support local communities to grow coconut trees in their
	private farms to offset overall reduction of coconut trees in the
	area.
Generation of	- Regularly sprinkle water on dusty grounds including quarry
fugitive dust	access roads and active mining areas
	- Maintain a vegetation buffer around the schools, local homesteads
	and other social amenities that border limestone pits.

Potential negative	Proposed mitigation measures	
impacts		
	- Maintain a hedge of trees along all quarry access roads to act as	
	wind break, noise attenuator and trap fugitive dust	
Noise disturbance	- Ensure quarry equipment and machinery are well serviced and	
	maintained as per manufacturer's instructions.	
	- Use noise attenuators such as a hedge of vegetation around active	
	quarry pits and along quarry access roads.	
	- Regularly measure and monitor noise levels to ensure they are	
	maintained within the prescribed limits as provided for in the	
	Environmental Management and Coordination (noise and	
	excessive vibration pollution) (Control) Regulations 2009.	
	- MCL to develop and document a comprehensive environmental	
	noise management and conservation programme that will cover	
	all quarry activities.	
Soil erosion	- Maintain pockets of vegetation including trees to act as wind	
	breaks in areas where limestone will not be mined.	
	- Maintain a vegetation buffer around the schools, local homesteads	
	and other social amenities that border limestone pits.	
	- Plant trees and other vegetation in open areas to minimise	
	exposure of open ground to agents of erosion.	
	- Maintain a hedge of trees along all quarry access roads to act as	
	wind break	
Spills of oils and	- Provide an equipment service and maintenance garage complete	
lubricants	with a service sump and oil/water separator for servicing quarry	
	equipment.	
	- Provide for oil absorbents to aid in cleaning out any spilled oil	
	and lubricants	
Ponding of water in	- Ensure all quarry pits are adequately and effectively drained to	
quarry pits	ensure no collection, stagnation and or ponding of rainwater in	
	the pits when it rains.	
Generation of solid	- Ensure all waste generated is managed and disposed as provided	
waste	for in the Environmental Management and Coordination (Waste	

Proposed mitigation measures
Management) Regulations, 2006.
- Where possible and applicable practice the four Rs i.e. refuse to
generate waste, reduce waste generation, reuse generated waste or
recycle generated waste.
- Provide for receptacles for dropping and collection of waste
- Segregate waste at source appropriately.
- Contract the services of a waste collector, ensure the vehicle used
to collect waste are licensed by NEMA
- Maintain dually filled and completed waste tracking documents
for all waste collected and disposed from the quarry
- Fence off all active quarry pits and disused quarry pits to ensure
no unauthorized person or livestock access the quarry pits.
- Promptly backfill all quarry pits where mining of limestone is
complete.
- Ensure all quarry pits are adequately and effectively drained to
ensure no collection, stagnation and or ponding of rainwater in
the pits when it rains.
- Ensure quarry equipment and machinery are well serviced and
maintained as per manufacturer's instructions
- Ensure only well trained and experience plant and equipment
operators are hired to operate quarry equipment and machinery
- Use alternative routes/feeder roads to reduce number of trucks on
one local feeder road.
- Monitor number of trucks on local feeder roads from and to
quarry
- Use fewer trucks of higher carrying capacity as opposed many
trucks of lower carrying capacity
- Maintain pockets of vegetation within the quarry area to minimise
surface runoff and increase rainwater percolation to improve
recharge of local aquifer.
- Quickly vegetate all areas where mining is completed to reduce

Potential negative	Proposed mitigation measures
impacts	
	soil moisture loss when dry and improve ground water aquifer recharge when it rains. - No mining of limestone close to any existing well or borehole
Dilapidation of local roads	 All trucks in and out of the quarry to strictly adhere to required axial load limits on all roads used. Install weighbridge in the quarry to monitor weight of loaded trucks before they leave the quarry. Upgrade local roads to meet heavy load transportation demand from the quarry Regularly rehabilitate and maintain all local roads being used

117. Environmental Management action plans

Table 30: Biodiversity conservation action plan

Issue/concern	Potential impact	Proposed	Monitoring	Responsibility	Timeframe	Budget estimate
		mitigation measure				
Vegetation removal	 ✓ Loss of local vegetation abundance ✓ Loss of fauna abundance ✓ Diminishing of local carbon sink ✓ Reduced foliage for local fauna ✓ Loss of local fauna habitats 	- Limit vegetation removal to areas to be mined - MCL to support planting of trees in public areas within project catchment - Back fill and plant trees in all pits where mining is completed	 Actual number of trees to offset vegetation loss Check for maintained vegetation pockets within project area Feedback from local community and other stakeholders 	- Top management of MCL - Local MCL site project Manager - Project contractor - MCL Environmental and Safety officer - Assigned MCL employees	From commencement of proposed project and be sustained throughout the life of the proposed project	5, 000, 000
Excavation of overburden	✓ Loss of biodiversity ✓ Fugitive dust ✓ Decrease in water retention capacity in the area ✓ Alteration of local	- Keep aside excavated overburden that is rich in biodiversity for later use in rehabilitation work - Limit	 Physical checks and observation of adherence to mitigation measures Feedback from local community 	 Top management of MCL Local MCL site project Manager Project contractor MCL 	From commencement of proposed project and be sustained throughout the life of the proposed project	1, 000, 000

Issue/concern	Potential impact	Proposed	Monitoring	Responsibility	Timeframe	Budget estimate
		mitigation				
		measure				
	aesthetics ✓ Soil erosion	excavation to areas to be mined only - Sprinkle water regularly to arrest fugitive dust - Maintain	and other stakeholders	Environmental and Safety officer - Assigned MCL employees		
		pockets of vegetation to camouflage the pits and act as wind breaks to minimise soil erosion				

Table 31: Local water resource conservation action plan

Issue/concern	Potential impact	Proposed mitigation	Monitoring	Responsibility	Timeframe	Budget
		measure				estimate
Removal of	- Increased	- Vegetation removal to	- Physical	- Top management	From	1, 000,
vegetation	surface runoff	be limited to only	checking of	of MCL	commencement	000
	- Reduced	areas to be mined	availability of	- Local MCL site	of proposed	
	rainwater	- Maintain pockets of	vegetation in	project Manager	project and be	
	percolation	vegetation in the area	areas not being	- MCL	sustained	
	- Decrease in	in all other areas not	mined	Environmental	throughout the	
	water retention	to be mined	- Tracking of	and Safety officer	life of the	
	capacity in the	- Promptly rehabilitate	promptness of	- Assigned MCL	proposed	
	area	all disused quarry pits	disused quarry	employees	project	
	- Increase local	and plant trees in all	pits	- Local community		

Issue/concern	Potential impact	Proposed mitigation measure	Monitoring	Responsibility	Timeframe	Budget estimate
Soil excavation and removal of overburden	soil moisture loss through evaporation Reduced local aquifer recharge Reduced local water percolation due to loss of local soil barrowing	rehabilitated areas - Limit excavation to quarry pit area only - Avoid excavation in areas with existing hand dug wells and boreholes	- Physical checking of existing hand dug wells and bores to ensure they are not	and other stakeholders - Top management of MCL - Local MCL site project Manager - MCL Environmental	From commencement of proposed project and be sustained throughout the	1.000.000
	fauna that are essential in barrowing local soil to increase soil porosity and by extension improve water percolation - Increase local soil moisture loss through evaporation - Reduced local aquifer recharge	- Rehabilitate all excavated and mined areas promptly once mining is complete	damaged - Tracking promptness of rehabilitation of mined areas	and Safety officer - Assigned MCL employees - Local community and other stakeholders	life of the proposed project	
Open cast mining	- Increased surface runoff	- Prompt rehabilitation of all open cast mined	- checking of existing hand	- Top management of MCL	From commencement	1, 000,000

Issue/concern	Potential impact	Proposed mitigation	Monitoring	Responsibility	Timeframe	Budget
		measure				estimate
	- Reduce local aquifer	areas of the proposed project site	dug wells and bores to ensure	- Local MCL site project Manager	of proposed project and be	
	recharge	- Areas within the	they are not	- MCL	sustained	
	- Damage to local water	proposed project site that have existing	damaged - Tracking	Environmental and Safety officer	throughout the life of the	
	aquifer	hand dug wells and	promptness of	- Assigned MCL	proposed	
	- Reduce	boreholes to be	rehabilitation of	1 ,	project	
	ground water	preserved	mined areas	- Local community and other		
	resource availability in			stakeholders		
	the area					

Table 32: Dust management action plan

Issue/concern	Potential impact	Proposed mitigation	Monitoring	Responsibility	Timeframe	Budget
		measure				estimate
Removal of vegetation	- Opening up ground which becomes susceptible to blowing of local wind that will increase amount of suspended soil particles in the air that will pollute local ambient air - Local air pollution from	 Sprinkle water as often as possible in all open areas devoid of vegetation where there is equipment activity Restrict vegetation removal to only areas to be mined Maintain pockets of vegetation in all areas that will not be mined that are within the project site Promptly rehabilitate 	- Measurement of suspended dust particles (local air quality) monitoring as per the requirements of Environmental Management and Coordination (Air Quality) Regulations 2014	 Top management of MCL Local MCL site project Manager MCL Environmental and Safety officer Project contractor Assigned MCL employees Local community and other 	 Air quality monitoring to be done every three months Quarry rehabilitati on to be continuous throughout the project life 	5, 000,000

Issue/concern	Potential impact	Proposed mitigation measure	Monitoring	Responsibility	Timeframe	Budget estimate
	fugitive dust generation from equipment activity	all mined areas	 Trucking of rehabilitation of mined areas Trucking of planting of trees and other vegetation in rehabilitated areas 	stakeholders		
Ground excavation	 Generation of fugitive dust Local dust pollution 	 Maintain a hedge of trees ten miters wide at the boundary of all mining areas and adjacent homesteads, schools and other public facilities Regularly sprinkle water 	- Air quality monitoring report as per the provisions of Environmental Management and Coordination (Air Quality) Regulations 2014 - Feedback from local community and other stakeholders	 Top management of MCL Local MCL site project Manager MCL Environmental and Safety officer Project contractor Assigned MCL employees Local community and other stakeholders 	- Air quality monitoring to be done every three months (quarterly) - Maintenan ce of hedge of trees to be continuous throughout the project life	5,000,000
Actual mining and recovery of limestone	Emission of cloud of dustPollution of local air	- Maintain a hedge of trees ten miters wide at the boundary of all mining areas and	- Air quality monitoring report as per the provisions	Top management of MCLLocal MCL site project Manager	- Air quality monitoring to be done every three	5, 000, 000

Issue/concern	Potential impact	Proposed mitigation measure	Monitoring	Responsibility	Timeframe	Budget estimate
	quality - Reduced local visibility	adjacent homesteads, schools and other public facilities - Regularly sprinkle water	of Environmental Management and Coordination (Air Quality) Regulations 2014 - Feedback from local community and other stakeholders	- MCL Environmental and Safety officer - Project Contractor - Assigned MCL employees - Local community and other stakeholders	months (quarterly) - Maintenan ce of hedge of trees to be continuous throughout the project life	
Loading of limestone to trucks	Generation of fugitive dust	- Sprinkle water on dusty limestone being loaded t	- Air quality monitoring report as per the provisions of Environmental Management and Coordination (Air Quality) Regulations 2014 - Feedback from local community and other stakeholders	 Top management of MCL Local MCL site project Manager MCL Environmental and Safety officer Project contractor Assigned MCL employees Local community and other stakeholders 	- Air quality monitoring to be done every three months (quarterly) Feedback from local community to be continuous throughout project life	5, 000, 000

Issue/concern	Potential impact	Proposed mitigation	Monitoring	Responsibility	Timeframe	Budget
		measure				estimate
Haulage of the limestone out of the quarry	Generation of fugitive dust along the haulage route	 Sprinkle water as often as possible on all haulage routes used Trucks to be driven in low speed along the haulage routes 	- Air quality monitoring report as per the provisions of Environmental Management and Coordination (Air Quality) Regulations 2014 - Feedback from local community and other stakeholders	 Top management of MCL Local MCL site project Manager MCL Environmental and Safety officer Project contractor Assigned MCL employees Local community and other stakeholders 	- Air quality monitoring to be done every three months (quarterly) Feedback from local community to be continuous throughout project life	5,000,000

Table 33: Noise and vibration management action plan

	abie 33. Muise aii	a vibration manage	<u> </u>		1	T	1
Is	sue/concern	Potential impact	Proposed mitigation	Monitoring	Responsibility	Timeframe	Budget
			measure				estimate
-	Mining	- Noise	- Develop and	- Periodic	- Top management	- Noise	1,000,000
	equipment	disturbance to	implement a	environmental	of MCL	measureme	
	activity on site	workers at the	comprehensive noise	noise	- Local MCL site	nts to be	
-	Loading of	mining site	and vibration	measurements	project Manager	carried out	
	limestone into	- Noise	management plan for	as per	- MCL	biannually	
	trucks	disturbance to	the entire quarry site.	Environmenta	Environmental	- All other	
-	Haulage of	neighbouring	- Periodic noise levels	1 Management	and Safety	mitigation	
	limestone in a	households	measurements as	and	officer	measures to	

Issue/concern	Potential impact	Proposed mitigation	Monitoring	Responsibility	Timeframe	Budget
fleet of trucks in and out of the quarry	- Noise disturbance to neighbouring schools - Noise disturbance to neighbouring social amenities	measure provided for in the Environmental Management and Coordination (noise and excessive vibration) (pollution) Control Regulations 2009. - Mining equipment to be serviced and maintained as per manufacturer's instruction - Noise attenuators such as a hedge of trees of ten meters wide to be maintained between adjacent homesteads, schools and social amenities and active quarry pit Quarry workers to be provided with ear plugs	Coordination (noise and excessive vibration) (pollution) Control Regulations 2009 Feedback from neighbours and other stakeholders	- Project contractor - Assigned MCL employees - Local community and other stakeholders	be put in place from commence ment of the proposed project and be sustained throughout the operational life of the project	estimate

Table 34: Traffic management action plan

	Table 34. Traine management action plan						
Is	sue/concern	Potential impact	Proposed	Monitoring	Responsibility	Timeframe	Budget estimate
			mitigation				
			measure				
-	Increased	- Reduction of	- Appropriate	- Physical	- Road Agency	The proposed	1,000,000

Issue/concern	Potential impact	Proposed	Monitoring	Responsibility	Timeframe	Budget estimate
		mitigation				
		measure				
traffic on local access road - Fleet of trucks on local roads	local road safety concerns for members from local community Safety concerns for children crossing and using local roads - Fugitive dust emission from increased vehicular use of local roads - Increased noise disturbance for institutions such as schools along the local roads	road signs to be erected along affected local roads for safe use of the roads - Sensitization of local community on increase of vehicular traffic on local roads and the need to exercise care and safety while using the roads - Regular maintenance of the local roads to deter off-road driving due to poor road condition - Elect speed pumps along road roads to	checking of the condition of carriage way of the local roads, placement of safety road signs along the road and erection of speed pumps Records of training and sensitization of local community on local road safety Records of cases of accidents, incidents and near misses on local roads Records of water sprinkling along local roads	in-charge of the local roads - County Government of Kilifi - Project contractor - Local community - Individual truck drivers using local roads - MCL top management	mitigation measures to be put in place from the beginning of the proposed project and be sustained throughout the life of the project	

Issue/concern	Potential impact	Proposed	Monitoring	Responsibility	Timeframe	Budget estimate
		mitigation				
		measure				
		deter over speeding Regular sprinkling of water to arrest fugitive dust along affected local roads.	including pictures and frequency charts Ambient dust measurement records - Ambient noise measurement records - Feedback from local community and other			
			stakeholders			

Table 35: Waste management action plan

Issue /concern	Potential negative impact	Proposed mitigation measure	Monitoring	Responsibility	Timeframe	Budget estimate
Waste generation from construction of quarry camp	 Littering and untidiness of the workplace Blockage and clogging of local storm water drainage system 	 All generated waste to be handled, managed and disposed as provided for in the Environmental Management and Coordination (Waste Management) Regulations, 2006 Management to provide waste bins at strategic 	- Physical checking of the workplace	 Quarry Manager MCL Environme ntal Safety and Health Officer Project contractor Assigned 	Prior to commencement of activities at the workplace requires waste management structures to be put in place and be sustained	1, 000, 000

Issue /concern	Potential	Proposed mitigation	Monitoring	Responsibility	Timeframe	Budget
	negative impact	measure				estimate
		position for dropping of waste. - Management to contract a licensed waste collector to collect and safely dispose all generated waste. - Management to ensure any vehicle used to very waste from the facility to disposal site is NEMA licensed.		employees	throughout the lifespan of the project	
Waste generation from day to-day use of quarry camp		 Minimize waste generation, embrace reuse and recycling where possible Provide waste bins at every workstation for dropping of waste Consolidate waste from all waste bins into a transfer station for collection and disposal as per waste management regulations 	 Waste disposal trucking documents Physical checking of the workplace 	 Quarry Manager MCL Environme ntal Safety and Health Officer Project contractor Assigned employees 	Throughout the operational life of the quarry	200, 000
Waste generation from servicing of quarry equipment	 Contamination of workplace with oils and greases Littering of workplace with oil and 	 All oil and grease stained rugs to be collected and dropped in a designated waste bins for appropriate disposal. All used oil filters and air filters from equipment and 	 Waste disposal trucking documents Physical checking of the workplace 	 Quarry Manager MCL Environme ntal Safety and Health Officer 	Throughout the operational life of the quarry	200, 000

Issue /concern	Potential	Proposed mitigation	Monitoring	Responsibility	Timeframe	Budget
	negative impact	measure				estimate
	grease stained	other automobile servicing		- Project		
	rugs	to be collected and		contractor		
		dropped in designated		- Assigned		
		receptacles for latter		employees		
		collection and appropriate				
		disposed.				

Table 36: Oil spills management action plan

T /	D 4 41 1	ion pian	•, •	D 11.11.4	TD: 6	D 1 4
Issue /concern	Potential	Proposed mitigation	monitoring	Responsibility	Timeframe	Budget
	negative impact	measure				estimate
 Servicing of quarry equipment Servicing of trucks Servicing of service vehicles 	- Contaminatio n of local soil from oil spills - Contaminatio n of local ground water resources from oil spills - Burning and destruction of vegetation by spilled oil	- Servicing of all quarry equipment, trucks and service vehicles to be done in a properly constructed servicing garage with appropriate facilities for collection of oil and greases - All collected used oil and greases to appropriately handled and kept in drums Only NEMA licensed used oil handles to dispose the collected waste oil	 Physical examination of the workplace Sampling, testing and analysis of local water quality from local wells and boreholes Local soil sampling, testing and analysis Records of quantities of generated waste oil Records of quantities of disposed waste oil by NEMA licensed waste oil handler Feedback from neighbors 	- MCL top Management - Quarry Manager - MCL Environment al, Safety and Health Officer - Project Contractor - Assigned employees	From commence ment of project implementat ion activities and then throughout the project life	500, 000.

11.8 Environmental monitoring

11.8.1 Noise and excessive vibrations monitoring

The noise levels should be monitored as provided for in the Environmental Management and Coordination (noise and excessive vibration) (pollution) Control Regulations 2009 taking consideration zonation requirements and day and night as shown table 37 below.

Table 37: Maximum permissible noise levels for constructions sites when measurement taken within the facility

	Facility	Maximum Noise Level Permitted (Leq) in dB(A)		
		Day	Night	
i.	Health facilities, educational institutions, homes for disabled etc.	60	35	
ii.	Residential	60	35	
iii.	Areas other than those prescribed in (i) and (ii)	75	65	

Timeframe: Day; 6:01am-6:00pm & Night; 6:01pm-6:00am

Source: Second schedule of the Environmental Management and Coordination (Noise and Excessive Vibration Pollution) (Control) Regulations, 2009.

Further noise and excessive vibration shall be monitoring in line with provisions of Regulation 14(3) that states that any person carrying out construction, demolition, mining or quarrying work shall ensure that the vibration levels do not exceed 0.5 centimeters per second beyond any source property boundary or 30 meters from any moving source. The monitoring is to ensure the maximum permissible limits are not exceeded as shown in the table 38 below.

Table 38: Maximum Permissible Noise Levels for Mines and Quarries

Fac	ility	Limit Value in dB (C) Max
1	For any building used as a health facilities,	109 dB (C)
	educational institutions, convalescent home, old	
	age home or residential building	
2	For any building in an areas used for residential	114 dB (C)
	and one or more of the following purposes:	
	commerce, small-scale production, entertainment,	
	or any residential apartment in an area that is	
	used for purposes of industry, commerce or	

small-scale production, or any building used for
the purpose of industry, commerce or small-scale
Production.

Source: Third schedule of the Environmental Management and Coordination (Noise and Excessive Vibration Pollution) (Control) Regulations, 2009.

11.8.2 Air Quality Monitoring

Monitoring of particulate matter to ensure that the project activities adhere to the Ambient Air Quality requirements at Property Boundary for General Pollutants. Part (b) of the First Schedule of the Environmental Management and Coordination (Air Quality) Regulations, 2014 require that the particulate matter for at a property boundary should not exceed $70\mu g/m^3$. Further air quality monitoring aim will be to ensure that stipulated air quality tolerance limits stipulated in the First Schedule of the Environmental Management and Coordination Act (Air Quality) Regulations, 2014 is not exceeded as shown in table 39 below.

Table 39: Ambient Air Quality Tolerance Limits

Pollutant	Time weighted	Industrial area	Residential,	Controlled
	average		Rural and	areas
			Other area	
Suspended	Annual Average	$360\mu g/m^3$	$140g/m^3$	$70\mu g/m^3$
particulate				
matter				
Respirable	Annual average	$70\mu g/m^3$	50g/m ³	50μg/m ³
particulate				
matter				
P.M _{2.5}	Annual average	$35\mu g/m^3$		
	24 Hours	$70\mu g/m^3$		

Sources: First Schedule of the EMC (Air Quality) Regulations, 2014, for pollutants within quarry sites. The monitoring will ensure emission limits of air pollutants for controlled and non-controlled facilities including mining and quarry is observed as tabulated below.. The table 40 below is an excerpt from the third schedule of the regulations on emission limits for mining and quarry.

Table 40: Emission Limits

Parameter	Emission Limit
Opacity	20%
Particulate (Dust) PM ₁₀ (mg/Nm ³)	400

Sources: Third schedule of EMC (Air Quality) Regulations, 2014

11.8.3 Water quality monitoring

Monitoring of quality of local groundwater resources will be carried out as provided for in the second schedule of the Environmental Management and Coordination (Water Quality) Regulations.2006 Legal notice Number 120 as tabulated in the table 41 below.

Table 41: Water quality monitoring parameters

Parameter Parameter	Results		
	Observed value	Guide value(maximum	
		allowable)	
рН		6.5-8.5	
Suspended solids		30 (mg/L)	
Nitrates-NO ₃		10 (mg/L)	
Ammonia-NH3		0.5 (mg/L)	
Nitrite-NO ₂		3 (mg/L)	
Total dissolved solids		1200 (mg/L)	
E-coli		Nil /100ml	
Floride		1.5 (mg/L)	
Phenols		Nil (mg/L)	
Arsenic		0.01 (mg/L)	
Cadmium		0.01 (mg/L)	
Lead		0.05 (mg/L)	
Selenium		0.01 (mg/L)	
Copper		0.05 (mg/L)	
Zinc		1.5 (mg/L)	
Alkyl benzl sulphonates		0.5 (mg/L)	
Permanganate value		1.0 (mg/L)	

Source: The Environmental Management and Coordination (Water Quality) Regulations.2006

11.8.4 Solid waste disposal monitoring

Monitor the type of solid waste generated, quantity of solid waste generated, frequency of collection and disposal, where the waste is disposed and proof of waste tracking documents

in the format provided in FORM III schedule one of the Environmental Management and Co-Ordination (Waste Management) Regulations 2006. This monitoring is to be done monthly.

11.9 Training and capacity building

The following training and capacity building is proposed:-

- Sensitization of the proponent and contractor (s) on the importance of the ESMP, its contents, how it is applied and who is responsible for the implementation of each part of the ESMP.
- Training and capacity building for quarry employee on the importance and proper use of PPEs while at the workplace.
- Training and capacity building for management staff and all quarry employees on acceptable waste management practices.
- Training and capacity building of quarry site occupational safety and health committee on quarry site occupational safety and health requirements and individual safety obligations.
- Training and capacity building of site first aid.
- Training and capacity building on quarry site fire safety
- Sensitization on HIV and AIDS and other communicable diseases

11.10 Institutional arrangements for safeguard implementation and reporting 11.10.1Institutional arrangement

The responsibility of implementation of the safeguards is vested on Mombasa Cement Limited who is the project proponent while the National Environment Management Authority (NEMA) ensures compliance through enforcement. NEMA will coordinate with relevant lead agencies to ensure compliance and enforcement of the ESMP. There will be periodic site visits by relevant lead agencies coordinated by NEMA to assess compliance. Inspection reports of the outcome of the site visits will be prepared by the lead agencies/NEMA and served to the proponent for implementation. The proponent will be required to prepare periodic monitoring reports and annual environmental audit reports and submit these reports to NEMA. Further the proponent will be required to promptly respond to NEMA improvement orders by compiling a report on the issues raised in the orders. The contractor who will be constructing structures on site and be involved in actual quarry of the coral limestone will be required to prepare monthly progress reports and submit the progress reports to the proponent on the contractor's contractual obligations on safeguards implementation responsibilities specified in the ESMP. The contractor will be supervised on

the ground directly by the proponent. The proponent will oversee the implementation of the ESMP.

11.10.2 Reporting obligations

The following reports will be prepared:

- ✓ Monthly progress reports by the contractor on the implementation status of every obligation of the contractor on safeguards implementation specified in the ESMP. These monthly reports will be submitted by the contractor to the Proponent.
- ✓ Periodic monitoring reports to be prepared by the proponent and submitted to NEMA. Specifically; quarterly air quality monitoring report, water quality monitoring reports and biannual noise and vibration monitoring reports.
- ✓ Initial Environmental and Social Audit report to be prepared by the proponent and submitted to NEMA in the first year of operation of the project to confirm the efficacy and adequacy of the ESMP.
- ✓ Self-environmental and social audit report to be prepared annually by the proponent and submitted to NEMA to report on the progress of implementation of the ESMP. The first self-environmental and social audit reports will be prepared one year after submission of the initial environmental and social audit report.
- ✓ Reports responding to NEMA improvement orders to be prepared by the proponent and submitted to NEMA as and when such improvement orders are issued.

11.10.3 Quarry rehabilitation monitoring

Monitoring of progress in quarry pits rehabilitation will be done on a continuous basis. Once an active quarry pit is exhausted and confirmed that mining of limestone is complete. It will be required that backfilling and rehabilitation of the disused quarry pits to begin immediately. All disused quarry pits will be monitored continuously to ensure timely rehabilitation.

11.11 Quarry rehabilitation plan

Quarry rehabilitation is returning the quarried land to a different and usually productive use; it is thus the return of the land to a useful condition as opposed to leaving it as a wasteland.

11.11.1 Rehabilitation procedure

Rehabilitation procedure will involve:-

- ✓ Re-spreading and contouring of topsoil materials and stored overburden materials.
- ✓ Stabilization of battered slopes and grassing in completed and restored extraction areas to create a free draining and stable landform.

✓ Monitoring of re-vegetation to ensure the success of the rehabilitation.

Key principles of rehabilitation include:

- ✓ Reinstallation of topsoil to ensure the soil can be used for agricultural or other uses.

 This may require the topsoil to be mixed with organic material or a soil conditioner.
- ✓ Appropriate vegetation cover undertaken using appropriate low-seeding grass species. Topsoil and re-grassing should be undertaken during rainy season to maximise on growth.
- ✓ Development of a free draining stable landform.
- ✓ The removal of all quarry operating machinery, equipment and buildings at the conclusion of all extraction activities.
- ✓ Maintaining the site through controlling weeds and grazing, as appropriate.
- ✓ Monitor and where necessary, maintain rehabilitated areas to ensure they are functioning appropriately post-rehabilitation for a period of 24 months.

Rehabilitation planning that is integrated with extraction sequences will ensure rehabilitation can commence, in areas where extraction activity has concluded. This will ensure that vegetation can be established, or a return to other land use (e.g. pasture), as soon as possible rather than leaving a disused quarry area on part of the Site. It also ensures that rehabilitation effort is not wasted on areas which will be disturbed again later.

11.11.2 Quarry rehabilitation works

Quarry rehabilitation works to be undertaken after the completion of the extraction of the coral limestone will include:

- ✓ Removal of all fixed and mobile plant.
- ✓ Removal of all temporary and permanent structures unless required for future use.
- ✓ Removal and appropriate disposal of all waste materials.
- ✓ Demolition of all concrete structures, including quarry office, sanitary facilities and weighbridge.
- ✓ Backfilling of all open pits
- ✓ Levelling of bunds and overburden stockpiles.
- ✓ Planting of appropriate vegetation including trees
- ✓ Caring, maintaining and monitoring of the planted trees and other vegetation to ensure growth and development to maturity and hence success of the rehabilitation.

Table 42 is the rehabilitation action plan

.

Table 42: Quarry pit rehabilitation action plan

Table 42: Quarry pit rehabilitation action plan				
Activity	Equipment and tools	Actors	Timeframe	
Backfilling	- Excavators	- Quarry site manager	- Backfilling of quarry pits to begin immediately	
	- Caterpillars	- Quarry supervisors	quarrying is completed in a particular quarry pit.	
	- Dumpers	- Foremen	- Before a new quarry pit is opened, backfilling of the	
	- Shovels	- Quarry workers	old one should be completed first	
	- Spades			
Compacting	- compactor	- Quarry site manager	Compaction of backfilled material to be continuous	
	- compressor	- Quarry supervisors	as backfilling is being done	
		- Quarry workers		
Leveling and	- Leveler	- Quarry site manager	Leveling and landscaping to be done continuously	
landscaping	- Rakes	- Quarry supervisors	once backfilling and compaction is complete.	
	- Harrower	- Foremen		
	- Shovels	- Quarry workers		
	- Spades			
	- Wheelbarrows			

Activity	Equipment and tools	Actors	Timeframe
Vegetation/tree	- Hoes	- Quarry site manager	- Tree planting to begin immediately once reveling
planting	- Spades	- Quarry supervisors	and landscaping is complete.
	- Forked jembes	- Foremen	-Selection of appropriate tree species to be done in
	- Rakes	- Quarry workers	consultation with the Forest Service Kilifi Office.
	- Watering cans		- Tree planting to be done continually in all
	- Wheelbarrows		backfilled, compacted, leveled and sites.
			- Continues watering of planted tree seedlings to be
			done.

11.12 Grievance redress mechanism

11.12.1 Definition and purpose

This Grievance redress Mechanism (GRM) is defined as organizational system and resources established as part of the EMP for the implementation of the proposed coral limestone quarrying project to receive and address concerns about the impact of the implementation of the proposed mining project on any stakeholder (persons, groups or communities). The stakeholder input handled through this GRM system and procedures are called "grievances," "complaints," or "feedback," This GRM is intended to be accessible, collaborative, expeditious, and effective in resolving concerns raised by any stakeholder on the implementation and operation of the proposed coral limestone mining project through dialogue, joint fact-finding, negotiation, and problem solving. This GRM will be the "first line" of response to stakeholder concerns that have not been addressed and or prevented by proactive stakeholder engagement.

11.12.2 Formation

There is a need for the formation and establishment of a GRM to address grievances that may arise during the implementation and operation of the proposed coral limestone mining project. This need has been necessitated by the fact that currently there is no GRM to address grievances that may arise during the project cycle. There is need therefore to establish this GRM as part of the EMP implementation process to ensure transparency and accountability where an individual, a group or a community is aggrieved by the implementation of aspects of the proposed project. Formation of the GRM will entail formation of a committee at the local level (project implementation level).

11.12.3 GRM Committee Members

It is proposed that there be one level of this grievance redress process; the level will have a committee established with defined membership. The level will be at the local (project implementation level). The GRM committee will comprise of experienced and competent persons able to command the respect of affected persons, groups and communities. Membership of the GRM Committee at the local level will be as follows:-

- ✓ Member of County Assembly, Matsangoni Ward (or appointed representative).
- ✓ Ward Administrator Matsangoni Ward (or appointed representative).
- ✓ Liaison Officer MP's Office Kilifi North Constituency representing Matsangoni Ward

- ✓ Chiefs of Roka and Matsangoni Locations
- ✓ Assistant Chiefs of Roka Sub-Location, Chumani Sub-Location, Uyombo Sub-Location, and Matsangoni Sub-location
- ✓ Four members (two male and one female) to represent Nyumba Kumi from each sublocation
- ✓ Four Members (two male and two female) to represent Wazee Wa Mtaa from each sub-location
- ✓ Four youth representatives (two male and female female) from each sub-location
- ✓ Two representative of people with disability
- ✓ Two representative of civil society (from a civil society active in the project area)
- ✓ Three members from the project proponent

The members will select the Chair Person and the Secretary for the Committee.

11.12.4 Mode of Communication

The grievances will be submitted to the Grievance Redress Committee at the local level in any of the following ways:-through SMS, written letter, email or raise the grievance in a local meeting where the grievance will be captured in the form of minutes to be forwarded to the local Grievance Redress Committee.

11.12.5 Process

When there is a grievance at the project area, it is proposed that the affected individual(s), affected group(s), or affected community will be required to forward complaints to the local GRC. The local GRC will be required to record the grievances and call a meeting of the committee to resolve the grievances. The next step in the process will be for the GRC to meet and resolve each grievance forwarded to them at the project community level 7-10 working days of receiving the grievance.

11.12.6 Information Awareness

To ensure appropriate dissemination of information, transparency and accountability, it is proposed that this grievance redress mechanism procedure be printed in both English and Swahili and posted on a notice board at the project site, Chiefs and Assistant Chiefs Offices and MCA's Office.

11.12.7 Record keeping

All submitted complaints will be captured in a register or a project file at the local project level by the GRC. This file should always be in the custody of the GRC. The status of the grievances submitted and the grievance redress at the site will be reported on a regular basis to the affected persons as soon as it is practically possible as well as other stakeholders.

11.13 Decommissioning plan

Decommissioning of the project will involve terminating project operations, dismantling of all project equipment and allied infrastructure and rehabilitating the site to the original status. Before decommissioning will be done, the Project Management will communicate in writing to the National Environment Management Authority stating their intension to decommission and provide a detailed decommissioning plan for approval.

13. CONCLUSIONS AND RECOMMENDATIONS

13.1 Conclusions

The following are some of the conclusions drawn from the assessment findings of the proposed coral limestone mining project by Mombasa Cement Limited at the proposed project site.

- ✓ Mombasa Cement Limited the proponent of the proposed project site has procured all the plots of the proposed project site. The titles of all the plots of the proposed project site are in the name of the proponent.
- ✓ The proponent has obtained change of user from agricultural to industrial (stone cutting and mining) of some of the plots of the proposed while others the change of user is yet to be processed.
- ✓ Within Roka Maweni area, the neighborhood of the proposed project site and the wider catchment of the proposed project, there are many active quarries extracting coral limestone building blocks using machine cutting technology.
- ✓ Fugitive dust is evident from the activities of existing coral limestone building blocks a clear indication that dust pollution will be of concern from the proposed project.
- ✓ There are hand dug wells in some of the plots of the proposed project site and in the neighboring plots. Water in these wells is for domestic use by local community. The quality of the water in the wells is mainly saline.
- ✓ Some of the plots of MCL for the proposed project site are adjacent to schools such as that next to Uyombo Girls Secondary School.
- ✓ Local roads serving the proposed project site such as Roka Maweni Beach Road are maintained by the County Government of Kilfi.
- ✓ Coral limestone outcrops are evidently visible on the surface of some of the plots of the proposed project site within no or minimum overburden.
- ✓ A larger proportion of the plots of the proposed project site have vegetation cover that range from grasses, to shrubs to trees.
- ✓ The proposed project is likely to have negative impacts to the biophysical and social environment. There is appropriate technology and other measures that can be used to appropriately mitigate the potential negative impacts to acceptable national standards.
- ✓ Monitoring of environmental parameters will be important throughout the project cycle.

✓ Continuous stakeholder engagement will be necessary to ensure emerging stakeholder issues and concerns are timely addressed throughout the project cycle.

13.2 Recommendations

The following recommendations are suggested:

- ✓ The project proponent, Mombasa Cement Limited to be patient and wait until the EIA
 Process is concluded and should only begin implementation of the proposed project when
 the National Environment Management Authority issues an Environmental Impact
 Assessment License to the project proponent for the implementation of the proposed
 project.
- ✓ Mitigation measures proposed to be fully implemented and monitored to ensure environmental protection and sustainability once the proposed project is licensed for implementation.

LIST OF REFERENCES

- Almagi, D., Sondo, V.A. and Ertel, J. (2007). Constrains to environmental impact assessment practice: a case study of Cameroon. *Journal of Environmental Assessment Policy and Management* 9 (3), 357-380.
- Braithwaite CJR (1984). Depositional history of the late Pleistocene limestones of the Kenya Coast. *Geological Society of London*. 41(4):685-99.
- Caswell P.V (1956) Geology of Kilifi-Mazeras No. 34 Geology Survey Kenya
- Caswell PV., (1953). Geology of the Mombasa-Kwale area. Geological Survey of Kenya Report. 24:69.
- CEC 1985. On the assessment of effects of certain public and private projects on the environment. Official Journal L175, 5 July
- Charbonnier P (2001) Management of mining, quarrying and ore-processing waste in the European Union. BRGM service EPI, France
- Daughton, C.G and Ternes T.A, (1999). Environmental Health Perspectives, 107, 907.
- ECA 2005. Review of the Application of Environmental Impact Assessment in selected African Countries. Addis Ababa: ECA. www.uneca.org/eca_programmes/sdd/documents/eia_book_final_sm.pdf.
- Elliot, M and Thomas, I. 2009. Environmental Impact Assessment in Australia, 5th edn. Annandale: The Federation Press.
- Embleton BJ and Valencio DA. (1977). Paleomagnetism and the reconstruction of Gondwanaland. *Tectonophysics*; 40:1-12.
- Environmental Protection Agency (EPA). 1993. Control of Volatile Organic Compound Emissions from Batch Processes. EPA453/R-93-017. Washington, DC: US EPA, Office of Air Quality.
- Folchi R (2003) Environmental Impact Statement for Mining with Explosives: A Quantitative Method, I.S.E.E. Paper presented at the 29th Annual Conference on Explosives and Blasting
- Glasson J., Therivel R. and Chadwick A., (2012) Introduction to Environmental Impact Assessment Fourth Edition, Milton Park, Abingdon, Oxon.
- Glasson, John. Therivel, Riki and Chadwick, Andrew (1994) *Introduction to Environmental Impact Assessment*. London
- GoK- Constitution of Kenya 2010

- Government of Kenya 2006 Environmental Management and Co-ordination (Waste Management) Regulations, 2006, *Government Printer Nairobi*, 2006
- Government of Kenya Environmental Management and Co-ordination ((Noise and Excessive Vibration Pollution) (Control) Regulations 2009. *Government Printer Nairobi*, 2009.
- Government of Kenya Environmental Management and Co-ordination (Water Quality) Regulations, 2006, *Government Printer Nairobi*, 2006.
- Government of Kenya Environmental Management and Co-ordination (Water Quality) Regulations, 2006, *Government Printer Nairobi*, 2006.
- Government of Kenya, 2016. The Mining Act.
- Government of Kenya, Environmental Management and Co-ordination Act No. 8 of 1999.

 Government Printer Nairobi.
- Government of Kenya, The Employment Act 2007; Government Printer, Nairobi 2007
- Government of Kenya, The Labour Institutions Act 2007 Government Printer, Nairobi 2007
- Government of Kenya, The Land Act 2012, Government Printer Nairobi 2012.
- Government of Kenya, the Occupational Safety Act 2007 Government Printer, Nairobi 2007.
- Government of Kenya, the Public Health Act. Government Printer, Nairobi.
- Government of Kenya, the Water Act, 2016, Government Printer.
- Government of Kenya, The Work Injuries Benefits Act 2007. *Government Printer*, Nairobi 2007
- Government of Kenya; Environmental (Impact Assessment and Audit) Regulation. *Government Printer* Nairobi 2003.
- Hokel A.D et al. (1984) Geology and Mineral Resource of the Southern Coast Kenya, Geology Survey. 151-159
- Horkel, A., Niedermayr, J.K., Wachira, J.K., Pohl, W., Okelo, R.E. and Nauta, W.J. (1979). Geology of the Taita Hills area. Rept. Geol. Surv. Kenya, No.102.
- https://weather-and-climate.com/average-monthly-Rainfall-Temperature-Sunshine-in-Kenya
- IAIA. (2009). What is Impact Assessment? Fargo, ND:IAIA.
- Jay, S., Jones, C., Slinn, P., Wood, C., 2007. Environmental impact assessment: retrospect and prospect. *Environmental Impact Assessment Review*. 27, 287-300.
- Leopold, L. B. (1971). A procedure for evaluating environmental impact (Vol. 645). US Dept. of the Interior.
- Moorman, J.L and Ge, Z.2007. Promoting and strengthening public participation in China's Environmental Impact Assessment process: comparing China's EIA law and US. NEPA. Vermount Journal of Environmental LAW 8, 281-335.

- Morara, M., Okello, N., Kuhanwa, Z., Douven., W., Beevers, L. and Leentvaar, J. (2011). The importance of context in delivering effective EIA: case studies from East Africa, *Environmental Impact Assessment Review* 31 (3), 286-96.
- O'Hagan, A., Caitlin, E., Buck, C. E., Daneshkhah, A., Eiser, J. R., Garthwaite, P. H., Jenkinson, D. J., Oakley, J. E. and Rakow, T. (2006) Eliciting Distributions Uncertainty and Imprecision, in Uncertain Judgements: Eliciting Experts' Probabilities. Chichester: John Wiley and Sons, Ltd. doi: 10. 1002/0470033312.ch7.
- Onyancha, C., and Nyamai, C., (2014). Lithology and Geological Structures as Controls in the Quality of Groundwater in Kilifi County, Kenya. *British Journal of Applied Science & Technology*, 4(25):3632-3643.
- PETRA, Cosmin. "The specific methods use for identifying environmental effects and impacts." Scientific Bulletin of the" Petru Maior" University of Targu Mures 6 (2009): 208.
- Pohl W and Horkel AD. (1980). Notes on the geology and mineral resources of the Mtito Andei Taita Area (Southern Kenya). *Mitt, oesterr. geol.* Ges. 73:135-52.
- Sadler B. (1996). International study of the effectiveness of environmental assessment, Final report. Ottawa: Canadian Environmental Assessment Agency
- Technique. Northville, Tennessee, USA Jimeno LC, Jimeno LE, Carcedo FJA (1995) Drilling and blasting of rocks. Geo-mining Technological Institute of Spain, pp 345–351
- Wood, C. (1995). *Environmental Impact Assessment. A comparative review*. John Wiley & Sons. Inc., New York. NY. USA.
- Wood, C. 2003. Environmental Impact Assessment: a comparative review, 2nd edn, Prentice Hall.